EFFECTS OF MUSCULOSKELETAL AND SENSORY
DEGRADATION DUE TO AGING ON
THE BIOMECHANICS OF SLIPS AND FALLS

by

THURMON E. LOCKHART, B.S.I.E., M.S.I.E.

A DISSERTATION

IN

INDUSTRIAL ENGINEERING

Submitted to the Graduate Faculty
of Texas Tech University in
Partial Fulfillment of
the Requirements for
the Degree of

DOCTOR OF PHILOSOPHY

Approved

Accepted

May, 2000

ACKNOWLEDGMENTS

I would like to first thank my advisor, Dr. Jeffrey C. Woldstad , for introducing me to the interesting area of slips and falls, and his enduring guidance and encouragement.

I also extend my sincere thanks to the committee members, Drs., M.M. Ayoub, J.D. Ramsey, Roger James, and James L. Smith for their invaluable comments and encouragement.

My appreciation is also extended to Mr. PingShan, Lee for volunteering his time and effort during the experimentation.

Finally, this dissertation is dedicated to my wife Olivia, and my children, who have helped me along the road less traveled.

TABLE OF CONTENTS

ABSTRACT	vii
LIST OF TABLES	ix
LIST OF FIGURES	xii
1. INTRODUCTION	1
1.1 Rationale	1
1.2 Research Objectives	6
1.3 Need for the Study	9
2. LITERATURE REVIEW	10
2.1 Biomechanics of Human Gait	10
2.1.1 Function of Gait	11
2.1.2 The Process of Walking	12
2.1.3 Gait Parameters	17
2.1.4 Trajectory of the Total Body Center of Gravity	29
2.1.5 Balance and Posture in Human Gait	49
2.2 Location of Anatomical Center of Gravity of the Body	53
2.2.1 The Direct Approach	53
2.2.2 The Indirect Approach	55
2.2.3 Center of Gravity Modeling Method	77
2.3 Tribology	80
2.3.1 Coefficient of Friction (COF)	81
2.3.2 Static versus Dynamic COF	87
2.3.3 Friction Measurement	88
2.3.4 Slip Resistance Measuring Device	92
2.4 The Psychophysical Approach	96
2.4.1 Perception of Slipperiness	96
2.5.1 Sensory Input	101

2.5.2 Response Selection	105
2.5.3 Response Execution	105
2.6 Epidemiology of Slip and Fall Accidents	106
2.6.1 Epidemiology of Slip and Fall Accidents of Older Individuals	108
2.7 Summary	113
 3. METHOD	 116
3.1 Subjects	116
3.2 Apparatus	116
3.2.1 Simulated Floors	116
3.2.2 Contaminants	118
3.2.3 Motion Analysis System	118
3.2.4 Bertec Force Plate and Labview Interface	118
3.2.5 Fall Arresting Rig	118
3.2.6 Slip Resistance Tester	118
3.2.7 NeuroCom NeuroTest System	119
3.2.8 Force Transducer (Chatillon DFGS-R-500)	119
3.2.9 Remote Controlled Floor Changer	119
3.2.10 Container	119
3.3 Experimental Variables	121
3.3.1 Independent Variables	121
3.3.2 Dependent Variables	121
3.3.3 Sensory Organization Test and Muscle Control Test Scores	134
3.3.4 Maximal Isometric Strength	135
3.4 Procedure	135
3.4.1 Familiarization Session	135
3.4.2 Protocol	139

3.5 Data Analysis	141
3.5.1 ANOVAs	141
3.5.2 Correlation Analysis	143
3.5.3 Regression Analysis	143
4. RESULTS AND DISCUSSION	145
4.1 Treatment of Data	145
4.2 ANOVA Results	145
4.2.1 Step Length (SL)	145
4.2.2 Step Length Index (SLI)	152
4.2.3 Heel Velocity (Horizontal)	156
4.2.4 Horizontal COGV Before Heel Contact	161
4.2.5 Horizontal COGV After Heel Contact	166
4.2.6 Vertical COGV After Heel Contact	171
4.2.7 Velocity of COFV _{diff}	176
4.2.8 RCOF	179
4.2.9 ARCOF	184
4.2.10 Slip Distance (SD)	188
4.2.11 Slip Distance I (SDI)	193
4.2.12 Slip Distance II (SDII)	198
4.2.13 Sliding Heel Velocity	203
4.2.14 Heel Acceleration	207
4.2.15 Velocity of COG During Slip	211
4.3 Correlation Analysis	215
4.4 Regression Analysis	215
4.5 SOT and MCT	219
4.5.1 Sensory Organization Test	219
4.5.2 Muscle Control Test	219
4.6 Maximal Isometric Strength	219

4.7 Slip and Fall Classification	224
5. CONCLUSIONS AND RECOMMENDATIONS	227
5.1 Conclusions	227
5.1.1 Principal Experimental Findings	227
5.2 Final Remarks	230
5.3 Recommendations for Future Research	231
REFERENCES	232
APPENDICES	249
A. PERSONAL DATA FORMS	250
B. CONSENT FORM	252
C. SPECIAL INSTRUCTIONS FOR SUBJECTS	254
D. PILOT TEST	256

ABSTRACT

Injuries associated with slip and fall accidents continue to pose a significant problem to industry, both in terms of human suffering and economic losses. Although much has been learned over the last few decades about the deterioration of muscular strength, gait adaptations and sensory degradation among older individuals, still little is known about how these intrinsic changes affect biomechanical parameters of slip and fall accidents among the aging workforce. The objective of this study was to closely investigate the process of initiation and recovery of inadvertent slips and falls. The specific aim of the proposed research was to investigate the changes in the biomechanical parameters of walking and ground reaction forces due to intrinsic deficits associated with increase in age. More specifically, how deterioration of muscular strength and sensory degradation among older individuals affect biomechanical parameters of slip and fall accidents under normal and abnormal conditions.

The investigation compared biomechanical parameters of walking in three age groups; (18-30 years), (35-59 years), and (65 years or over). Biomechanical parameters included; step length, heel velocity, required coefficient of friction, slip distance, and position and velocity of center of gravity of the whole body during heel contact phase of the gait. These parameters were measured utilizing force platforms, a 3-D motion analysis system, and a fall arresting rig. To determine the position and velocity of center of gravity during heel contact phase of the gait, a 3-D link (14) segment model was utilized. Walking surfaces included oily vinyl tiles (DCOF-0.08) and outdoor carpet (DCOF-1.80). Subjects walked according to their natural cadences. A sensory organization test was also performed to obtain information concerning the subject's proprioceptive, visual, and vestibular systems. These sensory components were measured using an Equitest Posturography Platform. In addition, isometric strength test was performed (using a force transducer) to obtain information concerning the subject's over-all strength.

The results indicated that younger subjects slipped as often as the elderly subjects, however, the recovery process of older individuals was much slower and less effective. The ability to successfully recover from a slip (thus preventing a fall) is believed to be affected by lower extremity muscle strength and sensory degradation of the elderly individuals.

LIST OF TABLES

2.1. Cadavers Used in Braune and Fischer's Study.	57
2.2. Segment weights and center of gravity locations.	58
2.3. Segment weights and center of gravity locations.	59
2.4. Regression equations for computing the weight of body segment.	61
2.5. Mean segment weights and center of gravity locations.	62
2.6. Ratio of mean volume of the limb segments to body volume.	63
2.7. Segmental volume and center of gravity locations.	66
2.8. Results from Bernstein's study of 152 living subjects.	68
2.9. Body segment percentages of total body weight for living women.	79
2.10. A scheme of processing stages during responses to falls.	102
2.11. Events that led to the injury.	107
2.12. Distribution by accident type.	107
2.13. Distribution by occupational category.	109
2.14. Distribution by type of work surface.	109
2.15. Incidence of fall in different settings.	111
2.16. Causes or types of falls: Review of literature.	112
3.1. Subject information	117
3.2. Definition of the 3-D model segments (Frontal model).	129
3.3. Definition of the 3-D model segments (Sagittal model).	131
4.1 Summary of a three-way ANOVA on SL	146
4.2 Descriptive summary of SL on Age Groups	148
4.3 Descriptive summary of SL on Floor Levels	149
4.4 Descriptive summary of SL on Load Levels	150
4.5 Descriptive summary of SL on Interactions	151
4.6 Summary of a three-way ANOVA on SLI	153
4.7 Descriptive summary of SLI on Age Groups	154
4.8 Descriptive summary of SLI on Floor Levels	155

4.9 Summary of a three-way ANOVA on HV	157
4.10 Descriptive summary of HV on Age Groups	158
4.11 Descriptive summary of HV on Floor Levels	159
4.12 Descriptive summary of HV on Load Levels	160
4.13 Summary of a three-way ANOVA on COGVB	162
4.14 Descriptive summary of COGVB on Age Groups	163
4.15 Descriptive summary of COGVB on Floor Levels	164
4.16 Descriptive summary of COGVB on Load Levels	165
4.17 Summary of a three-way ANOVA on COGVA	167
4.18 Descriptive summary of COGVA on Age Groups	168
4.19 Descriptive summary of COGVA on Floor Levels	169
4.20 Descriptive summary of COGVA on Load Levels	170
4.21 Summary of a three-way ANOVA on VCOGV	172
4.22 Descriptive summary of VCOGVA on Age Groups	173
4.23 Descriptive summary of VCOGVA on Floor Levels	174
4.24 Descriptive summary of VCOGVA on Load Levels	175
4.21 Summary of a three-way ANOVA on $\text{COGV}_{\text{diff}}$	177
4.25 Descriptive summary of $\text{COGV}_{\text{diff}}$ on Age Groups	178
4.26 Summary of a three-way ANOVA on RCOF	180
4.27 Descriptive summary of RCOF on Age Groups	181
4.28 Descriptive summary of RCOF on Load Levels	182
4.29 Descriptive summary of RCOF on Interaction	183
4.30 Summary of a three-way ANOVA on ARCOF	185
4.31 Descriptive summary of ARCOF on Age Groups	186
4.32 Descriptive summary of ARCOF on Load Levels	187
4.33 Summary of a three-way ANOVA on SD	189
4.34 Descriptive summary of SD on Age Groups	190
4.35 Descriptive summary of SD on Load Levels	191
4.36 Descriptive summary of SD on Interaction	192

4.37	Summary of a three-way ANOVA on SDI	194
4.38	Descriptive summary of SDI on Age Groups	195
4.39	Descriptive summary of SDI on Load Levels	196
4.40	Descriptive summary of SDI on Interaction	197
4.41	Summary of a three-way ANOVA on SDII	199
4.42	Descriptive summary of SDII on Age Groups	200
4.43	Descriptive summary of SDII on Load Levels	201
4.44	Descriptive summary of SDII on Interaction	202
4.45	Summary of a three-way ANOVA on SHV	204
4.46	Descriptive summary of SHV on Age Groups	205
4.47	Summary of a three-way ANOVA on SHacc	208
4.48	Descriptive summary of SHacc on Age Groups	209
4.49	Summary of a three-way ANOVA on COGVS	212
4.50	Descriptive summary of COGVS on Age Groups	213
4.51	Summary of ANOVA results (Initiation)	214
4.52	Summary of ANOVA results (Slip Performance)	214
4.53	Summary of multiple regression	218
4.54	Descriptive summary of Sot and MCT on Age Groups	220
4.55	Summary of one-way ANOVA on MIS	221
4.56	Summary of one-way ANOVA on Leg	222
4.57	Summary of one-way ANOVA on Torso	223
4.58	Slip recovery index	226

LIST OF FIGURES

1.1. Force vectors applied by the left foot.	5
1.2. The process of inadvertent slips and falls	7
2.1. The time dimensions of walking cycle.	13
2.2. Deviations of head, upper thorax, lower thorax, and pelvis.	15
2.3. Body kinematics at HC for a typical walking trial.	20
2.4. Phasic action of hamstrings (adapted from Inman et al., 1981).	22
2.5. Gait phases in normal level walking.	26
2.6. Comparison of RCOF.	28
2.7. Displacements of center of gravity in three.	31
2.8. The path curve of the common center of gravity.	32
2.9. Mean patterns of vertical, lateral, and forward displacement.	33
2.10. The path of the common center of gravity in frontal plane.	35
2.11. Lateral pathway of center of gravity.	36
2.12. Vertical and lateral pathways of the center of gravity.	37
2.13. Simplified model depicting bipedal locomotion.	39
2.14. Effects of pelvic rotation.	40
2.15. Effect of pelvic tilt.	42
2.16. Mean patterns of sagittal rotation.	44
2.17. Knee flexion during stance.	45
2.18. Lateral displacement of center of gravity.	47
2.19. Effects of narrow walking base.	48
2.20. Inverted pendulum model.	51
2.21. Somatotypes of 30 college-aged males.	63
2.22. Determination of the weight of a body segment.	67
2.23. Schematic illustration of the Hanavan model.	71
2.24. The sectioned body in X and Z plane.	72
2.25. Lateral and anterior view of 17-segment anthropomorphic model.	74

2.26. MacKinnon and Winter's Frontal Model	75
2.27. Friction concept related to the velocity of sliding.	82
2.28. Coefficients of low-velocity dynamic friction.	83
2.29. Force vectors applied by the foot during the heel contact.	85
2.30. Typical required COF.	86
2.31. Relationship between step length and coefficient of friction.	87
2.32. Typical friction measurement devices.	93
2.33. Diagram of the PSRT.	97
2.34. Comparison of mean subjective ranking.	100
3.1. Layout of the RCFC	120
3.2. Composite view of the gait parameters	122
3.3. Marker placements, internal landmarks used to generate frontal model.	127
3.4. Marker placements, internal landmarks used to generate sagittal model.	128
3.5. Marker placements in transversal plane (top).	132
3.6. Marker placements in transversal plane (under).	133
3.7. Static strength test postures.	136
3.8. Layout of the NeuroCom.	138
3.9. Field layout of the experiment.	140
3.10. Summary of data analysis	144
4.1 Age effect on SL	148
4.2 Floor effect on SL	149
4.3 Interaction effect on SL	151
4.4 Age effect on SLI	154
4.5 Floor effect on SLI	155
4.6 Floor effect on HV	159
4.7 Age effect on COGVB	163
4.8 Floor effect on COGVB	164
4.9 Age effect on COGVA	168

4.10 Floor effect on COGVA	169
4.11 Load effect on VCOGVA	175
4.12 Age effect on $COGV_{diff}$	178
4.13 Interaction effect on RCOF	183
4.14 Age effect on ARCOF	186
4.15 Age effect on SD	190
4.16 Interaction effect on SD	192
4.17 Age effect on SDI	195
4.18 Interaction effect on SDI	197
4.19 Age effect on SDII	200
4.20 Interaction effect on SDII	202
4.21 Age effect on SHV	205
4.22 Composite pattern of SHV	206
4.23 Age effect on SHA	209
4.24 Composite pattern of SHA	210
4.25 Age effect on COGSV	213
4.26 Fitted values of SD and actual SD	218
4.27 Slip Classification	225
A1.1. The position of the COG (X).	259
A1.2. The position of the COG (Y).	259
A1.3. The position of the COG (Z).	260
A1.4. Stick figure of the subject in the frontal plane.	261
A1.5. Combined position of the COG.	262
A1.6. Velocity profile of the COG in frontal plane (Y).	263
A1.7. Velocity profile of the COG in frontal plane (Z).	264
A1.8. The position of the COG in sagittal plane (X).	265
A1.9. The position of the COG in sagittal plane (Z).	266
A1.10. Stick figure of the subject in sagittal plane.	267

CHAPTER 1

INTRODUCTION

1.1 Rationale

Reducing slip and fall accidents has been a topic of interest to ergonomics researchers since the 1920s. Traditionally, these researchers have utilized four basic approaches to investigate slip and fall accidents; epidemiology, biomechanics, tribology and psychophysics. However, in spite of the improvements in tribometric techniques to assess shoe/floor interactions, increased knowledge of the biomechanical responses to walking on slippery surfaces, and numerous journal publications in postural control, fall accidents continue to represent a significant burden to society, both in terms of human suffering and economic losses. Furthermore, with the general increased life expectancy and increased proportion of the aged workforce as the segment of overall population (45 to 65 years old – WHO, 1993), the workplace is likely to experience a greater risk for slip and fall accidents and may have an additional impact on the economics of the health care system and the industries.

The age distribution and the mean age of the population are undergoing rapid and significant change worldwide. In 1900, only one in 25 persons was over age 65. Based on current projections made by the United States Census Bureau (USCB, 1998), the present population of older individuals (those 65 year of age and over) will be doubled by the year 2030 and will constitute 17% of the total population (approximately 55 million elderly individuals, and 1 out of every five Americans will be 65 years of age or over). In addition, the distribution of the population in the U.S. compared between 1985 and 2000 (Manton et al., 1991) further reveals a greater proportion of the population being over 40 years of age. Similarly, in the UK it is projected that by the year 2021 the majority of the population will be beyond middle age (40-65 years) with a significant increase in population over 80 years of age. In Sweden, a reduction in the younger age group will result in a greater proportion of the population being over 50 years of age (Coleman, 1993).

Many studies have shown that with advancing age there is an increasing incidence of slip and fall injuries (Campbell et al., 1981; Rubenstein et al., 1988; Rice et al., 1989).

The National Safety Council (1993) reported that in 1992, falls were the second highest cause of accidental death for 45-75-year-olds and the highest accidental cause of death for those aged 75 years and over. In terms of occupational injuries, falls are the second leading cause of work-related fatalities next to motor vehicle accidents, and the number of fatal falls exceeds the combined number of workplace deaths associated with poison, electric current, fire, burns and drowning. More than 17% of all work-related injuries in 1988 and 12% of all worker fatalities in 1992 resulted from falls (National Safety Council, 1993). In addition, Rice et al. (1989) reported that based on a human capital approach, the total lifetime cost of injuries due to falls in the U.S. in 1985 was estimated at \$37.3 billion. For elderly individuals, falls make up the largest percentage of accidents. The National Safety Council reported that in 1994, 13,300 Americans met their death by falling; of these deaths, 9,923 were people over 65 years of age (National Safety Council, 1995). Additionally, falls and hip fractures among older individuals rank as one of the most serious public health problems in the U.S. with costs expected to escalate to over \$16 billion by the year 2040 (Cummings, Rubin, and Black, 1990; Sattin, 1992).

A review of the literature on slip and fall accidents indicates that multiple mechanisms are involved in slip and fall accidents. In general, the ability to walk safely and preserve balance (keeping the body's center-of-gravity over its base of support) in the event of a slip and fall is dependent upon intact visual, vestibular, proprioceptive, and musculoskeletal systems (Lacour, Vidal, and Xerri, 1983; Nashner, 1982; Tideiksaar, 1990). However, with advancing age, a variety of physiologic changes affecting these systems may interfere with gait and balance, placing these individuals at a higher risk for slip and fall accidents.

Major physiologic changes affecting the potential for slip and fall accidents begin to appear starting in the mid-twenties. In general, isometric muscle strength peaks in the mid-twenties and then decreases slowly until after 50 years of age when there is an accelerated decline (Larsson, 1982; Astrand and Rodahl, 1977). Many studies suggest that age-associated changes in muscle strength have an important effect on recovery of slip and fall accidents (Larsson, 1979; Wolfson et al., 1985; Wollacott, 1986; Bonder and Wagner, 1994). At the time of the heel contact phase of the gait cycle, the center-of-

gravity (COG) of the body is falling (Winter, 1991). This downward movement is decelerated by slight flexion of the knee against the resistance of the quadriceps (Winter, 1980). After heel contact, the foot is plantar flexed against the resisting tibialis anterior muscle (Inman et al., 1981). Contraction of the quadriceps acting on the knee and the tibialis anterior muscle on the foot causes the movements of COG of the body to be slowed, consequently, the downward motion of the COG of the body is smoothly decelerated. However, progressive decline of the strength of the quadriceps muscle in older individuals (Larsson, 1979) may change the vertical displacement of the COG of the body suddenly, resulting in a jarring effect which may increase the likelihood of slipping. Wolfson et al. (1985) reported that ankle muscle strength was significantly lower for those who fall compared to non-fallers, and suggested that diminished strength of the ankle muscles may make it difficult to rapidly adjust the center-of-gravity of the whole body to prevent falls. Thus, a general decrease in lower extremity muscle strength may impede an older worker's ability to recover balance and increase the potential for a slip-induced fall.

Many studies have documented the decline of postural control (keeping the body's center-of-gravity over its base of support during quiet stance and active movement) due to sensory degradation among elderly individuals (Sheldon, 1963; Woolacott, Sumway-Cook, and Nashner, 1982). This decline of postural control is believed to be an integrative process associated with a greater risk of falling (Isaacs, 1985; Brocklehurst, Robertson, and James-Groom, 1982; Overstall, Exton-Smith, Imms, and Johnson, 1977). Sensory inputs important for balance are: vision, proprioception, and vestibular sensations (Lacour, Vidal, and Xerri, 1983; Nashner, 1982). Vision plays a major role in maintaining stability, both at stance and while undergoing movement such as walking (Tinetti and Speechley, 1989). Visual acuity, adaptation to the dark, peripheral vision, contrast sensitivity, and accommodation, all of which are related to stability, may be affected by age-related changes (Fozard, Wolf, and Bell, 1977; Kornzweig, 1977; Goldman, 1986; Cohn and Lasley, 1985). As a result, an older individual's use of visual reference information will be impaired. For example, narrowing the visual field deprives the older person of that part of the field most sensitive to movement (Stelmach and Worringham, 1985). Visual deficits then, may result in an

increase in the time taken for the visual system to alert the central nervous system to a potential fall, thereby increasing the likelihood of fall accidents. Many studies indicate that proprioceptive deficits are also significantly higher in older individuals (Rabbitt and Rogers, 1965; Wollacott et al., 1982; Skinner et al., 1984). The proprioceptive system contributes to stability, particularly during changes of position. Wollacott et al. (1982) demonstrated the significance of ankle proprioception for balance retention in the elderly by utilizing a moveable platform that permitted either stabilization of the visual field or of the support surface. Comparing the postural sway, they found that the elderly had large increases in postural sway when ankle proprioception was eliminated (via a moveable platform). This large increase in postural sway was associated with a greater risk of falling (Isaacs, 1985). The major contribution of the vestibular apparatus to posture is in maintaining the whole body balance by perceiving the changes in direction as well as motion. Although there is an agreement on the role of the vestibular apparatus in eliciting fall responses (Melvill and Watt, 1971a, 1971b), and in resolving conflicting visual and proprioceptive information (Nashner, 1973, 1982), aging changes that affect vestibular function have not been widely examined.

Increasing age can also have an effect on gait due to postural and balance changes. Elderly people tend to have a shorter step length and a broader walking base, which results in an increase in stance time and double support time (Murray, Kory, and Clarkson, 1969; Gillis, Gilroy, Lawley, Mott, and Wall, 1986; Imms and Edholm, 1979; Winter, Patla, Frank, and Walt, 1990). Many researchers have observed that on slippery floor surfaces, subjects tended to shorten their stride length in order to reduce foot velocities, foot shear forces and reduce the likelihood of slipping (Cooper and Glassow, 1963; Ekkubus and Killy, 1973). As a result, the shorter stride length and the broader walking base of elderly individuals are thought to result in a more stable or safer gait pattern, however, these gait adaptations may have some important implications for initiation of slip induced falls. Lockhart (1997) reported that elderly individual's required coefficient of friction (RCOF) was slightly higher (on the average) than their younger counterparts. The RCOF is the measured ratio of the horizontal foot force to the vertical foot force and represents the minimum coefficient of friction that must be available at the shoe-floor interface to prevent slipping. The RCOF has been related to the tangent of the

Figure 1.1. Force vectors applied by the left foot during the heel contact phase in normal level walking. (F_h = horizontal, F_v = vertical, F_{μ} = frictional, and F_n = normal force) (adapted from Gronqvist et al., 1989).

angle between the leg and a line perpendicular to the floor (Figure 1.1) (Sherman, 1986). As a result, increasing the step length will, in general, increase RCOF (Perkins, 1978). However, many studies indicate that younger subjects stride length were longer than older subjects. These findings suggest that there might be other factors contributing to older individuals slightly higher RCOF. Winter et al. (1990), reported that the horizontal heel velocity during the heel contact phase of the gait cycle was significantly higher for elderly individuals than for younger individuals, even though the walking velocity of older subjects was slower. This increase in horizontal heel velocity during a critical time of weight transfer might increase the potential for slip-induced falls if the friction between the heel and the floor is reduced due to contamination of the floor surface. Thus, general gait instability among older individuals, and specifically, higher horizontal heel velocity during the critical phase of the gait cycle may increase the RCOF and thereby, increase the likelihood of slip and fall accidents.

1.2 Research Objectives

Injuries associated with slip and fall accidents continue to pose a significant problem to industry, both in terms of human suffering and economic losses. Although much has been learned over the last few decades about the deterioration of muscular strength, gait adaptations and sensory degradation among older individuals, still little is known about how these intrinsic changes affect biomechanical parameters of slip and fall accidents among an aging workforce.

In general, the objective of this study was to closely investigate the process of initiation and recovery of inadvertent slips and falls. Figure 1.2 illustrates a hypothetical inadvertent slip and fall situation with possible causes and effects. The process is divided into four distinct phases (environment, initiation, detection and recovery). The environmental phase considers the effects of contamination. As noted by Chaffin, Woldstad and Trujillo (1992), any fluid contaminant between two sliding surfaces will provide lubrication and thereby lower the dynamic COF values. Therefore, presence of contamination (oil, water, etc.) will reduce the available DCOF (ADCOF) of the floor surfaces. Consequently, slip is initiated by the combination of low DCOF and higher RCOF. As indicated earlier, initial gait characteristics such as stride length and heel

The Process of Initiation, Detection, and Recovery of Inadvertent Slips and Falls

Figure 1.2. The process of initiation, detection, and recovery of inadvertent slips and falls with possible causes and effects.

velocity may affect RCOF due to the increase in horizontal foot force. If older individuals initial gait characteristics are altered (e.g., higher heel velocity) due to intrinsic deficits associated with increase in age, the potential for slip induced falls may increase. In addition, age-associated decline in muscular strength may have an important effect on initiation of slips. At the time of the heel contact phase of the gait cycle, the center-of-gravity of the whole body is falling. This vertical movement is decelerated by flexion of the knee against the resistance of the quadriceps. Progressive decline of the strength of quadriceps muscle in older individuals may change the vertical displacements of center-of-gravity of the body suddenly, which may result in higher RCOF. Therefore, one of the objectives of this study was to investigate the initiation phase of the unexpected slips and falls by comparing the initial gait characteristics (such as the stride length, heel velocity, and velocity of COG) and whole body strength (including the strength of lower extremities) of older individuals and of their younger counterparts.

Irrespective of the activity being performed or the environmental factors associated with the time of a potential fall, there are certain processing stages that the central nervous system must undertake (detection phase) if a fall is to be avoided or compensated for (recovery phase). First, during the detection phase, if a potential fall is imminent, sensory input must trigger or alert those centers responsible for response selection. This alerting process may be initiated by one or more of the following sensory inputs; proprioception, vision, and vestibular function. At the input stage, any age-related disruption in the quality of the signal from the periphery may increase the likelihood of falls. In addition, diminished strength of lower extremity muscles of older individuals may make it difficult to rapidly adjust the center-of-gravity of the whole body to prevent falls. The second objective of this study was to investigate the detection and recovery phase of the unexpected slip and fall accidents by comparing sensory organization scores (see section 3.3.3), strength of lower extremity muscles and slip distances of older individuals and their younger counterparts.

The primary objectives of the research presented in this dissertation are encapsulated in the following experimental hypotheses:

Hypotheses: #1 Older age group's RCOF will be higher than their younger counterparts due to the muscle weakness and initial gait characteristics.

#2 Older age group's vertical COG velocity will be faster than their younger counterparts due to weaker lower extremity muscle strength.

#3 Older age group's slip performance measures (e.g., slip distance, sliding heel velocity, heel acceleration and adjusted required coefficient of friction) will be poorer (less optimally adjusted to maintain balance, and make slip and fall accidents more likely) than their younger counterparts due to muscle weakness and sensory degradation.

#4 Older age group's slip distances will be longer than their younger counterparts due to muscle weakness and sensory degradation.

#5 Increasing the work demand (induced by the load) will affect the gait of older groups more than their younger counterparts in ways that make slip and fall accidents more likely.

1.3 Need for the Study

This research will provide a better understanding of the gait characteristics of different age groups as they walk on slippery floor surfaces. Although epidemiological studies on slip and fall accidents reveal higher incidence of fatal injuries among older individual, still little is known about the relationship between age-related factors and slip and fall accidents. Particularly, the age range (category) associated with the greatest risk of falling has not been identified by a biomechanical study. In general, this information will allow engineers to design better work environments as well as jobs to reduce the incidence of slips and falls among aging workforce. In addition, this study can provide knowledge concerning possible intervention strategies (muscle strengthening and balance exercises, etc.) for improving dynamic equilibrium.

CHAPTER 2

LITERATURE REVIEW

Reducing slip and fall accidents has been a topic of interest to ergonomics researchers since the 1920s. Four basic approaches have been employed in studying slipping accidents; epidemiology, biomechanics, tribology and psychophysics.

The literature review is divided into six sections. The first section discusses the literature investigating the biomechanical analysis of human gait. In section two, the location of anatomical center-of-gravity of the body will be discussed. The third section presents literature that investigates the factors influencing slip resistance under various contact surface conditions (the tribological approach). Fourth, literature investigating the relationship between the perception of a sensation and the physical stimulus which produce the sensation (the psychophysical approach) is discussed. Next, the physiological factors influencing the slip and fall behavior of the older individuals are discussed. Finally, literature investigating epidemiology of slips and falls is discussed in section six.

2.1 Biomechanics of Human Gait

Locomotion, a characteristic of animals, is the process by which the animal moves itself from one geographic position to another. Walking can be defined as "a method of locomotion involving the use of the two legs, alternately, to provide both support and propulsion (Inman, Ralston, and Todd, 1981)." Finally, gait can be described as the manner or style of an individual's walking pattern.

The mastering of the erect bipedal type of locomotion appears to be a learned process and relatively prolonged affair. Popova (1935), studied the mechanism of walking in the growing child. She pointed out that the characteristic patterns of walking seen in adults are not achieved until the child reaches the age of 7-9 years. Before this age, Inman et al. (1981), concluded that the child modifies the displacements that occur in various segments with changes in bodily proportions, and develops improved neural control.

If walking is a learned activity, then each of us portray certain personal peculiarities superimposed on the basic pattern of erect bipedal locomotion. Thus, it is possible to recognize a person at a distance by a glimpse of their gait. However, under normal conditions, walking involves the integrated activity of muscles acting across many joints. Because of the synergistic and antagonistic nature of many of these muscles, the sequence and type of movement of different body parts are essentially the same in all individuals (Steinder, 1977; Winter, 1991). Therefore, in order to analyze principles of body stability and the mechanisms of slips and falls, it is necessary to understand dynamic principles of each body segment in locomotion and the translation of the body as a whole (center-of-gravity) through space.

The purpose of this review is to assist in the understanding of gait mechanisms involved in walking (both young and old) which reflect the dynamic principles of each body segment in locomotion. It is also to describe the translation of the body as a whole through space via the concept of the pathway of the center-of-gravity of the body. The first section describes the function of gait. The second section describes the process of walking in terms of body segments in locomotion. The third section describes relevant gait parameters of walking. The fourth section describes the translation of the body utilizing the pathway of the center-of-gravity of the body. Finally, section five describes the relationship between body posture and balance in human gait. The location of anatomical center-of-gravity of the body will be also discussed in the section 2.2.

2.1.1 Function of Gait

The sole purpose of walking is to transport the body safely and efficiently across the terrain. In order to achieve safe and efficient propulsion of the body, five major functions must be performed during each stride period (Winter, 1991).

1. Maintenance of upper body support (such as preventing collapse of the lower limb) during stance phase of the gait (Winter, 1980, 1984).
2. Maintenance of upright posture and balance of the total body. (Nashner, 1980, 1982; Cappozzo, 1981; Thorstensson, 1984; Winter, 1987).
3. Acquiring safe ground clearance and smooth (gentle) heel contact by foot trajectory control (Winter, 1992).

4. Mechanical energy generation to maintain or increase forward velocity (Winter, 1983a, 1983b).
5. Mechanical energy absorption to decrease forward velocity (Winter, 1983a, 1983b).

All of these major functions must be performed within the biomechanical constraints of the body and the physical constraints of the environment. In addition, the central nervous system (CNS) must also integrate efferent instructions with proprioceptive feedback and vestibular and visual inputs to generate the correct patterns of moment of force at each joint.

2.1.2 The Process of Walking

Human locomotion falls into a general category known as the “striding bipedalism,” a locomotion activity in which the center-of-gravity is carried alternately over the right and left foot. Normal walking depends on a series of reciprocal movements involving the alteration of the function of each leg between supporting the body and advancing into the next position.

2.1.2.1 Body Segments in Locomotion

Apart from the multiple variations that may occur between different individuals or within the same individuals (for instance, as a result of changes in the speed of walking), there are certain observable events that are shared by all. In the following sub-sections, the process of walking in terms of body segments in locomotion will be further reviewed.

2.1.2.1.1 Lower Extremities. Gait has been studied in forms of the “walking cycle” which is the time interval between successive floor contact of each foot. The activity of one leg can be divided into a shorter swing phase and longer stance phase.

The stance phase occurs when the foot is in contact with the floor (starting at heel contact [passive] and ending at toe-off [propulsive]) and the swing phase occurs when the foot is advancing forward to take the next step (Figure 2.1). During each walking cycle, there are two period of single limb support and two brief periods of double limb support (while one limb is about to begin swing phase and while the other has just finished).

Figure 2.1. The time dimensions of walking cycle (from Inman et al., 1981).

Forward locomotion is achieved by pushing off on the leg in stance phase while swinging the other leg forward. At heel contact the forward moving heel hits the ground, and since the limb is kept relatively straight with the foot (at right angle to the shank), deceleration of the foot converts to acceleration of the hip. In addition, the hip and the knee extend (Williams and Lissner, 1962; Cooper and Glassow, 1963; Davis, 1983). Continued forward movement of the body results in the forefoot coming to ground, and the propulsive part of the support phase begins. At this point, (the muscles plantar flex the foot, flex the knee and extend the hip), the heel is raised and pushes the foot backwards under the body. This is associated with fixation and elevation of the pelvis by the abductors as well as tilting of the body toward the swing leg that allow it to land in a line anterior to the stance leg (Koller et al., 1985). The backward (propulsion) force is resisted by friction under the sole.

In the swing phase, the leg is flexed and slightly externally rotated at the hip, flexed at the knee, and dorsiflexed at the foot. Throughout the remainder of the swing phase, the limbs move under the influence of gravity alone, and finish in a position which allows direct entry into the next step (Mochon and McMahon, 1980; Basmajian, 1976).

Stance time can be expressed in seconds or as a percent of stride period. For natural cadence (refer to section 2.1.3.1), investigators (Andriacchi et al., 1977; Grieve and Gear, 1966; Murray et al., 1966) report a fairly consistent stance time: 58% to 61% of the one stride period. Swing time varied from 42% to 39%. Double support time (stance - swing) was calculated to vary from 16% to 22%, and if perfect symmetry is assumed, this would consist of two double support times of 8% to 11% per stride period. Imms and Edholm (1979) compared the gait parameters of eight age groups from 20 to 87 years old, and found that the older individuals spend longer time in the stance phase than the swing phase.

2.1.2.1.2 Head and Trunk (Pelvis and Thorax). Although the general shapes of the displacement curves are similar for the trunk and the head, the amplitudes of the motions decrease progressively from the pelvis toward the head (Figure 2.2).

Figure 2.2. Deviations of head, upper thorax, lower thorax, and pelvis (sacrum), relative to average forward displacement (from Inman et al., 1981).

Murray et al. (1984) plotted displacements of the head in the vertical direction for 7 female adults. The vertical displacement averaged 6.2 cm at fast speed, 4.9 cm at natural cadence and 3.6 cm at slow cadences. The lateral displacement decreased from 4.2 cm at slow cadences to 2.7 cm at fast walking.

The relationship between the motion of the trunk and the step length was investigated by Weber and Karpovich (1964) and Cooper and Glassow (1963); they observed an increase in the forward inclination of the trunk with increased walking speed. This inclination of the trunk serves to maintain forward force more effectively as well as prevents the hips from being pushed forward from under the trunk, which would tend to make the trunk fall backward (Williams et al., 1962; Jenson and Schultz, 1970; Broer and Zernicke, 1979). Thorstensson et al. (1984) reported the range of rotation as subjects increased their speed from 1 m/s to 2.5 m/s was: A/P (front /back) - 2.5° to 2.8°, M/L - 2.5° to 5.0°. The inclination of the trunk in the forward direction was 6.0° at 1 m/s and 12.0° at 2.5 m/s.

Inman (1966) reported the vertical displacement of the pelvis (second sacral segment) during normal adult walking to be ± 2.5 cm. Thurston et al. (1981) reported the pelvic vertical displacement to be ± 2.0 cm and its M/L (side to side) sway to be ± 2.2 cm. Thorstensson et al. (1984) reported an increased vertical displacement of the pelvis (± 1.4 cm to ± 3.4 cm) as the subject increased speed from 1 m/s to 2.5 m/s. Lateral sway decreased from ± 2.3 cm to ± 1.5 cm over this speed range.

Stokes et al. (1989) provided a detailed 3-D analysis of the pelvic and thoracic angle and displacement profiles utilizing a motion analysis system. The results indicated that the thorax and pelvis do not move in unison. Rather, the thorax generally remains more fixed in the plane of progression because of flexion and rotation of the spinal column. This is especially true in the transverse plane where the total pelvic rotation increased from 5.7° at slow walking to 20.0° at very fast walking while the thorax remained below 5.0°. Thurston et al. (1981) also reported reduced mean ranges of transversal pelvic rotations (11.3°) to lumbar transversal rotation (8.0°).

2.1.2.1.3 Upper Extremities. Corrective postural movements are made by the upper body, arms, and shoulder. In walking, arm swing is used to offset some of the rhythmical acceleration and deceleration of the trunk by the leg movements, and also to

dampen out the rotational forces on the trunk arising from the same causes (Jensen and Schultz, 1970; Haywood, 1986). The arm swing varies considerably with variation in the speed of the walk. In the unladen state, the arm swings forward from the shoulder with the arms hanging more or less relaxed in a sagittal plane, but may move slightly toward medial plane (Cooper and Walls, 1971).

Murray, Draught, and Kory (1967) observed that the increased arm swing was accomplished by increasing shoulder hyper-extension in the backward swing and increased elbow flexion in the forward swing.

2.1.2.2 Effect of Load Carrying On Biomechanical Parameters

Corrective postural movements are made by the upper body, arms, and shoulders. In walking, arm swing is used to offset the rhythmical acceleration and deceleration of the trunk by the leg movements, and also to damp out the rotational forces of the trunk arising from the same causes (Jensen and Schultz, 1970; Haywood, 1986). However, these dampening effects are not available during the laden state (Davis, 1983). Load carrying (in front) also displaces the body center of mass anteriorly, placing it closer to the forward edge of the supporting base. Thus, requiring additional rotational torque at the foot-ground contact. Increasing the rotational torque during heel contact phase of the gait may increase the value of RCOF thereby, increasing the slip severity. Li (1991) observed that carrying a load affected both the vertical and horizontal ground reaction forces and increased likelihood of slips. In addition, carrying a load eliminates important visual input about the limb and the contaminated floor. Bunternghit et al. (accepted-inpress), revealed that gait parameters of the subjects were altered during obstruction of the immediate visual field of the floor surface area.

2.1.3 Gait Parameters

Objective assessments of gait parameters (such as, stride length, heel velocity, slip distance, and Required Coefficient of Friction (RCOF) etc.) during walking under normal and abnormal conditions have been obtained by many investigators (Herman et al., 1976; Perkins 1978; Crowinshield et al., 1978; Winter, 1991). In the following sub-sections, gait parameters (cadence, stride length, walking velocity, heel velocity, linear

accelerations of the head relative to that of the pelvis, and RCOF) of old and young individuals relevant to the slips and falls investigation will be further reviewed.

2.1.3.1 Natural Cadence, Stride length, and Walking Velocity

When an individual walks slowly or with a fast cadence, one must over-ride natural frequency and consciously force cadence to a faster or slower rate. Natural or free cadence is defined as the steps/min when a subject walks as naturally as they can (Winter, 1991).

Stride length is defined as the linear displacement in the direction of progression between successive point of foot-to-floor contact of the same foot (Murray, Kory, and Clarkson, 1966). Stride length has been one of the essential determinants in gait analysis (Ohmichi and Miyashita, 1983).

Many researchers have observed that on slippery floor surface, subjects tended to shorten their stride length in order to keep the body center-of-gravity within a smaller region, so that a greater stability could be achieved (Cooper and Glassow, 1963; Steindler, 1977).

Grieve (1968) and Drillis (1958) observed that walking velocity was the product of stride length and cadence. Murray et al. (1966) also noted that increases in walking speed increased both the stride length and cadence. However, Drillis (1958) observed that the variation in walking speed was due to changes in stride length rather than frequency of steps (cadence).

Natural cadences reported in the literature had averages varying from 101 to 122 steps/min for adults (less than 65 years old). Winter (1991) recorded 60 university student's (aged 18-32 years) natural cadence, and reported to have cadence of 107 steps/min (with S.D. = 8.8 steps/min). Drillis (1958), for 936 pedestrians, reported a mean cadence of 112 steps/min, varying from 78 to 144 steps/min. Du Chatinier et al. (1970), revealed that females walked slightly more rapidly than males (116 vs. 122 steps/min) for a population of 72 males and 57 females. Finley and Cody (1970) also reported a higher natural cadence for females (116 steps/min, s.d.=11.7, N=472) than for males (110 steps/min, s.d.=10.0, N=434). Molen and Rozendal (1972) reported for 500 young adults that the male cadence averaged 113 compared to 124 for females.

Murray et al. (1969), in a study of walking patterns in healthy old men (aged 65 to 87 years), reported a decrease in the average cadence and stride length. Meserlian (1995) reported the average cadence for older people to be about 100 steps/min. Gillis et al. (1986) also found that both cadence and stride length decreased in the elderly. However, in a recent study in which the elderly subjects were screened for both fitness and walking-related problems (Winter et al., 1990) there was no decrease in cadence (110 vs. 111 steps/min), but a significant decrease in stride length. Lockhart (1997) also reported significant difference in stride length. In general, younger subjects had longer stride length (131.04 cm) than older subject (115.29 cm) when compared with the normalized height index. Stride length was also significantly affected by level of slipperiness of the floor surface (increase in stride length with increase in ADCOF of the floor surface).

Finley et al. (1969), in a study of 23 elderly women ranging in age from 64 years to 86 years, reported significant step length and velocity differences from a group of younger women. Walking velocity of the older group was 1.57 mph versus 1.83 mph for the younger women and they concluded that this was attributed to a reduced step length: 15 in. versus 18.5 in. Murray et al. (1969) found a mean velocity of 1.2 m/s in 24 subjects aged 67 to 87 years old. Bassey et al. (1976) estimated the walking velocity of men aged 64 to 66 years as 1.3 m/s. Imms and Edholm (1981) investigated gait and mobility of 71 elderly subjects randomly chosen with and without various medical and neuralgic conditions and found that walking velocity decreased with increasing age, but was dependent on existing pathologic conditions affecting the motor system.

2.1.3.2 Heel Velocity

The control of the foot during swing is essentially a ballistic and positional task (Winter, 1991). Horizontal velocity builds up gradually after heel-off and reaches a maximum velocity late in the swing phase and drops rapidly to near zero just prior to heel contact (HC). The vertical trajectory during mid and late swing phase drops rapidly, but just 10% before HC (based on stride period), the vertical drop is arrested about 1 cm

Figure 2.3. Body kinematics at HC for a typical walking trial. (Adapted from Winter, 1991).

above the ground level (Winter, 1991). During the last 10% of swing, the heel is lowered very gently to the ground as horizontal velocity decreases rapidly to near zero. Figure 2.3 shows the body kinematics at HC for a typical trial (Winter, 1991). It can be seen that the forward velocity of the body's center-of-gravity was 1.6 m/s and the heel velocity was reduced to 0.4 m/s horizontally and a mere 0.05 m/s vertically.

The significance of the heel velocity before the HC is that at the end of swing phase the heel velocity must be reduced sufficiently so that a dangerous slip will not occur. Winter (1990) reported heel contact velocity in the horizontal direction was significantly higher for the elderly (than younger counterpart) even though walking velocity was slower for the elderly than young adults. He also noted that friction between the heel and the floor reduced heel velocity to zero, and cautioned against low COF floor surfaces. He also concluded that the only way to reduce the forward velocity of the foot prior to HC is through increased or earlier activation of the hamstring muscles. Figure 2.4 illustrates phasic action of hamstrings. These muscles become active at the termination of swing phase (Inman et al., 1981). Note that they are being elongated as they act to decelerate the swinging leg. According to Cavagna et al. (1968), this is a very effective use of muscle. After they have been stretched they are in a condition to exert their maximal force. The hamstrings continue their activity into early stance to assist the gluteus maximus in extending the hip.

2.1.3.3 Sliding Velocity

The relative sliding velocity (has been called slipping velocity) between the shoe sole and the flooring surface immediately after heel contact has been one of the essential gait parameter for slips and falls investigations (Perkins, 1978; Strandberg and Lanshammar, 1981; Leamon and Son, 1988). Perkins (1978) and Strandberg and Lanshammar (1981) reported that there was some slipping of the heel immediately after heel contact even when no loss of balance was noticed by the subject. The heel often decelerated initially and then began to increase velocity when loss of balance was observed. They concluded that if the heel sliding velocity after heel contact did not decrease to a certain limit, loss of balance or even a fall will result. Heel velocity (sliding) was defined as follows:

Figure 2.4. Phasic action of hamstrings (from Inman et al., 1981).

$$\text{Heel Velocity} = \sqrt{V_x^2 + V_z^2} \quad \text{Eq. 2.1}$$

where V_x and V_z are the velocities of heel in horizontal and lateral direction, respectively. Using the above definition (differentiation of shoe position data), Strandberg and Lanshammar (1981) reported that the average heel velocity of the slipsticks remained below 0.5m/s. In other words, if the sliding velocity peak remained below 0.5 m/s, the subjects never fell. Brunternghit (1990) concluded that the average maximum heel velocity was 0.9 m/s for both males and females when slip occurred. Heel velocities of 1.9 m/s for males and 1.5 m/s for females were associated with loss of balance (slides). Son (1990), utilizing two walking velocities (1.3 m/s and 2.2 m/s) and two floor conditions (dry and oily steel), suggested that heel velocity was significantly affected by floor slipperiness. Heel velocity at slip start was .77 m/s (at 1.3 m/s walking velocity) to .78 m/s (at 2.2 m/s walking velocity) for dry steel, and .88 m/s (at 1.3 m/s walking velocity) to 1.04 m/s (at 2.2 m/s walking velocity) for oily steel. He suggested that the change in heel velocity (sliding) was due to the change in swinging time and double-support time of the leg during the heel contact. In other words, subjects tried to land their feet quickly in order to compensate the body instability due to the slippery floor, and consequently, a quick landing of the swinging foot produced a high heel velocity.

2.1.3.4 Linear Accelerations of the Head (Relative to the Pelvis)

The linear accelerations of the head relative to that of the pelvis in the sagittal plane were measured by Ruder (1989). The vertical acceleration of the head (ear canal) was seen to be maximum in the upwards direction during weight acceptance and a maximum in the downwards direction during mid-stance phase of the gait cycle with average magnitudes of 2 m/s^2 . The pelvic vertical accelerations were just marginally higher. The horizontal head acceleration was $\pm 1.1 \text{ m/s}^2$, compared with $\pm 2.1 \text{ m/s}^2$ at the pelvis. In the frontal plane the medial/lateral accelerations (MacKinnon, 1990) showed that the pelvis averaged $\pm 1.8 \text{ m/s}^2$ which was reduced to $\pm 1.38 \text{ m/s}^2$ at the head. He also reported the average angular acceleration of the pelvis for 4 subjects (10 trials each) to be 2.6 r/s^2 r.m.s. while the head's angular acceleration averaged 1.0 r/s^2 r.m.s. The significance of this measurement is that it represents how the trunk plays an active role in

reducing the translation and rotational displacements and accelerations of the head relative to the pelvis. There were major reductions in head and shoulder angular rotations in the frontal and transverse planes, major reductions in A/P horizontal displacements and accelerations, moderate reductions in M/L horizontal accelerations and minor reductions in vertical accelerations. Thus the trunk-spinal musculature appear to play an active role in damping the head movement (apparently aimed at providing a stable platform for the eyes and reducing the signal input to the vestibular system).

Winter (1990), reported that the head A/P acceleration for the elderly was significantly higher ($.475 \text{ m/s}^2$ for the young adults vs. $.621 \text{ m/s}^2$ for the elderly) in spite of the fact that their hip acceleration was significantly lower (1.91 m/s^2 for the young adults vs. 1.54 m/s^2 for the elderly). He also reported the ratio of head to hip acceleration as a measure of the damping effect by spinal column, and noted that the young adults reduced it to 23% while elderly were able to reduce their head acceleration to only 42% of that of the pelvis. Thus, he concluded that a severely attenuated head acceleration is necessary to maintain a stable platform for the visual system. He also gave an alternative explanation in which an elderly individual's vestibular system has a reduced gain and thus requires larger acceleration input in order to monitor the A/P accelerations experienced by the head.

2.1.3.5 Ground Reaction Force

The ground reaction forces as measured by a force platform reflect the vertical and shear forces acting on the surface of the platform. As such, they are an algebraic summation of the mass-acceleration products of all body segments while the foot is in contact with the force platform. The vertical force reflects the accelerations due to gravity as well as the accelerations seen by the camera.

The mechanics and the forces involved in slipping are important in understanding fall accidents. The forces applied by the foot-floor when it touches the foot-floor surface act in three directions (Perkins, 1978): vertical (F_v), horizontal (F_H) in the direction of body motion, and horizontal-transverse (F_T) to the direction of body motion.

At the instant of the heel contact, there is a forward thrust component of force on

the swing foot against the floor. This results in a forward horizontal force (F_H) of the ground against the foot.

Walking speed, which is the product of cadence and step length, affects the magnitude of F_H . Forward horizontal force (F_H) increases with increasing step length and cadence; however, the effects of cadence are more pronounced than the step length (Soames and Richardson, 1985).

Longitudinal-transverse force (F_T) is the result of the lateral momentum during the gait. This lateral momentum exists due to an out-toeing walking pattern (Broer and Zernicke, 1979). However, the force component F_T can be ignored in normal level walking due to the small transverse forces observed in locomotion experiments (Gronqvist, Roine, Jaroinen, and Korhonen, 1989).

Vertical Force (F_v) is result of the body weight and the downward momentum of the swing leg against the ground during the heel contact. Vertical force (F_v) is affected by walking speed and cadence, which has more pronounced effect than step length.

2.1.3.5.1 Required Coefficient of Friction (RCOF). The required coefficient of friction represents the minimum coefficient of friction that must be available at the shoe-floor interface to prevent forward slipping at heel contact.

Perkins, (1978) utilized a force platform to measure the horizontal (F_H) and Vertical (F_v) components of the force exerted between the shoe and ground during normal walking. An analogue divider calculated the ratio of horizontal to vertical forces (F_H/F_v) and displayed this on an oscillograph as a function of time (Figure 2.5).

Perkins (1978) found six peak forces in the normal gait cycle. The first four peaks occurred during the landing phase and the remaining two peaks occurred during the take off phase. Peaks 1, 3, and 4 are caused by a forward force, whereas Peaks 2, 5, and 6 are caused by a backward force on the force platform.

Peak 1 is caused by the force of impact of the heel tip against the force platform and has a forward direction as a result of the approach angle of the heel to the ground. However, this peak has been found to be inconsistent due to low vertical force during this phase (peak 1).

- ▨ right foot in stance phase
- left foot in stance phase
- foot in swing phase

Figure 2.5. Gait phases in normal level walking with typical horizontal, vertical, and their ratio for one step (Perkins, 1978).

Peak 2 is caused by a backward force exerted on the heel of the shoe shortly after contact. This force has been noted by several investigators (Perkins, 1978; Lanshammar and Strandberg, 1981), but no reason for its existence has been suggested.

Peaks 3 and 4 are caused by the main forward force which retards the motion of the body and leg. During peaks 3 and 4, the vertical force has risen and significant proportion of the body weight is being applied through the heel tip (less than .1s after heel contact). Therefore, the error in F_H/F_v ratio is relatively small (Perkins, 1978). As more of the body weight is progressively transferred to the striking foot, the center-of-gravity of the body moves over the now stationary foot and the forward force causing Peak 4 decreases. During the take-off phase, the F_H/F_v (again) increases due to the force (Peaks 5 and 6) exerted by the foot propelling the body forward.

The significance of the ratio (F_H/F_v) is that it indicates where in the walking step a slip is most likely to occur. If the magnitude of F_H/F_v exceeds the coefficient of friction (COF) between the two surfaces at a particular moment in time, a slip will occur (Perkins and Wilson, 1983).

There are two critical gait phases in normal level walking from the view point of slipping (Perkins, 1978; Strandberg and Lanshammar, 1981).

1. Shortly after the heel contact-when only the back edge of the heel is in contact with the ground (peaks 3 and 4 in Figure 2.5). Peaks 1 and 2 are not considered hazardous because F_v is quite small at peak 1 and because F_H is directed backward at peak 2.
2. At the moment of toe-off-when only the forepart of the shoe is in contact with the ground (Peak 5 and Peak 6 in Figure 2.5).

Theoretically, forward slip at peaks 3 and 4 during landing is more hazardous since the forward momentum of the body will continue to apply the body weight on the slipping foot. Conversely, backward slip at peaks 5 and 6 is less likely to be hazardous, as most of the body weight has been transferred forward from the slipping foot to the opposite leading foot. Backward slip at Peak 2 shortly after landing appears to be hazardous, but the likelihood of slip continuing in a backwards direction is small since the force rapidly changes direction (Perkins and Wilson, 1983).

Figure 2.6. Comparison of RCOF between young and old on four floor levels and cadence levels.

Floor slipperiness, cadence, and age (old and young) appears to have a significant effect on RCOF (Lockhart, 1997). The floor effect was compared utilizing measured RCOF for each floor level across both age groups and cadence levels, and the results indicated statistically significant RCOF difference between four floor slipperiness levels. The RCOF decreased with decreasing ADCOF (available dynamic COF was measured using the horizontal pull slipmeter). Also, the RCOF values were significantly higher as the cadence increased. Finally, the overall means of RCOF of the age group and floor levels indicated that the elderly group could not adjust their RCOF to ADCOF on very slippery floor (oily vinyl tile floor) surface. Figure 2.6 illustrates this concept. The RCOF was adjusted well below the ADCOF of the stainless steel, ceramic tile, and oily plywood floor surface (for both young and old), however, for the oily vinyl tile floor, the elderly subjects could not adjust their RCOF to ADCOF during moderate to very fast cadence levels.

2.1.4 Trajectory of the Total Body Center-of-Gravity

The body's center-of-gravity is a key factor in human gait analysis as it reflects the motion of the whole body (Hay, 1973). The center-of-gravity is the theoretical point about which the mass of that body is evenly distributed. This reduction of the partial masses of the body into a common center-of-gravity simplifies the situation to a point where the effect of the moving forces upon the mechanism of gait as a whole can be calculated. In the human body, the location of this theoretical point will depend upon several factors including the distribution of segmental masses, and the location of those segments.

In the standing position, the center-of-gravity is situated centrally in the pelvis, approximately at the level of the second sacral vertebra. However, during forward walking, the equilibrium is lost with the take-off of the propelling foot when the body's center-of-gravity momentarily lies beyond the anterior border of the supporting surface, and regained as soon as the swinging leg is extended forward and heel touches the ground (Carlsoo, 1962). In addition, the legs move forward and backwards, the arms swing, and the trunk moves up and down and from side to side during locomotion. Consequently, the center-of-gravity progresses forwards and at the same time moves up and down and from side to side.

The trajectory of the center-of-gravity of the whole body during walking has been studied since the late 1800's. Marey and his group at the University of France first recorded the spatial displacement of the body parts as the subjects walked in a twenty-meter circle. Later, they developed several methods of interrupted-light photography to record both the angular and linear displacements of the center-of-gravity of the body during walking. Braune and Fischer, using a modification of Marey's photographic technique, made extensive measurements of the path of the center-of-gravity of the body during walking. Murray et al. (1964a and 1964b) utilizing photographic technique, also made extensive measurement of the path of the center-of-gravity of the body in vertical, lateral, and forward directions for men aged 20 to 87 years. Recently, Shimba (1984) used a force platform to estimate path of the center-of-gravity in the transverse plane. Iida and Yamamuro (1987) utilizing Shimba's force platform technique calculated the path of center-of-gravity of the body during walking in three dimensions. More recently, Ruder (1989) and Mackinnon (1990) estimated path of the center-of-gravity in transversal plane based on a weighted average of each segment's center of mass.

In the following sub-sections, the results of the above investigations are reviewed.

2.1.4.1 Trajectory of the Center-of-gravity in Sagittal Plane (Vertical Oscillations)

In normal level walking, the center-of-gravity describes a smooth sinusoidal curve when projected on the plane of progression (Figure 2.7).

The path curve of the common center-of-gravity in the sagittal plane moves up and down. This motion is sinusoidal and is about 50 mm in extent for adult males at normal walking speed (Inman et al., 1981). The summits occur at the middle of the stance phase of each side and the lowest point occurs during double support when both feet are on the ground (Figure 2.8). At the peak of vertical movement, the horizontal velocity reaches a minimum (maximum acceleration). Conversely, the reverse is true at the time of lowest trajectory.

Murray et al. (1964a) reported that the mean vertical excursion for sixty normal men aged (20 to 65 years) was $49 \text{ mm} \pm 11 \text{ mm}$, and noted that the patterns of vertical oscillation were similar in this age group (Figure 2.9). Murray et al. (1964b) reported that the amplitude of the total vertical excursion was less for the older men ($46 \text{ mm} \pm 11$

Figure 2.7. Displacements of center-of-gravity in three planes of space during single stride cycle (the lateral displacement [a], the vertical displacement [b], and the displacements of [a] and [b] as projected onto a plane perpendicular to the plane of progression [c]) (Inman et al., 1981).

Figure 2.8. The path curve of the common center-of-gravity in the sagittal plane.

Figure 2.9. Mean patterns of vertical, lateral, and forward displacement for the five age groups. H indicates the highest points of vertical movement; L, the lowest points; F, fast forward movement; S, slow forward movement; Lt, displacement to the left; and Rt, displacement to the right (Murray et al., 1964b).

mm) than for the younger men. Iida and Yamamuro (1987) showed a ± 1.7 cm (34 mm peak-to-peak) vertical displacement for men and ± 1.2 cm (24 mm peak-to-peak) for women (this discrepancy might have been resulted from the methods used [photographic technique vs. force platform estimation]).

Murray et al. (1964a) concluded that the magnitude of the vertical excursion during free-cadence walking correlated significantly with the length of the stride and the peak-to-peak vertical oscillation increased as cadence increased. They also noted that the vertical oscillations are mainly due to the alternately oblique and perpendicular positions of the lower extremities during double-limb and single-limb support.

2.1.4.2 Trajectory of the Center-of-gravity in Frontal Plane (Lateral Oscillations)

In the frontal plane the common center-of-gravity moves from left to right as each alternate leg becomes weight bearing. It follows a smooth sinusoidal curve, but with only one oscillation per stride as opposed to the two vertical oscillations in the sagittal plane (Figure 2.7 and 2.10). The center-of-gravity attains its greatest distance from the midline shortly after the support of the standing leg is shifted to the whole sole. At this point there is an inversion of motion (the velocity is zero, the acceleration is maximal). Afterwards, the center-of-gravity follows the period of double support and the velocity increases as the center-of-gravity again approaches the midline.

Recently, Shimba (1984) and MacKinnon (1990) reported that the lateral path of the center-of-gravity passes forward along the medial border of the foot (sometimes slightly outside that border) (Figure 2.11).

Murray et al. (1964a) reported the mean (peak-to-peak) magnitude of lateral motion for the sixty men aged (20 to 65 years) was $60 \text{ mm} \pm 17 \text{ mm}$ with the most lateral deflections occurring early in single-limb support (Figure 2.9). Murray et al. (1964b) showed that the total excursion of lateral motion was slightly greater for the older subject (65 to 87 years old) than for the younger men (Figure 2.12). Figure 2.12 also shows that the amplitude of the lateral excursion was greater for the free cadence (6.0 ± 1.7 cm) than for the faster cadence (5.2 ± 1.9 cm). Iida and Yamamuro (1987) reported the lateral displacement for men (± 2 cm) was greater than that for women (± 1.5 cm).

Murray et al. (1964a) concluded that the lateral movements represent automatic

Figure 2.10. The path of the common center-of-gravity in frontal plane.

Figure 2.11. Lateral pathway of center-of-gravity passing forward along the medial border of the foot (MacKinnon, 1990).

Figure 2.12. Vertical and lateral pathways of the center-of-gravity. Graphs A and C show mean patterns of the vertical and lateral pathways, respectively. Graphs B and D show the mean amplitudes of the total vertical and lateral excursions during fast and free speed (Murray et al., 1964b).

postural adjustments, shifting the line of gravity alternately toward the eccentrically placed bases of support in keeping with the demands of stability.

2.1.4.3 Trajectory of the Center-of-gravity in Transverse Plane (Forward Displacement)

In the transverse plane the center-of-gravity carries out forward and backward movements (U shape). In this plane the center-of-gravity moves forward commensurably with the movements of the pelvis. The maximum forward point is reached as the heel is set to the ground and the maximum backward movement occurs at the moment of the take-off phase of the gait. The amplitude of these back and forward oscillation is, according to Braune and Fischer (1889), about 12 mm.

Murray et al. (1964a) reported that the forward movement was not constant but proceeded in two gentle waves of increased and decreased rates of displacement within each walking cycle (Figure 2.9). They also noted that the most rapid forward movement occurred shortly after heel-contact (during the periods of double-limb support) and the forward speed declined as the body climbed to its highest and most lateral position during single-limb support.

While this is reasonably true for fast walking, in slower walking the peak of the vertical displacement occurs before that of the lateral displacement, and therefore, the path follows an asymmetrical figure-of-eight (Inman et al., 1981) (Figure 2.7).

2.1.4.4 Smooth Sinusoidal Displacement of Center-of-gravity

Achievement of even sinusoidal displacements depends on smoothly coordinated angular displacements of the various segments of the lower limb (Inman et al., 1981). Saunders et al. (1953), used a series of simple models to illustrate how this smooth sinusoidal displacement pathway was achieved in bipedal locomotion.

In this section, the theoretical models of the lower limb will be utilized to further aid in the understanding of achievement of even sinusoidal displacements of the center-of-gravity.

The first model is shown in Figure 2.13. The theoretical lower extremities are shown to consist only of a bar representing the pelvis, with the center-of-gravity depicted

Figure 2.13. Simplified model depicting bipedal locomotion (Saunders et al., 1953).

Figure 2.14. Effects of pelvic rotation. By permitting the pelvis to rotate in a horizontal plane during locomotion, the center-of-gravity is prevented from falling as far during the phase of double weight bearing as was shown in Figure 2.13. The solid line at the top represents the curve shown in Figure 2.13 and the dotted line represents the curve shown in Figure 2.14 (Saunders et al., 1953).

as a small block lying midway between the two hips. The leg is represented as rigid levers without foot, ankle, or knee mechanism, that is articulated only at the hip joints, and which will only permit flexion and extension. They noted that such a system of quasilocomotion would produce something analogous to the process of stepping off distances with a pair of compasses. In this system, the radius of each arc is equal to the length of limbs, and with each step, the extent of flexion and extension of the hip joint is the same. Such a type of locomotion requires that the center-of-gravity be elevated to a height equal to the center-of-gravity in the standing position. Thus, it will result in a severe jolt at the point of interaction of each two arcs, where there is an abrupt change in the direction of movement of the center-of-gravity (Inman et al., 1981; Low and Reed, 1996). Decreasing the total elevation, depressing the center-of-gravity, and smoothing the series of interrupted arcs require coordinated movements involving all the joints of the lower extremities. In the following sub-sections, a qualitative description of the principal elements (movements of the lower extremities) utilizing Saunter's model (1953) is presented to provide a basis for the quantitative descriptions of the gait parameters involved in achievement of smooth sinusoidal displacements of the center-of-gravity.

2.1.4.4.1 Rotation of the Pelvis. The effects of pelvic rotation are to flatten the arc of the passage of the center-of-gravity in “compass” gait (model 1) by elevating the ends of the arc (Figure 2.14). Due to this pelvic motion, for any given stride length, less flexion and extension of the hip is needed. Consequently, there is less vertical movement of the trunk due to the smaller angles needed at the hip (Low and Reed, 1996). In addition, the angles at the intersections of successive arcs are less abrupt and the severity of the impact at floor contact is reduced.

As indicated earlier, in normal level walking, the pelvis rotates about a vertical axis alternately to the right and to the left (relative to the line of progression). The magnitude of this rotation is approximately 5° at slow walking speed to 20° at very fast walking speed (Stokes et al., 1989). Murray et al. (1964b) indicated that older men showed smaller excursions of pelvic rotation than younger men. Therefore, the angles at the intersections of successive arcs might be more abrupt for older individuals and may result in greater impact during floor contact than younger counterpart.

Figure 2.15. Effect of pelvic tilt. Due to the pelvic tilt, the center-of-gravity need not be elevated as much when the body passes over the weight-bearing leg during midstance. The solid line at the top represents the curve shown in Figure 2.14 (Saunders et al., 1953).

2.1.4.4.2 Pelvic Tilt. In normal level walking, as the hip of the stance leg rises, the pelvis is allowed to tilt down on the other side (that of the swinging leg) (Figure 2.15). At moderate speeds, the alternate angular displacement is about 3° to 5° (Murray et al., 1964a). This is controlled by the gluteus medius and minimus (Low and Reed, 1996). Due to this pelvic tilt, the center-of-gravity (swing leg hip) remains lower than the stance phase hip. As the hip on the swing side is lower, it is necessary for the swinging leg to shorten to clear the ground. This is achieved by knee flexion and ankle dorsiflexion. Thus, the summit of the arc is lowered, further flattening the pathway of whole body center-of-gravity.

There was no systematic differences in the excursion of pelvic tilt between the various age and height groups (Murray et al., 1964a).

2.1.4.4.3 Knee Flexion of the Stance Leg. In each walking cycle, the pattern of knee rotation has two waves of extension and two waves of flexion (Figure 2.16). At heel contact, the knee is extended in order to lengthen the forward-reaching extremity. At this time, the knee has already begun its first and lesser phase of flexion (Fl_1). Consequently, in mid-stance of the gait cycle, the knee flexes in range of 15° to 20° (Winter, 1980), and continues to remain flexed until the center of mass has passed over the weight-bearing leg (Saunders et al., 1953).

The effect of this knee flexion is twofold. Initially, it absorbs part of the impact of the body at heel contact and decreases the amount that the center of mass must be elevated as it passes over the weight-bearing leg. Knee flexion of the stance leg effectively shortens this leg in the middle of stance phase so that, as the leg passes from flexion to extension at the hip, it does not cause the hip to rise high (Figure 2.17). Thus, during the beginning and end of stance phase, knee flexion contributes to smoothing the abrupt changes at the intersections of the arcs of translation of the center-of-gravity (Saunders et al, 1953; Inman et al., 1981).

Older men showed less knee flexion during swing than the younger men did. However, during the stance phase of the gait cycle, the knee flexion was almost identical in the various age and height groups (Murray et al., 1964a, 1964b).

Figure 2.16. Mean patterns of sagittal rotation (pelvis, hip, knee, and ankle) for the five age groups (Murray et al., 1964b).

Figure 2.17. Knee flexion during stance. The solid line at the top represents the curve shown in Figure 2.15 (Saunders et al., 1953).

2.1.4.4.4 Knee, Ankle and Heel Mechanism. The three elements discussed so far (pelvic rotation, pelvic tilt, and knee flexion of the stance leg) act to decrease the magnitude of the vertical displacement of the center-of-gravity of the body. However, the pathway of the center-of-gravity still consists of a series of arcs, and the intersections of the center-of-gravity will be subject to a sudden change in vertical displacement. This would result in a jarring effect on the body (Inman et al., 1981). Thus, an additional mechanism must be active that smoothes the pathway of the center-of-gravity by a gradual change in the vertical displacement of the center-of-gravity from a downward to an upward direction, converting a series of intersecting arcs into a sinusoidal path. This is accomplished by certain movements in the knee, ankle, and foot.

At the time of the heel contact, the center of mass of the body is falling (Winter, 1991). This downward movement is decelerated by slight flexion of the knee against the resistance of the quadriceps (Winter, 1980). After heel contact, the foot is plantar flexed against the resisting tibialis anterior muscle (Inman et al., 1981). Contraction of the quadriceps acting on the knee and the tibialis anterior muscle on the foot causes the movements of center-of-gravity of the body to be slowed, consequently, the downward motion of the center-of-gravity of the body is smoothly decelerated.

2.1.4.4.5 Lateral Displacement of the Body. As indicated previously, the body is shifted slightly over the weight-bearing leg with each step. This magnitude is approximately ± 3.5 cm (Murray et al., 1964a). The side to side displacement of the pelvis is reduced by keeping the walking base narrow (Low and Reed, 1996). Figure 2.18 and 2.19 illustrates lateral displacement of the center-of-gravity in wide and narrow walking base gait.

Stride width was measured by Murray et al. (1964a and 1964b) utilizing the transverse distance between points on the central long axes of the feet (located by a line from the lateral malleolus drawn perpendicularly to the line of progression) during foot-to-floor contact. They found that the older subjects' stride width was slightly wider than those of the younger men (Murray et al., 1964b). Consequently, the lateral excursion of the center-of-gravity was greater for the older subjects than the younger counterpart (Murray et al., 1964b).

Figure 2.18. Lateral displacement of center-of-gravity in wide walking base (Saunders et al., 1953).

Figure 2.19. Effects of narrow walking base. By providing the model with a degree of genu valgum, the walking base is narrowed and the amplitude of lateral displacement is decreased while the shank remains vertical (Saunders et al., 1953).

2.1.5 Posture and Balance in Human Gait

In the end, gait represents a translatory progression of the body as a whole. During walking, the body experiences translatory motion while the arms and legs experience rotary motion about the active joints. The balance of the human body or its parts requires that all gravitational forces be completely neutralized by counter forces. These counter forces are supplied by the resistance of the supporting surface of the body. However, when gravitational forces fall outside of the supporting surfaces, the translatory force of gravity is not neutralized. In order to neutralize the rotatory forces, the line of COG must also fall in the supporting surface. In general, two factors influence stability (Steindler, 1977). First, the broader the supporting area (area over which one object is supported by another, in the standing position, the base of support of the human body is the area bounded by the contact points of the feet with the floor) the greater is the force necessary to destroy the balance by throwing the line of COG beyond the supporting surface. Second, the lower the center-of-gravity is located, the greater is the arc which an unbalancing force must describe before it can bring the center to fall outside the supporting area (i.e., more stable).

In the human body, the constant mass is supported in standing on a small base. Additionally, the area of the base and the position of the center-of-gravity are subject to constant rapid changes and therefore, require a complex reflex system involving the integration of sensory nerves and the motor nerves controlling the muscles to maintain balance in any given posture of the body. The deviation of the center-of-gravity is constantly monitored by (Fozard, Wold, and Bell, 1977; Nashner, 1982; Stelmach and Worringham, 1985):

1. Sensory mechanoreceptors in the capsules and ligaments of joints, which provide information about their position and rate of movement.
2. Stretch receptors in muscles (muscle spindles), which give information on the amount and rate of muscle stretching.
3. Pressure receptors (exteroceptors) in the skin, which provide information about the amount of pressure on the skin of the soles of the feet.
4. The vestibular apparatus, including the semicircular canals found in the inner ear within the temporal bone of the skull, gives information of the motion of the

head in all planes.

5. The visual system giving information about the position of the body in relation to objects and surfaces that can be seen.

All this information is processed in the central nervous system (principally in the cerebellum and the brainstem) and signals are sent to skeletal muscles to contract appropriately to adjust the position of the body to maintain the center-of-gravity over the base. This process involves unconscious prediction of body motion so that the adjustments are not merely responding to the existing body position, but arranging that the center-of-gravity to base relationship is appropriate for subsequent movements (i.e. the next step in walking).

2.1.5.1 Balance Task of Walking versus Standing

Human bipedal walking provides a challenging balance task to the CNS and appears to be completely different than the balance task during standing. During standing the CNS is challenged to keep the body's center-of-gravity safely within the borders of the two feet (or one foot if balancing on one foot). Studies of balance and posture during quiet or perturbed standing have identified the ankle muscles (plantarflexors/dorsiflexors, invertors/evertors) as dominant (Winter, 1991). However, during locomotion, ankle muscles are no longer important because the balance task has changed (Winter, 1987). As explained in section 2.1.4.2 (Lateral Oscillations of the COG), the lateral path of the center-of-gravity passes forward along the medial border of the foot (even slightly outside that border). Thus, during single support the body is in a continuous state of falling down because the body's center-of-gravity is outside the foot. The only way that recovery is achieved is to position the swing limb so that during double support the CNS can make any re-balancing adjustments.

2.1.5.2 Inverted Pendulum Model

The second challenging fact is that the distribution of body mass is such that $2/3$ of its mass in the head, arms and trunk is located $2/3$ of body height above the ground. Such an inverted pendulum is inherently unstable when considering the forward

About C of M

$$M_j = m \ddot{x}_o (y_j - y_o) + m (\ddot{y}_o + g) (x_o - x_j) + I_o \alpha$$

Figure 2.20. Inverted Pendulum Model of head, arms, and trunk (Winter, 1991).

momentum of head, arms and trunk and the trajectory of center-of-gravity. The inverted pendulum model of head, arms and trunk will be briefly introduced to elaborate disturbing moments of gravitational and acceleration factors.

The dynamic equilibrium equations that describe the moments acting on the segment are usually derived as acting about the center of mass of the segment (Figure 2.20) (Winter, 1991).

About center of mass:

$$M_j = m \ddot{x}_o (y_j - y_o) + m (\ddot{y}_o + g) (x_o - x_j) + I_o \alpha$$

where,

M_j = net muscle moment acting at the joint

m = mass of the segment of interest

$\ddot{x}_o$ = horizontal acceleration

$\ddot{y}_o$ = vertical acceleration

g = gravitational acceleration

α = angular acceleration

Substituting : $I_j = I_o + md^2$ and rearranging,

$$M_j = \underbrace{mg (x_o - x_j)}_{\text{gravitational}} + \underbrace{m \ddot{y}_o (x_o - x_j) - m \ddot{x}_o (y_o - y_j)}_{\text{couple due to C of M acceleration}} + \underbrace{I_o \alpha}_{\text{inertial}} \quad \text{Eq. 2.2}$$

Equation 2.2 represents the final equilibrium equation with the moments as they act about the pivot point, in this case the hip joint.

The first term, M_j , is the net muscle moment acting at the joint in the plane of interest (either the plane of progression or the frontal plane). The second term is the gravitational moment due to the fact that the center-of-gravity does not lie directly over the joint center. The next two terms combined are the couples created by the fact that the joint center is accelerating and the final term is the associated moment that causes the

segment to undergo an angular acceleration, α . By partitioning these terms in this manner prevalence of the disturbing moments (gravitational and acceleration) and how well the CNS recognized and counters these disturbances are readily seen.

2.2 Location of Anatomical Center-of-Gravity of the Body

Detailed quantitative analyses of human motion require knowledge of the location of the center-of-gravity of the body (or bodies). Many attempts have been made to develop suitable methods of determining the location of center-of-gravity. There are basically two approaches which have been used in determining the location of the center-of-gravity of the human body, the direct and indirect approaches. The direct approach considers the body as a whole, and the indirect approach considers the body as various parts or segments. In the following subsections, the methods for determining location of the center-of-gravity are reviewed (direct and indirect). Finally, the mathematical models and methods for the determination of the whole body center-of-gravity are reviewed.

2.2.1 The Direct Approach

Borelli (1679) is generally credited with being the first person to attempt to locate the center-of-gravity of a human body. He placed his subject in a supine position on a board and then moved the board back and forth on a triangular-sectioned support until a position of balance was achieved. However, he failed to realize that the vertical plane passing through the edge on which the board was supported contained the center-of-gravity of the subject-plus-board system and not necessarily that of the subject alone. During the 19th and early 20th centuries numerous methods were developed for the purpose of locating the center-of-gravity in either the transverse or frontal plane (Weber, Wilhelm, and Weber, 1836; Meyer, 1853; Mosso, 1884; Demeny, 1887; Richer, 1921; Haycraft and Sheen, 1900; Croskey, Dawson, Luessen, Alma, Marohan, and Wright, 1922). Although there were considerable differences between these methods in terms of the equipment used and the experimental procedures followed, they all had at least one thing in common. Like the method of Borelli, they all depended on adjusting the position of the subject, and/or the apparatus until the system came to rest with its center-of-gravity in the same vertical plane as the fulcrum upon which it was supported.

Cotton (1931) devised a method involving the use of a board balanced on a single central support and held in a horizontal position by a spring scale attached to one end. The scale recorded the force necessary to maintain the system in a horizontal position. The location of the transverse plane containing the subject's center-of-gravity was then readily obtained by computing moments about the fulcrum provided by the central support.

Cotton (1932) next devised a method for locating the equivalent frontal plane. This technique required the subject to lie on a second board placed at right angles across the board to which the support and spring scale was attached. The vertical plane containing the center-of-gravity was then determined with the system tilted upward slightly toward the spring scale end, and then again with the system tilted upward toward the other end. The antero-posterior location of the center-of-gravity was determined by the line of intersection between the two planes.

Basler (1931) developed techniques involving the use of a balance or reaction board. This method required the use of a large triangular board supported in a horizontal position by two metal spikes each of which rested on the platform of a spring scale and a third spike which rested on a fixed support. The subjects were placed on board with required position and the readings on the scales were measured. These measurements, together with the known weight of the subject, were then used in determining the moments about each of two axes through the points of support. Solution of the resulting moment equations yielded the location of the center-of-gravity of the subject in two planes (transverse and sagittal planes for a subject in a back-lying position; transverse and frontal planes for a subject in a side-lying position).

Santschi, Du Bois, and Omoto (1963) determined the location of the transverse and frontal planes containing the center-of-gravity using a method primarily devised for the purpose of obtaining the moments of inertial of a human body in a variety of positions. The method involved strapping the subject into a large compound pendulum which was then set to oscillate through an angle of $\pm 1^\circ$. After the period of the pendulum had been determined, the location of the center-of-gravity of the subject in one plane was then computed using an equation involving the two periods, the weight and volume of the subject, the ambient air density, and the known physical characteristics of the pendulum

itself. The whole process was repeated with the subject strapped into a second compound pendulum to locate a second plane containing the center-of-gravity.

Weinbach (1938) described a method for determining the height of the center-of-gravity of a subject standing in an erect position, using measurements taken from photographs or taken directly from the subject. The method was based on the assumptions that successive horizontal cross-sections through the body were elliptical in shape and thus their areas could be computed using the formula:

$$a = \frac{\pi}{2} \cdot f \cdot s \text{ (sq. mm)} \quad \text{Eq. 2.3}$$

where f is the number of mm in one-half the front view, and s is the number of mm in the side view section. Next a volume contour map was drawn by plotting the cross-sectional areas as ordinates against the heights of the cross-sections for the ground as abscissa. From the resulting curve, a second curve was derived using a series of geometric constructions. Finally, the areas under the two curves were measured with a planimeter and the ratio of one (representative of the volume of the body below the center-of-gravity) to the other (representative of the volume of the whole body) was used in computations to determine the height of the center-of-gravity above the soles of the feet.

2.2.2 The Indirect Approach

In this approach, the body is considered to be composed of an arbitrary number of segments, whose weights and center-of-gravity locations are known. The moments of the individual segments about an arbitrary axis are computed, summed, and equated to the moment of the whole body about this same axis:

$$W x = w_1 x_1 + w_2 x_2 + w_3 x_3 + \dots + w_n x_n, \quad \text{Eq. 2.4}$$

where $w_1, w_2, w_3 \dots w_n$ are the weights of the n segment; W is the weight of the body (i.e., $w_1 + w_2 + w_3 + \dots w_n = W$); and $x_1, x_2, x_3 \dots x_n$ and x are the respective distances of the centers of gravity of the segments and the whole body from the chosen axis. A simple rearrangement of this equation yields the distance of the center-of-gravity of the whole body from the axis and thus fixes its location in one dimension:

$$x = w_1 x_1 + w_2 x_2 + w_3 x_3 + \dots + w_n x_n / W. \quad \text{Eq. 2.5}$$

A similar computation of the moments about a second and third axis fixes the location of the whole-body center-of-gravity in a second and third dimensions:

$$y = w_1 y_1 + w_2 y_2 + w_3 y_3 + \dots + w_n y_n / W, \quad \text{Eq. 2.6}$$

$$z = w_1 z_1 + w_2 z_2 + w_3 z_3 + \dots + w_n z_n / W. \quad \text{Eq. 2.7}$$

The accuracy of the results obtained using this approach depends in large part on the validity of the available data concerning the weight and the location of the COG of each of the body segments. Numerous studies have been undertaken with a view to obtaining suitable data. These may be classified under five broad headings: (1) cadaver studies, (2) immersion studies, (3) reaction board studies, (4) mathematical modeling studies, and (5) miscellaneous studies.

2.2.2.1 Cadaver Studies

Braune and Fischer (1889) obtained four male cadavers (Table 2.1), placed them on a horizontal board in a symmetrical supine position (legs extended and rotated laterally, elbows slightly flexed, forearms in midrange position), and froze them solid. They then drove three thin, metal rods through each cadaver at right angles to its three cardinal planes, suspended it from each of the three rods, in turn, and once equilibrium had been established each time, scratched lines on it to indicate the positions at which the vertical plane containing the supporting rod intersected the trunk. The point of intersection of the three planes determined the COG of the body (Table 2.2).

Fischer (1906), utilizing the same method as described above, dissected a small cadaver (150.0 cm [59.3 in.], and 44.057 kg [97.1 lb.]) and determined the weights and center-of-gravity locations of 14 individual body segments. Dempster (1955), as part of a comprehensive 3-year project undertaken on behalf of the U.S. Air Force, obtained eight white, male cadavers. After freezing the cadavers with dry ice, he bisected the joint angles with cuts through the joint center, weighed each segment, and determined the "linear location" of its COG using a balance plate. The anatomical location of the COG of each segment was determined by drilling small transverse holes in the direction of the COG inserting pointed dowel sticks in these holes and then making a saw cut through the segment in the plane of the sticks. Upon completion of this transverse bisection, the pointed ends of the sticks indicated the location of the COG of the segment (Table 2.3).

Table 2.1. Cadavers Used in Braune and Fischer's Study (Adapted from Braune and Fischer, 1889).

Age		Supine Height	Weight	Build
I	18	169 cm	not reported	"well built"
II	45	170 cm	75.10 Kg	"muscular"
III	50	166 cm	60.75 Kg	"muscular"
IV	not reported	168 cm	56.90 Kg	"muscular"

Table 2.2. Segment weights and center-of-gravity locations (adapted from Braune and Fischer, 1889).

Segment		Mean weight of segment Relative to total body weight	Mean distance of C.G. from proximal axis as fraction of segment length
Head		.070	
Torso		.461	
Arm	R	.062	.526
	L	.063	
Upper arm	R	.033	.470
	L	.034	
Forearm and Hand	R	.030	.472
	L	.029	
Forearm	R	.021	.421
	L	.020	
Hand	R	.008	
	L	.008	
Leg	R	.173	.407
	L	.173	
Upper leg	R	.107	.439
	L	.107	
Lower leg and foot	R	.065	.519
	L	.065	
Lower leg	R	.047	.420
	L	.048	
Foot	R	.017	.434
	L	.017	

Table 2.3. Segment weights and center-of-gravity locations (adapted from Dempster, 1955).

Segment	Mean weight of segment as % of total body weight		Center-of-gravity location with respect to stated reference points
Trunk minus limbs	56.5		60.4% to vertex; 39.6% to hip axes
Trunk minus shoulders	46.9		64.3% to vertex; 35.7% to hip axes
Both shoulders	10.3		84.0% of clavicular link dimension to sternal end of clavicle (oblique)
Head and neck	7.9		43.3% to vertex; 56.7% to seventh cervical centrum
Thorax	11.0		62.7% to first thoracic centrum; 37.3% to twelfth Thoracic centrum
Abdomen plus pelvis	26.4		59.9% to first lumbar centrum; 40.1% to hip axes
Whole upper limb	R	4.9	51.2% to gleno-humeral axis; 48.8% to ulnar styloid
	L	4.8	
Arm	R	2.7	
	L	2.6	
Upper arm			43.6% to gleno-humeral axis; 56.4% to elbow axis
Forearm and hand	R	2.2	67.7% to elbow axis; 32.3% to ulnar styloid
	L	2.1	
Forearm	R	1.6	43.0% to elbow axis; 57.0% to wrist axis
	L	1.5	
Hand	R	0.6	50.6% to wrist axis; 49.4% to knuckle III
	L	0.6	
Whole lower limb	R	15.7	43.4% to hip axis; 56.6% to medial malleolus
	L	15.7	
Thigh	R	9.6	43.3% to hip axis; 56.7% to knee axis
	L	9.7	
Leg and Foot	R	5.9	43.4% to knee axis; 56.7% to medial malleolus
	L	6.0	
Leg	R	4.5	
	L	4.5	
Lower Leg			43.3% to knee axis; 56.7% to ankle axis
Foot	R	1.4	42.9% to heel; 57.1% to toe I
	L	1.4	

Barter (1957) attempted to overcome limitations imposed by the small sample sizes in the studies of Braune and Fischer (1889), Fischer (1906), and Dempster (1955) by combining their results for the weights of the various segments and treating them statistically by means of a regression analysis. The equations derived by Barter are presented in Table 2.4.

Clauser, McConville, and Young (1969) used 14 preserved male cadavers, carefully selected to closely approximate the wide range of physical body sizes found in normal populations. An extensive series of anthropometric measurements were taken on each cadaver, and whole body center-of-gravity was located using Swearingen's (1962) apparatus and the body was carefully dismembered so that the required segment parameters could be determined. The anthropometric and segmental data was then subjected to a step-wise multiple regression analysis and regression equations were derived for the prediction of segment weight, volume, and center-of-gravity location from the anthropometric measures. The mean values for the weight of each segment, expressed as a ratio of the total body weight and for the location of the center-of-gravity as a ratio on the segment length, were also determined (Table 2.5).

2.2.2.2 Immersion Studies

Harless (1860) developed a method for determining the weights of the segments of a living subject. He obtained a total of 44 limb and head segments from a wide variety of adult corpses (four males, two females, median age 33.5 years, age range 22-68 years) and determined the weight of each when it was suspended in air, and when it was totally immersed in water, he then computed its specific gravity using the formula:

$$\text{Specific gravity} = W_{\text{air}} / W_{\text{air}} + W_{\text{water}} \quad \text{Eq. 2.8}$$

He suggested that the weight of a segment of a living subject could be determined in a simple computation involving the volume of the segment (water displacement method).

Several investigators have determined the volumes of the limb segments of living subjects and then computed values for the mass or weight of these segments using assumed values for their density or specific weight.

Dempster (1955), selected 39 white, male, college-aged, subjects representative of four body builds (median, rotund, thin, and muscular) (Figure 2.21) and determined the

Table 2.4. Regression equations for computing the weight of body segment (adapted from Barter, 1957).

Body segment	Regression equation	Standard error of estimate
Head, neck, and trunk	.47 X Total body wt. +12.0	(± 6.4)
Total upper extremities	.13 X Total body wt. -3.0	(± 2.1)
Both upper arms	.08 X Total body wt. -2.9	(± 1.0)
Forearms plus hands	.06 X Total body wt. -1.4	(± 1.2)
Both forearms	.04 X Total body wt. -0.5	(± 1.0)
Both hands	.01 X Total body wt. +0.7	(± 0.4)
Total lower extremities	.31 X Total body wt. +2.7	(± 4.9)
Both upper legs	.18 X Total body wt. +3.2	(± 3.6)
Both lower legs plus feet	.13 X Total body wt. -0.5	(± 2.0)
Both lower legs	.11 X total body wt. -1.9	(± 1.6)
Both feet	.02 X Total body wt. +1.5	(± 0.6)

Table 2.5. Mean segment weights and center-of-gravity locations (adapted from Clauser et al., 1969).

Segment	Segment weight (% of body weight)	COG (% of segment length)
Head	7.3	46.6
Trunk	50.7	38.0
Total arm	4.9	42.2
Upper arm	2.6	52.2
Forearm and hand	2.3	62.6
Forearm	1.6	39.0
Hand	0.7	18.0
Total Leg	16.1	38.2
Thigh	10.3	37.2
Calf and foot	5.8	47.5
Calf	4.3	37.1
Foot	1.5	44.9

Figure 2.21. Somatotypes of 30 college-aged males used in Dempster's immersion study of living subjects (Hay, 1977).

volumes of their limb segments by immersing them in water and noting the volume of water displaced. The data obtained in this manner (expressed in percentages of the total body volume) are presented in Table 2.6.

Drillis and Contini (1966) employed a wide range of measurement techniques in order to determine the volume, mass, density, center of mass, mass moment of inertia, and radius of gyration of the living human body and its segments. Among these were two immersion-type techniques. The "N.Y.U. Modified Immersion Method", in which the segment being studied was placed in an empty tank which was then filled to the appropriate level, and the "Segment Zone Method" in which the same procedure was followed with the water level raised in small equidistant steps so that the distribution of volume could be determined throughout the length of the segment. The mean volumes obtained for the limb segments of 12 male subjects (age range 20-39 yr., mean age 27.2 yr.) and the location of the segment centers of gravity are presented in Table 2.7.

2.2.2.3 Reaction Board Studies

The weight of a body segment (or, alternatively, the location of the center-of-gravity of that segment) can be determined using a modification of the reaction board technique of du Bois-Reymond. After the subject has taken up his position on the board, the reading on the scales and the horizontal location of the segment center-of-gravity is noted. The subject then alters the position of the segment in question and the same two parameters are noted a second time. The weight of the segment is then computed as in the caption for Figure 2.22.

Bernstein (1967) used a sophisticated version of the reaction board procedure shown in Figure 2.22 to determine the masses and the center-of-gravity locations of the major limb segments of 152 living subjects (both male and female) ranging in age from 10-75 years. The results obtained are summarized in Table 2.8.

2.2.2.4 Mathematical Modeling Studies

Mathematical models allow for the calculation of inertial properties of body segments and of the whole body not only in one position but in many positions and, therefore, can be used to simulate human movement (Nigg and Herzog 1994).

Table 2.6. Ratio of mean volume of the limb segments to body volume (adapted from Dempster, 1955).

Segment	Rotund (%)	Muscular (%)	Thin (%)	Median (%)
Whole upper limb	5.28	5.60	5.20	5.65
Arm	3.32	3.35	2.99	3.46
Forearm plus hand	1.95	2.24	2.23	2.15
Forearm	1.52	1.70	1.63	1.61
Hand	0.42	0.53	0.58	0.54
Whole lower limb	20.27	18.49	19.08	19.55
Thigh	14.78	12.85	12.90	13.65
Leg plus foot	5.52	5.61	6.27	5.97
Leg	4.50	4.35	4.81	4.65
Foot	1.10	2.20	1.46	1.25

Table 2.7. Segmental volume and center-of-gravity locations (adapted from Drillis and Contini, 1966).

Segment	Segment Volume (% of body volume)	Location of COG (% of seg. length)
Hand	.566	39.2
Forearm	1.702	42.3
Forearm and hand		38.2
Upper arm	3.495	44.9
Whole arm	5.730	43.1
Foot	1.297	44.5
Shank	4.083	39.3
Shank and foot		45.0
Thigh	9.241	41.0
Whole leg	14.620	39.7

Taking moments about A in position 1:

$$R_1 x = w y + (W - w) z$$

Taking moments about A in position 2:

$$R_2 x = w(y + \Delta y) + (W - w) z$$

Subtracting:

$$(R_2 - R_1) x = w \Delta y$$

$$w = \frac{(R_2 - R_1) x}{\Delta y}$$

Figure 2.22. Determination of the weight of a body segment (Hay, 1977).

Table 2.8. Results from Bernstein's study of 152 living subjects (adapted from Bernstein, 1967) on relative masses of the limbs.

Segment	Men	Women	Gen. Mean	Ratio M/W
Upper arm	0.02655	0.02600	0.02632	1.021
Forearm	0.01818	0.01820	0.01819	1.000
Hand	0.00703	0.00550	0.00642	1.279
Thigh	0.12213	0.12815	0.12485	0.948
Lower leg	0.04655	0.01845	0.04731	0.961
Foot	0.01458	0.01295	0.01313	1.126

Mathematical models of the human body are based on the representation of the segments by standard geometric shapes. The simplest approach is to assume that each segment is a single homogeneous solid such as a right elliptical cylinder or a frustum of a right circular cone (Whitsett, 1963; Hanavan, 1964) (Figure 2.23). Dimensions for the shapes are based on anthropometric measures taken on the subject. The remaining input variable, segment mass is estimated using regression equations based on cadaver studies (Barter, 1957). A number of attempts have been made to represent the segments of the body as regular geometric solids of known density and to determine the center-of-gravity of the whole body by appropriate computations.

Among the first to use this approach was Harless (1860) who assumed a known specific gravity on the basis of previous research, and determined the weight and the location the center-of-gravity of each segment by computation.

Matsui (1958) derived a method for determining the weight and center-of-gravity location of geometric solids representing 18 body segments. The volume of each segment was computed from anthropometric measurements and divided into two parts, the bone volume and the muscle volume. The mass of each segment was then computed by adding the product of the bone volume and the bone density to the product of the muscle volume and the muscle density. For male subjects, 1.418 and 1.076 were used as the "bone density" and "muscle density" values, respectively. Matsui found good agreement between his bone volume measurements (determined using X-rays) and those obtained by a previous Japanese worker and between his computed segment masses and those reported by Braune and Fischer (differences of less than 1%).

King, Patch, and Shinkman (1961) assumed that a human body could be represented by a stick figure composed of seven rigid segments free to rotate about seven fixed points of articulation. He used segment masses and center-of-gravity locations reported by Lay and Fischer (1940) (derived from the data of Braune and Fischer) and determined the extent to which the center-of-gravity deviated from a standard location when a variety of body positions were assumed. Comparison of results obtained using the model with corresponding results obtained by Swearingen (1962), revealed large discrepancies.

Kulwicksi, Schlei, and Vergamini (1962) developed a model consisting of six right circular cylinders (two arms, two legs, torso, and head) in order to evaluate the effectiveness of certain movements in producing rotation while in a weightless state. The linear dimensions of the model were based on the 50th percentile data obtained by Hertzber, Daniels, and Churchill (1954) in their survey of U.S. Air Force personnel and the weights for each segment were based on the mean weights for Dempster's (1955) cadavers.

Whitsett (1963) constructed a mathematical model consisting of 14 segments for the purpose of studying man's mechanical behavior in some selected conditions associated with weightlessness. The dimensions of the segments were determined by direct measurement from the subjects, the masses of the limbs by using Barter's (1957) regression equations, and the locations of the segment center-of-gravity by using Dempster's (1955) cadaver data and by assuming coincidence with the midpoint of the segment length on the axis of symmetry.

Hanavan (1964) designed a 15-segment mathematical model to predict the inertial properties of the human body in any fixed body position (Figure 2.23). The dimensions and properties of the segments (head, upper torso, lower, torso, and 12 limb segments) were calculated using a total of 25 anthropometric measurements taken on the individual subject. The weights of the segments were computed using the regression equations derived by Barter (1957) with corrections to ensure that the sum of the segment weights was equal to the weight of the whole body. He concluded that the average results were within approximately 10 percent of the experimental data. When coordinates of the whole body center-of-gravity were determined using the model and then compared with those for the corresponding positions in the study of Santschi et al. (1963), it was found that generally one-half of the predicted values fell within 0.7 in. of the experimental data.

Jensen (1978) developed a model representing the segments of the body as elliptical zones two centimeters wide so as to effectively follow the shape fluctuations of the segment (Figure 2.24). The model consisted of 16 segments (head, neck, upper trunk, lower trunk, and 12 limb segments), and the division of each segment followed the procedures recommended by Dempster (1955) but with the sections modified so that they fall in the X Y plane (Figure 2.24). The accuracy of the method was evaluated by

SEGMENT	NUMBER(S)	CONSTRUCTION
HEAD	1	right circular ellipsoid
UPPER TORSO	2	right elliptical cylinder
LOWER TORSO	3	right elliptical cylinder
HAND	4, 5	sphere
UPPER ARM	6, 7	frustum of right circular cone
LOWER ARM	8, 9	frustum of right circular cone
UPPER LEG	10, 11	frustum of right circular cone
LOWER LEG	12, 13	frustum of right circular cone
FOOT	14, 15	frustum of right circular cone

Figure 2.23. Schematic illustration of the Hanavan model with description of specific segments (Adapted from Hanavan, 1964).

Figure 2.24. The sectioned body in X and Z plane (Jensen, 1978).

comparing the estimates of total body mass with the mass as measured on a weigh scale. The results indicated less than 2% error.

Hatze (1980) suggested the use of an alternative computational model for the estimation of inertial parameters for 17 body segments including the shoulders as separate entities (Figure 2.25). He listed several advantages of this model over previous models and attempted to confirm its accuracy by comparing experimentally determined parameter (values with predicted values for four subjects). Some of the advantages are; the model subdivides segments into small mass elements of different geometrical structures, thus allowing the shape and density fluctuations of a segment to be modeled in detail; in general, no assumptions are made on segmental symmetry, and principal axes transformations are performed whenever necessary; the model differentiates between male and female subjects; the input data errors are drastically reduced by performing direct anthropometric measurements rather than indirect measurements from photo images; the overall accuracy of the model is better than 3% (when computed parameter values are compared with the corresponding values as determined experimentally) with a maximum error of about 5%.

Recently, MacKinnon and Winter (1993) constructed a mathematical model consisting of 14 segments to investigate the control of balance and posture in the frontal and sagittal planes during human walking. Thirty-one reflective markers were used to define a whole body center-of-gravity model. The locations of the external and extrapolated internal markers are shown in Figures 2.26(a) and 2.26(b). Internal landmarks were estimated at the mid-metatarsalphalangeal, subtalar, hip, L4/L5 and C7/T1 joints, mid-tibial plateau, mid-femoral condyles and mid-head. Internal landmarks at the knees, C7/T1 and head were calculated as the midpoint between markers as shown in Figures 2.26 (a and b). The mediolateral location of the mid-metatarsalphalangeal joint center was determined as the point of intersection of a line between the toe marker and subtalar joint center and the perpendicular line to a marker placed on the lateral border of the head of the fifth metatarsal. The subtalar joint center was estimated by extrapolating down 1.9 cm (Isman and Inman, 1969) and perpendicular to the midpoint of the line between markers place on the lateral and medial malleoli. The mediolateral location of the hip joint center was determined by extrapolating medially 19.7 %

Figure 2.25. Lateral and anterior view of 17-segment anthropomorphic model (Hatze, 1980).

Figure 2.26 (a and b). The locations of the external and extrapolated internal markers (MacKinnon and Winter, 1993)

(Brinckmann et al., 1981) of the distance between the right and left anterior-superior iliac spines. The vertical and anterior/posterior location of the hip was determined using the coordinates of the greater trochanter marker. The medial/lateral location of the L4/L5 landmark was estimated at the midpoint between the right and left anterior-superior iliac spines. The L4/L5 joint center was estimated anterior and posterior to a mid-posterior superior iliac spinal marker and 38% of the mid-posterior superior iliac spines to mid-anterior-superior iliac spines (distance based on a small sample of normative radiographs). The internal and external landmarks allowed the definition of a 14-segment whole body model which included phalangeal, foot, lower leg, thigh, pelvis, abdomen and thorax, head and neck, upper arm, and forearm and hand segments. Anthropometric estimates of each segment's mass, and center of mass were calculated using the tables provided by Winter (1990) and Zatsiorsky and Seluyanov (1983, 1985). Utilizing frontal and sagittal models, trajectories of the whole body center-of-gravity was projected on to the transversal plane.

2.2.2.5 Imaging Studies

Photographic techniques for determining body volume have also been reported by Jensen (1978). The technique utilizes the stereophotogrammetry (different planes) and monophotogrammetry (same plane) combined with values for density of the human body to determine the location of the center-of-gravity of a human body or its segments.

More recently, Brooks and Jacobs (1975) used gamma mass scanning as a means of quantifying mass distribution in animal segments while Zatsiorsky and Seluyanov (1983, 1985) applied the same technique in analyzing human body segment inertial characteristics. This technique involves the use of a gamma ray scanner to monitor the radiation (emitted from a cobalt 60 source) passing through the body under investigation.

Huang and Wu (1976) developed a technique by which tissue densities could be estimated *in vivo* using computerized tomography (CT). Their results showed good agreement between bone, muscle, and fat densities published in the literature and those determined from cross-sectional CT scans of the head and chest. Huang et al. (1979) and Huang and Suarez (1983) extended the use of CT technology to a consideration of mass distribution in both human and animal specimens. By first defining the boundaries of

different tissues in a CT cross-section, the inertial characteristics of the individual tissues and whole segments were subsequently computed from tissue density and volume data. Rodrigue and Gagnon (1983) employed CT to estimate forearm density for 20 human cadaver segments. Based on a series of transverse CT images, they calculated density estimates that were within 4.81% of criterion values obtained by direct measurement. Martin, Mungiole, Marzke and Longhill (1988) used magnetic resonance imaging (MRI) technique to measure inertial properties. This technique (MRI) is based on the specific orientation of the magnetic moment (dipole) of hydrogen nuclei for a particular tissue when the body is placed in a magnetic field (Pykett, 1982). The magnetic moment generates an electromagnetic force that is detected by a receiver coil interfaced with a computer. Computer generated pictures depict the cross-section of the body through which the magnetic field passes. Each tissue shows up as specific shades of brightness (white to black), depending on the orientation of the magnetic dipole. The results indicated that there was close agreement between criterion and MRI determined values for mean segment center of mass location.

2.2.3 Selecting a Center-of-Gravity Modeling Method

The preceding review clearly indicates that there are a wide range of direct methods and a large amount of segmental data that one might use in determining the location of the center-of-gravity of a human body. Choosing methods or sets of data (from the literature) depends on several factors. Among these are: (1) the degree of accuracy required; (2) the characteristics of the subject, or subjects, involved in the study; (3) the nature of the body positions for which center-of-gravity determinations are required; (4) the number of subjects and the extent to which they are available for testing.

2.2.3.1 Accuracy

The accuracy of several of the methods and sets of segmental data reviewed above has been called into question due to some cases the techniques used were crude, in others because the computations involved were based on false assumptions, in others because the reporting of procedures and/or results was incomplete. The methods or data reported by Bernstein (1967), Borelli (1680), Braune and Fischer (1889), Cleaveland

(1955), Hanavan (1964), Weinback (1938), and Whitsett (1963) can be dismissed as unsuitable for the purpose of the whole body center-of-gravity modeling (Hay, 1973).

2.2.3.2 Characteristics of Subjects

If data gathered in a cadaver study are used, one must assume that the segment weights and center-of-gravity locations of the cadaver do not differ significantly from those of the living subject. If data from immersion, reaction board, or mathematical modeling studies are used, assumptions must be made about one or more of the segment densities, the segment center-of-gravity locations, and the geometry of the segments. However, at the present time there is very little evidence to support or refute any of these assumptions. Therefore, in the absence of any clear-cut guidelines concerning the validity of these assumptions, and to control other factors, it would be logical to select the data which has been gathered on subjects who most closely approximate the subjects under investigation in age, height, weight, sex, race, physique, and health status which influence the location of the center-of-gravity.

According to Hay (1973), investigators conducting studies with college-age male subjects might be best to use data from the immersion study of Dempster (1955); those using college-aged female subjects, the data of Plagenhoef (1971) (Table 2.9); and those using older subjects, data from the cadaver studies of Clauser et al. (1969) or Dempster (1955).

2.2.3.3 Nature of Body Positions

The body positions for which center-of-gravity determination are required exert a limiting influence on the methods that may be used (Hay, 1973). For erect standing, back-lying, and a limited range of other positions, any of the available methods may be used. For more complex body position, the direct methods are unsuitable because the subject cannot put his body in a static position and therefore, indirect methods should be utilized.

2.2.3.4 Number and Availability of Subjects

In arriving at the best method to employ, the number of subjects for whom it is desired to determine center-of-gravity locations and the availability of subjects must be

Table 2.9. Body segment percentages of total body weight for living women (adapted from Pagenhoef and Kjeldsen, 1971).

Segment	Subjects		
	College age	Dancers	Gymnasts
Hands	1.0	1.0	1.03
Forearms	3.1	2.9	3.21
Upper arms	6.0	5.8	5.49
Feet	2.4	2.7	2.48
Shanks	10.5	11.0	10.98
Thighs	23.0	24.3	16.52
Whole trunk (including head and neck)	54.0	52.3	60.24

considered. If there are only a few subjects involved, and if these subjects are readily available, it may be feasible to determine their individual segmental characteristics using an immersion or reaction board technique and to use this data in determining the required center-of-gravity locations by the segmental method. If there are a large number of subjects involved, using data gathered on other subjects, would be the most practical proposition.

2.2.3.5 Other Factors

Stijnen, Spaepen, and Willems (1977) investigated methods for the determination of the center-of-gravity of the human body from film. They used data relating to the position of the segmental centers of gravity, and the masses of these segments to locate total center-of-gravity of the body. They varied number of segments and segment mass data from the literature and concluded that the position of the center-of-gravity determined on the basis of film analysis coincides with the position of the gravity line obtained from the force plate data when more body segments were taken into account. In addition, for realistic simulations of gross body motions a fragmentation of the body into a minimum of 10 segments (trunk, head, arms, forearms plus hands, thighs, legs plus feet) is essential (Hatze, 1979). More refined models further subdivide the trunk into a lower and upper part, and include hands and feet (e.g., the 15-segment model of Hanavan, 1964), and the neck (16-segment model of Jensen, 1978) as separate segments.

2.3 Tribology

Slip resistance of shoe soles and the underfoot surfaces is important for human locomotion and pedestrian safety. An adequate frictional force is required to prevent slipping and tripping. Slip resistance is defined as the frictional force opposing the movement of an object across a surface (ASTM, 1975). This includes forces opposing movement in both static and dynamic phases of foot contact. The fundamental idea of slip resistance is that a slip will occur whenever the frictional force opposing the movement of an object is less than the shear force of the foot.

The tribological approach deals with surface dissipative processes in terms of hydrodynamics of contaminants between the shoe and the floor and viscoelastic characteristics of the shoe heel and sole materials (Andres and O'Connor, 1992). The

tribological approach to fall accident prevention has concentrated on the static and dynamic coefficient of friction between the shoe and floor surface.

In the following sections, a review of friction (dynamic vs. static) and slip resistance measurement devices are discussed.

2.3.1 Coefficient of Friction (COF)

The force developed between two contacting surfaces which acts parallel to the contacting surfaces and resists any sliding of the materials is referred to as the force of friction. The three laws describing the force of friction when one solid body slides over another, the frictional force are;

1. the frictional force is proportional to the load (normal force), and the constant proportionality is termed the COF (μ),
2. the frictional force is independent of the area of contact, and
3. the frictional force is independent of the sliding velocity.

The first two laws were stated by Leonardo da Vinci and rediscovered in the 1690s by Guillaume Amontons. The third law was first expressed in 1785 by Charles Augustin de Coulomb. Rabinowicz (1956) stated that if the three laws are correct, then friction will depend only on the applied load, and for any given materials the coefficient of friction will be constant under all conditions. However, since friction is not independent of sliding speed, the coefficient of friction between two bodies may vary as much as 30% to 50% according to the velocity of motion (Rabinowicz, 1956). In the early nineteenth century, Morin (1835) introduced the concept of static friction and kinetic friction. He concluded that since the frictional force resisting the start of motion for two bodies at rest was greater than the resistance after objects were in motion, there should be two coefficients of friction. By 1943, investigators realized that there must be a transition from static to kinetic friction (Sampson, Morgan, Reed, and Muskat, 1943). Today, as a result of work by a number of investigators, the variability in the static versus the dynamic COF is confirmed (Figure 2.27). In most engineering applications, static COF is greater than dynamic COF. The static COF varies regularly as a function of the static application time (adhesion of the two component forces) and the dynamic COF drops off as the sliding velocity increases (Figure 2.28).

Figure 2.27. Friction concept related to the velocity of sliding between two surfaces (in Brungraber, 1976, as adapted from E. Rabinowicz, 1956).

Figure 2.28. Coefficients of low-velocity dynamic friction of a natural rubber compound measured wet and dry against steel, plotted on a logarithmic scale of velocity (James, 1980).

The coefficient of friction (COF) is defined as a ratio of the foot's horizontal shear force (required to start or supporting a sliding motion) divided by the foot's vertical normal force (Chaffin, Woldstad, and Trujillo, 1992). COF is commonly used to describe the degree of traction between the sole and floor materials, and will vary depending on individual and task-related factors as well as the contact materials (e.g., rubber, leather).

The coefficient of friction also corresponds to the tangent of the angle θ between the leg and a vertical line (Sherman, 1986) (Figure 2.29). Figure 2.29 represents the force vectors (F_H, F_v, F_L) applied by the foot during the heel contact phase in normal level walking. Force F_L is applied when the foot lands on the floor, and can be represented by two forces at right angles to each other F_v (vertical force), and F_H (horizontal force). F_H is equal to $F_L \sin \theta$ and F_v is equal to $F_L \cos \theta$. As stated above, by definition the coefficient of friction is the horizontal force required to cause motion divided by the vertical force:

$$F_v = F_L \cos \theta$$

$$F_H = F_L \sin \theta$$

$$\text{therefore, COF} = F_H / F_v = F_L \sin \theta / F_L \cos \theta = \tan \theta . \quad \text{Eq. 2.9}$$

(The angle θ is determined by the length of the leg (L) and the 1/2 step length.)

Given the first classic law of friction: $F = \mu F_N$, and safe walking condition

(when COF is greater than the ratio of the horizontal and vertical force components applied to the floor (Carlsoo 1962)) : $\mu > F_H / F_v$, by combining two formulas the latter can be expressed;

$$F / F_N > F_H / F_v . \quad \text{Eq. 2.10}$$

Consequently, if the magnitude of the F_H and F_v , as well as the COF (μ) for actual shoe-lubricant-flooring combinations are known, it is possible to evaluate whether this combination is potentially hazardous from the viewpoint of slipping or not (Gronqvist, Roine, Jaroinen, and Korhonen, 1989). During normal level walking COF values shown in Figure 2.30 are typical, and the minimum requirement for the COF (normal, level walking) is 0.15-0.30 (Perkins, 1978; Strandberg and Lanshammar, 1981; Bring, 1982). If walking is more rapid than normal speed (stride length is longer and

Figure 2.29 Frictional (F_μ) and normal (F_n) force vectors vs. horizontal (F_h) and vertical (F_v) force vectors applied by the foot during the heel contact phase in normal level walking (adapted from Gronqvist et al., 1989).

Figure 2.30. Typical required COF values for walking without slipping are shown (bold curve) with a microslip recovery shown by a thin line (adapted from Strandberg and Lanshammar 1981.)

θ increase therefore, required COF increases (Figure 2.31), the value increase to about .40 (Chaffin, Woldstad and Trujillo, 1992).

2.3.2 Static versus Dynamic COF

Whether the static COF or the dynamic COF provides a better estimate of the degree of slipperiness has been studied in depth in various experiments. Many studies in the field of kinesiology have indicated that in normal walking conditions there is little or no relative movement between the foot and the floor (James, 1983). Perkins (1978) suggested that no movement between the shoe and ground occurs when both the heel and sole of the shoe are in contact with the ground. Therefore, many researchers (Luijen and Feld, 1973; Brungraber, 1977; Pooley, 1978; Gooch, 1981; Chaffin and Andersen, 1984; Rhoades and Miller, 1988) suggested that static COF should be incorporated for the studies of slips and falls. Ekkubus and Killey (1973) suggested that static COF is related to normal walking conditions and dynamic friction would only be valid after the foot has started to slip.

However, Brough, Malkin, and Harrison, (1979) utilizing high-speed cine photography found evidence of both heel and toe slip, and stated that slipping did not occur from a static position, but rather was rapid acceleration from an initial slow movement. Strandberg and Lanshammar (1981) also found small but non-zero values of the horizontal heel velocity at heel strike and stated that sliding motions are common and can be tolerated up to a certain level without disturbance of the gait pattern and without falling tendencies. Perkins and Wilson (1983) re-suggested that slip at peak 1 is influenced by a dynamic friction coefficient due to the shoe never stops moving at heel contact (refer back to Figure 2.5). Biomechanical analysis performed by Perkins and Wilson (1983), Strandberg (1983), Andres and Chaffin (1985), and Tisserand (1985) has indicated that the occurrence and severity of a slip depends not only on the friction when slip starts, but on how the friction varies as a slip progresses. In other words, dynamic COF may be of interest as well, in particular how it changes as the speed of the slip increase.

Figure 2.31. Calculated relationship between step length and coefficient of friction necessary for stability (James, 1983).

2.3.3. Friction Measurement

To protect people from slipping and falling, various groups have proposed that minimum values be set for the COF under standardized test conditions. In other words, by standardizing the shoe and floor conditions, applying a normal load, and measuring the resulting frictional force, the COF could be measured. In essence, these standardized COF values can be used to establish the slip hazard level for a given shoe or floor. However, the methods for determining the COF value for a particular shoe or floor material have not been standardized at the present time. This is mainly due to the many factors involved in establishing a safe coefficient of friction to prevent slips and falls. These factors can be divided into four categories (Pfauth and Miller, 1976; Tisserand, 1985):

1. Factors related to the floor surface, such as,
 - a. nature of surface,
 - b. surface relief of wear (roughness, smoothness),
 - c. exposure to exterior environmental conditions (temperature and humidity);
2. Biomechanical and psychological factors, such as,
 - a. various foot force distribution in individual movement pattern (walking velocity, slipping velocity, and contact area of sole),
 - b. physical and neurophysiological capacity of the subject (response of individual to sudden change in floor characteristic),
 - c. judgment and evaluations made by the subject (slipperiness of floor);
3. Task factors, such as,
 - a. types and frequency of static and dynamic manual tasks,
 - b. required changes in elevation and direction of movement;
4. Characteristics of shoe, such as,
 - a. nature of sole,
 - b. surface relief and shape of sole,

- c. wear and tear,
- d. static and dynamic mechanical characteristics.

In essence, designing an effective and accurate mechanical device to measure COF (slip resistance) of shoe sole means fixing values for each of the variables associated with factors (1), (2), and (3) and arriving at an overall value for point (4), characteristics of shoe (Tisserand, 1985). However, the above variables are so numerous that the resulting combination of factors would give rise to an infinite number of slip COF (values). Noting this enigma, Tisserand (1985) suggested a need for a scientific approach to the problem and, in particular, an experimental rather than empirical approach to obtain a meaningful coefficient of friction measurement.

In particular, the following factors have been recognized as affecting COF values during the last decade (psychophysical factors will be explained in next section).

2.3.3.1 Velocity of contacting surface

As mentioned earlier, when the heel contacts the ground during the gait phase, the heel-floor closing velocities may exceed .5 to 1 m/s. Under some combinations of shoe/floor materials, contaminants, and surface geometry, the static and dynamic COF values change due to the velocity. For example, James (1983) showed that natural rubber (NR) on a smooth steel plates responds entirely different when wet compared to dry conditions. Under very slow velocity <.1 cm/min, the values are almost equal, however, as the velocity increases the wet surfaces exhibit lower COF values. This is attributed to the natural rubber (NR) cutting through the film of water at slow speeds so that friction can approach the value obtained on the dry surface. As the speed increases, water cannot be expelled fast enough and the shoe rides on a cushion of water. Friction is consequently reduced. In this case, it is clear that the static COF values would not help in rating the slip hazard. Therefore, many investigators recommend testing materials under both static and dynamic conditions.

2.3.3.2 Normal load on contacting surface and contact time

Bring (1964) and Caubet (1964) established that μ_s varies regularly as a function of the static application time of the two component forces. The basic underlying

assumption in computing the COF is that the friction value increases proportionally to the normal force holding the contacting surfaces together, however due to adhesion and deformation forces, under some circumstances this may not be true (Chaffin, Woldstad and Trujillo, 1992). One way to look at the process that creates the frictional force is to decompose it into two separate but additive components (contacting surface and contact time) (Tisserand, 1985). Adhesion depends upon the time the two materials are in contact. Contact time appears to increase the static COF (a sticking effect); however, under most walking conditions (due to very fast shoe-floor contact time during walking), this is not a major factor compared to when one stands in one place for several minutes (Irvine, 1986).

Deformation of the contacting materials is affected by the stiffness of the materials, contact area, and normal loads applied. Gronqvist, Roine, Korhonen, and Rahikainen, (1990), stated that the reason that floor surface roughness measures correlate with dynamic COF values is due to deformation forces (i.e., rougher the floor, the higher the COF). Heel contact area does not significantly affect deformation forces due to the fact that the actual heel contact area is small during the heel strike (Chaffin, Woldstad and Trujillo, 1992). The effect of the normal load applied varies with shoe sole/floor materials (i.e., when a soft material such as crepe is loaded heavily on a rough surface, the deformation force effect on friction will be larger than when using a smooth surface or harder sole materials).

2.3.3.3. The Effect of Contamination

Any fluid contaminant between two sliding surfaces will provide lubrication and thereby lower the dynamic COF values (Chaffin, Woldstad and Trujillo, 1992). The presence of contaminants, which act as modifiers, will change both the slip resistant characteristics of a physical structure's surface and also the characteristics of the user's heel/sole surface. In essence, the fluid will behave as a hydrodynamic squeeze film, and in this context, lubricating qualities are dependent on the following conditions (Chaffin, Woldstad and Trujillo, 1992, adapted from Proctor and Coleman, 1988):

1. Area of the contacting surfaces. The larger the area, the lower the dynamic COF values because the lubricant is not easily squeezed out.

2. Roughness of surfaces. The size shape, and number of surface irregularities can allow the fluid to drain effectively, and hence improve dynamic COF values, compared to a smooth surface.
3. Velocity of the surface motions. Higher velocities will tend to trap fluids, but very slow velocities will allow time for fluids to drain.
4. Vertical loads. The greater the compressive forces acting on the fluid, the greater the amount of fluid squeezed from between the surfaces.
5. Fluid viscosity. The higher the viscosity, the longer the time required for the fluid to drain from between the surfaces.

2.3.4 Slip Resistance Measuring Devices

There have been many apparatuses developed by individuals, organizations, and federal agencies (e.g., OSHA, NIOSH, and NBS) intended to quantify slip resistance (i.e., COF). At least 70 different meters have cited in the literature (Strandberg and Lanshammar, 1985); however, none of these devices are universally accepted. In general, most devices fall into three categories, drag/towed-sled, pendulum, and articulated strut types.

There are two approaches to measuring friction. In the direct approach, the test device measures or indicates the horizontal and vertical forces. These include drag-type meters and articulated strut devices (Figure 2.32). The indirect approach calculates the frictional force by observing an energy loss in the test device. The most common example of the indirect approach is a pendulum-type device.

2.3.4.1 Drag-Type Meters

This type of device slides a weight of known value mounted with a footwear sole sample across the test surface. The device is pulled either manually or by a motor at an adjustable speed. It is the most common type of slipmeter due to its simplicity, portability, and ease of use. The COF is derived by dividing the force required to start motion or maintain motion by the weight of the sled (normal force) (Figure 2.32-a). Most frequently cited drag type devices include; the Horizontal Pull Slipmeter (HPS; ASTM F 6098-79), the Dynamometer Pull Meter (ASTM C 1028-84), the BigFoot

a. DRAG TYPE METER

b. ARTICULATED STRUT DEVICE

c. PENDULUM DEVICE

Figure 2.32. Typical friction measurement devices.

designed by Safety Sciences, Inc. (1977), the CEBPT Skidmeter (Majcherczyk, 1978), and the Tortus Floor Friction tester developed in Europe.

2.3.4.2 Articulated Strut Devices

These devices consist of a weight attached to a shaft articulated at an angle. A known vertical force is applied to a shoe faced with shoe sole or heel materials. An increasing lateral force is then applied until slip occurs. The ratio of lateral force at slip to the known vertical force is the COF. In Figure 2.32-b, there are three ways of going from the initial position to the position at the instant of slip.

1. The shoe can be pushed/pulled to the left until slip occurs (dynamic friction, Hunter Machines).
2. The floor surface can be moved to the left until the shoe slips (static friction, James Machines).
3. The weight can move to the right until the shoe slips (Static Friction, NBS-Brungraber Tester).

The James Machine developed by S. James of Underwriter Laboratories in 1951, remains to this day the industry standard method ASTM (D 2047-75) for testing manufactured floor surfaces and finishes.

2.3.4.3 Pendulum-type Tester

In a pendulum-type tester, a pendulum, faced with a shoe sole or heel material sweeps a path across a flooring surface. The potential energy of the pendulum at the beginning of a swing and its residual energy at the end of a swing can be determined from the known weight and position of the center-of-gravity of the pendulum. The difference, or loss in energy, is equal to the work done in sliding the contact material over the walkway surface, which is the average contact friction force times the distance of contact. By definition, the average frictional force is equal to the coefficient of friction times the average force normal to the plane of contact. From these relationships, an equation can be established for the coefficient of friction in which all factors except the scale reading at the end of the swing are known constants of the instrument (Figure 2.32-c).

The above measuring devices are limited in their ability to simulate biomechanical factors for accurate DCOF measurements. Strandberg and Lanshammar (1983) stated that on the basis of tribology and biomechanical analysis of slips and falls, the slip-resistance meter should reproduce the following operating variables from crucial gait phases:

- a. Contact time and normal force time derivative-for the influence of surface patterning and its drainage capability;
- b. Foot angle-for testing the most critical part of the shoe;
- c. Contact force application point at the shoe;
- d. Vertical force-for correct pressure in the contact area;
- e. Sliding velocity-for correct dynamic friction forces.

2.3.4.4. Others

Other types of measuring devices include: the Programmable Slip Resistance Tester, Universal Friction Testing Machine, and Multicomponent Quartz Force Plate. The Programmable Slip resistance Tester (PRST) was developed by Bidanda and Redfern (1991). This device allows slip resistance measurements to be performed under varying conditions that better reflect the interactions of the shoe and floor during human gait (Figure 2.32). The Universal Friction Testing Machine (UFTM) was developed as a prototype by NIOSH, but never put in production. The UFTM was a motor-driven device with two disks of identical footwear materials, mounted on a rotatable arm to slide over a sample floor surface. It measured the torque required to rotate the specimens and displayed the static and dynamic COF on a digital meter. Unfortunately, it suffered from serious reliability problems and was never commercially produced. The Multicomponent Quartz Force Plate manufactured by Kistler Instrument of Switzerland, measures the magnitude and direction of the ground to foot reaction force in three component forces, the static and dynamic COF as well as the point of force application or center of pressure during foot contact.

2.3.4.5 Comparisons

The versatility of different meters has been compared and commented on by many investigators (National Research Council, 1961; Bring 1964; Brungraber, 1976; Braun

and Brungraber, 1978; Bring, 1982; Cohen and Compton, 1982; Andres and Chaffin, 1985). Due to its heavy weight and bulkiness the James Machine can be only used in a controlled laboratory situation for testing sample floor material, not the actual floor. The NBS-Brungraber Tester, on the other hand, is easier to handle and can be considered as a portable James Machine. Tortus provides a permanent trace record when connected to a chart recorder, whereas most devices provide only a visual reading of the peak COF (analogy meter or gauge). However, overcoming most limitations, drag-type devices have generally met with the greatest acceptance among researchers and practitioners.

2.4 The Psychophysical Approach

Many investigators have documented the kinematics of the shoe/floor interaction. However, these models are strictly mechanical and do not take into account the neurological mechanisms of the humans inside the shoes. Many investigators confirmed that there is a relationship between kinematic change and behavioral change (when walking onto a slippery surface) (Tisserand, 1969, 1985; Strandberg and Lanshammar, 1985; Harris and Shaw, 1988; Leamon and Li, 1990; Swensen et al., 1992; Myung et al., 1993; Cohen and Cohen, 1994 a-b). Modification in muscle activity patterns when walking on different surfaces with varied friction give further proof that the person wearing the shoes can affect the outcome of exposure to slippery situations (Andres et al., 1991). Also, research into postural responses to transient perturbations has demonstrated that the walking human can adapt rapidly to many types of balance challenges (Nashner, 1982; Dietz et al., 1985). In the following sections, factors affecting the perception of slipperiness such as visual and tactile sensation are discussed.

2.4.1 Perception of Slipperiness

Attempts have been made to determine factors that influence people when they are walking. Carlsoo (1962) has studied human gait and whether or not different floor hardness can cause different patterns of walking with different muscle coordination and muscle-load. The results suggest that differences in muscle activities did exist for floors of different hardness. In addition, when potentially hazardous conditions are perceived

Figure 2.33. Diagram of the PSRT device and control (Redfern and Bidanda, 1993).

through visual and tactile sensation, or expected to exist in walking person's perceptual field, one's walking gait is adjusted accordingly (Ekkebus and Kelly, 1973; Swensen et al., 1992). The length of stride is shortened, which consequently produces low foot velocities and smaller foot shear forces, as the body's center-of-gravity is better maintained. The ground reaction force during the heel strike and the toe-off phases is also significantly reduced to diminish the likelihood of slipping.

2.4.1.1 Vision

The visual field is an important psychophysiological parameter involved in gait regulation. Studies of the human visual mechanism have indicated that the visual field of a walking person is dynamically changing and only a small part of the effective visual field is attended to. In other words, the attention is divided in such a way that the first priority is given to objects falling within the effective visual field. Therefore, if a slippery condition is not detected within one's effective visual field (usually 10-15 feet ahead), the likelihood of fall accidents is significantly increased (Zohar, 1978).

The optic flow field effect (Lishman, 1981) provides an explanation of how an individual's judgment of velocity and displacement of surrounding objects (during walking) can affect perception of tripping hazards. For example, if one is trying to catch a ball thrown toward oneself, the apparent diameter of the ball increases, since the size of the retinal image is also increased, and the brain seems to calculate the time of arrival of the ball from the rate of change in size of the retinal image. Thus, utilizing the optic flow field effect, judgment of the velocity and distance of approaching objects are effectively managed. However, judgment will be altered if a finite object is not in view (such as, an infinitely long corridor which has uniformly painted walls and ceiling, and an unpatterned carpet on the floor). In this situation, if there is a tripping hazard such as a step in the corridor, or someone has dropped something, then judgment of its (tripping hazard) distance can be hampered, resulting in potential danger of tripping and falling accidents.

2.4.1.2 Static versus Dynamic COF (Tactile)

Tisserand (1985) suggested that frictional values are estimated and memorized unconsciously from preceding steps (one's own model of slipperiness) and this

information is updated whenever subject feels the floor conditions are different from expected (reality). Therefore, if there is a discrepancy between the model and reality (failure of the evaluation system) slip and fall might result. Myung and Smith (submitted) also concluded that the subjective evaluation of floor slipperiness is sufficient to discriminate the differences among slippery floor surfaces.

Tisserand (1969) found that rank order correlation with subjective judgments of slip-resistance were negligible for static COF measurements and very high for dynamic COF measurements. Recently, Harris and Shaw (1988) found high correlation between (walker's) opinions of slipperiness and the kinetic friction of wet floors. Their results are in close agreement with Strandberg and Lanshammar's (1985) walking experiments demonstrating that kinetic friction values, measured with sufficient sliding velocity, correlated better with the actual risk of falling than low-speed kinetic friction values or static friction values. Another study by Swensen et al. (1992) compared the perceived slipperiness of steel beams by both professional iron workers and students. They were asked to rate and rank the slipperiness of each beam that were either uncoated or coated with contaminants (water, clay, oil) after walking across the beams. The results of this study indicated that there is a strong correlation between dynamic COF values and subjective ratings of floor slipperiness. Figure 2.34 shows the result of a series of experiments using ten subjects and five different shoes. The mean subjective ranking and the ranking using the dynamic COF are very similar (Tisserand, 1972a).

2.4.1.3 Visual versus Tactile Sensation

Recently, Cohen and Cohen (1994a) further explored the perceptual and cognitive factors involved in the perception of floor tile surface slipperiness. The results of this study also demonstrated that tactile cues are most sensitive to physical measurement of dynamic COF. A follow-up field study (Cohen and Cohen, 1994b) of the psychophysical assessment of the perceived slipperiness of floor tile surfaces concluded that people tended to make predictions about the slipperiness of walking surfaces and verified these expectations as they crossed them. The results suggests that visual cues to slipperiness are inferior to tactile sensation. They also suggested that in real-world conditions, the perception of walking surface slipperiness is probably the result of tactile cues, with

RELATIONSHIP BETWEEN μ_s , μ_k AND SUBJECTIVE MARK

Figure 2.34. Comparison of mean subjective ranking by ten subjects and ranking using static and dynamic COF for five shoes. Subjective binary choice test. (Tisserand, 1985).

visual impressions being confirmatory. Thus, in unfamiliar conditions, people may rely on the primary but inferior visual information about a surface's traction until they actually walk on it. The potential for an accident can be created due to misjudgment of slipperiness based on initial visual sensing and the limited time available to make immediate adjustments in gait to accommodate for the hazardous condition.

2.5 Processing Stages During Responses to Falls

Elderly individuals are particularly predisposed to falls due to the many normal changes in aging. Although it is difficult to distinguish clearly between those changes that are specifically due to aging and those that are strongly associated with age, the following section describes the changes commonly associated with the elderly population.

In describing the fall accidents due to the various changes in the elderly, the process stages governing the responses to postural instability (Table 2.10) will be utilized. The processing stages governing responses to postural instability refer to the sensory input or feedforward, the response selection, and the response execution.

2.5.1 Sensory Input

Irrespective of the activity being performed or the environmental factors associated with the time of a potential fall, there are certain processing stages that the central nervous system must undertake if a fall is to be avoided or compensated for (for a safe landing). First, if a potential fall is imminent, sensory input must trigger or alert those centers responsible for response selection. This alerting process may be initiated by one or more of the following sensory inputs; proprioception, vision, vestibular function, and also, may be initiated by feedforward mechanisms.

At the input stage, any age-related disruption in the quality of the signal from the periphery may increase the likelihood of falls. Inputs relevant for balance are vision, proprioception, and vestibular sensations (Lacour, Vidal, and Xerri, 1983; Nashner, 1982).

Table 2.10. A scheme of processing stages during responses to falls.

Processing Stages	Responses
Sensory Input or Feedforward	“Alerting” or “triggering” response selection center that potential fall is imminent.
Response Selection	Corrective response, protective responses
Response Execution	Open-loop, closed-loop

2.5.1.1 Vision

In normal postural control, vision acts as one of three principle reference systems (the others are proprioception and vestibular function). Lishman and Lee (1973) demonstrated the contribution of vision to the primary reference system in the experiments in which postural sway was shown to be synchronized with small (4 mm), low frequency (0.25 HZ) sinusoidal movements of the wall in front of the subject, even though most subjects were not aware of these movements. The central nervous system apparently interprets movement away from the body of a structure that is usually static (and therefore a reliable reference frame) as being movement of the body away from the structure. This leads to compensatory forward sway. Decreases in visual acuity, restriction of the visual field, increased susceptibility to glare, and poorer depth perception have all been demonstrated to occur with advancing age (Fozard, Wolf, and Bell, 1977). As a result, an elderly individual's use of visual reference information will be impaired. For example, narrowing the visual field deprives the elderly person of that part of the field most sensitive to movement, and also, poorer depth perception will make an elderly person less sensitive to anterior-posterior sway-induced changes in the distance between the eyes and stationary objects facing that person (Stelmach and Worringham, 1985).

Visual deficits, then, may result in an increase in the time taken for the visual system to alert the central nervous system to a potential fall. People with visual deficits may need a longer period of visual sampling to accurately assess the rate and direction of the fall, the time to land, and the nature of the surrounding environment.

2.5.1.2 Proprioception, Vibratory Sense, and Vestibular Function

Rabbitt and Rogers (1965) found that elderly individuals utilize afferent feedback systems more than younger individuals in monitoring their movements. They also concluded that proprioceptive deficits are significant in the elderly. Passive movement thresholds for the hip, knee, and ankle in subjects over 50 years of age were found to be twice those for subjects less than 40 years of age (Laidlaw and Hamilton, 1937). Skinner, Barrack, and Cook (1984) used both the reproduction of a passively presented knee angle and passive knee motion threshold detection as indices of proprioceptive

function in subjects between the age of 20 and 82 years. Both indices showed significant age-related declines.

Woollacott et al. (1982) demonstrated the significance of ankle proprioception for balance retention in elderly. They utilized a moveable platform that permitted either stabilization of the visual field or of the support surface (with respect to the subject), or both. This situation was achieved by having a visual surround or the support surface move synchronously with the subject's sway, thereby eliminating visual or proprioceptive cues to movement. Comparing the postural sway of 12 elderly subjects (61 to 78 years) with that of 12 young subjects (19 to 38 years), they found that the elderly had large increases in postural sway when ankle proprioception was eliminated (via moveable platform). In addition, when the subjects had their eyes closed, one half of the elderly subjects lost their balance. This ability of vision to act as a substitute for impaired or absent proprioception was also shown by Fernie, and Holliay (1978), who observed increased mean speed of sway in below and above knee amputees when their eyes were closed. Therefore, it appears that vision takes on a much more important role when proprioception is diminished or rendered unreliable.

One aging deficit that has been frequently found is impairment in vibratory sense. An increase in the threshold for vibration perception has been widely reported (Brocklehurst, Roberson, James and Groom, 1982; Kenshalo, 1977; Kokmen, Bossemeyer, Barney, and Williams, 1977). An important aspect of this deficit is that the lower extremities are most affected. Brocklehurst et al. (1982) found that vibration sense and proprioception were uncorrelated, however, the impaired vibration sense and proprioception were highly correlated. He concluded that impaired vibration sense contributes to postural sway more than any other sensory loss.

The major contribution of the vestibular apparatus to posture is in maintaining the reflex associated with keeping the head and neck in the vertical position and in corrective movements. Although there is agreement on the role of the vestibular apparatus in eliciting fall responses (Melvill and Watt, 1971a, 1971), and in resolving conflicting visual and proprioceptive information (Nashner, 1973, 1982), aging changes affecting vestibular function have not been widely examined.

2.5.1.3 Feedforward

Any voluntary motor act performed during stance or locomotion produces a reaction forces that, if uncorrected, will disturb equilibrium. Many researchers (Belen'kii, Gurfinkel, and Pal'tsev, 1967; Bouisset and Zuttara, 1981; Cordo and Nashner, 1982) have shown that such postural adjustments are preparatory, their initiation precedes the voluntary motor act, and that their direction and magnitude offset the reaction forces produced by the motion. The implication of this sequencing is that the central nervous system is capable of predicting the postural consequences of any particular action including the prediction of an imminent loss of balance. Mankovskii, Lysenyuk, and Mints (1980) has shown that old (60 to 69 years) and very old (90 years and over) subjects show a low correlation between the latencies of unilateral voluntary knee flexion while standing, and the postural adjustments that normally precede them. Especially in rapid movement, the frequency of loss of balance was increased; 0 to 5% for young subject (10 to 29 years); 30 to 60% in old subjects; 50 to 80% in very old subjects.

2.5.2 Response Selection

Simple reaction time (RT) is increased with age (Clarkson, 1978; Gottsdanker, 1980; Kroll and Clarkson, 1978; Loveless, 1980). These findings suggested that older subjects have difficulty in fully preparing a response and maintaining that preparation (Gottsdanker, 1980).

Response selection must be both accurate and timely. If postural instability goes uncorrected, a critical time boundary is soon exceeded, beyond which balance is irrecoverable. This time boundary period is about 300 ms. (Do, Breniere, and Brenguier, 1982) for producing a step forward in response to an unexpected fall. If aging has the effect of even a moderate slowing of response selection, then a large increase in the number of falls could result (Stelmach and Worringham, 1985).

2.5.3 Response Execution

Larish and Stelmach (1982) examined conditions (preparative response execution) where subjects made movements about which they had advance information that was valid or invalid, and found that older subjects reacted and moved more slowly

than younger subjects. Gottsdanker (1980) also demonstrated impaired ability to prepare responses in the aged.

Motor time is the component of reaction time (RT) that begins with the appearance of electromyographic activity and ends with movement initiation. It corresponds to the “electro-mechanical lag” or “rise time” of the muscle involved and allows inspection of how motor processes affect RT. Clarkson (1978) and, Kroll and Clarkson (1978) found that motor time increases with age, especially when the person is physically inactive.

Movement time or the simple duration of movement has been shown to increase with age (Clarkson, 1978; Kroll and Clarkson, 1978; Pierson and Montoye, 1958). The findings suggested that healthier adults have faster reaction (movement) time than less healthy adults of comparable age.

2.6 Epidemiology of Slip and Fall Accidents

The epidemiological approach is concerned with the identification of the incidence, distribution, and potential controls for illness and injuries in a population. A review of slip and fall studies indicate that slipping and tripping are very often the “trigger event” for the fall accidents (Cohen and Compton, 1982; Andersson and Lagerlof, 1983; Manning et al., 1988). Cohen and Compton (1982) conducted an epidemiological investigation (utilizing New York State Workers Compensation data and First Report of Injury) characterizing the most frequent and serious work surface-related injury related to the various industries, tasks, and work surface condition. The results show that the construction trades (e.g., painters, roofers, sheet metal workers etc.) have a higher percentage of injuries associated with falls to different level. While, office and service workers, restaurants, retail stores, hospitals and clothing manufacturers etc., have a higher percentage of injuries associated with falls on same level. Table 2.11 shows the distribution of accidents by the event that immediately led to the injury. The majority, or about 50%, of the cases were characterized as “slip.” Similar findings were reported by Manning et al. (1988), in a study of underfoot accidents in a work population of 10,000 in 1985. They reported a majority of accident that led to the injury (62%) were due to slipping. These events (Table 2.11) resulted in accident types shown in Table 2.12. Fall

Table 2.11. Events that led to the injury.

Events	% of Total Cases
Slip	50
Misstep	14
Loss of support	10
Postural over extension	7
Stumble	4
External force	1
Medical incident	<1
Unknown	<u>12</u>
	100

Table 2.12. Distribution by accident type.

Broad Accident Types	% of Total Cases
Fall on same level	26
Fall to a different level	19
Recovery on same level	14
Struck against object during fall	10
Recovery to a different level	1
Fall unknown	10
Recovery unknown	1
Other	<u>19</u>
	100

on same level ranking the highest with 26% of the total cases (Cohen and Compton, 1983). Similar findings were also reported by Davis (1983), Buck and Coleman (1985), and Tisserand (1985). Table 2.13 shows the distribution by occupational category. Unskilled laborers experienced about 27% of the injuries, and other occupational groups which show a high incidence of fall injuries include various types of skilled, office, and other "white collar" workers (Cohen and Compton, 1983). The type of work surface involved (in an accident) is shown in Table 2.14. The most frequent surface indicated was the "floor" (Cohen and Compton, 1983). Other surfaces frequently involved were: ground (outdoors), stairs, and ladders. Manning et al. (1988), also found 28% of the falls were attributed to floor contamination by liquid, 8% were caused by ice or snow. Similar findings were also made by Cohen and Compton (1983). They found, of the slips, 16% occurred on surface stated to be wet (contamination), 8.1% icy, 6.4% oily, and .7% muddy.

2.6.1 Epidemiology of Slip and Fall Accidents of Older Individuals

Falls and gait instability are among the most serious problems facing the elderly population and constitute a major cause of mortality, morbidity, immobility, and premature nursing home placement (Rubenstein, Robbins, Schulman, Rosado, Osterweil, and Josephson, 1988). Both the incidence of falls and the severity of complications increase after middle age (Campbell et al., 1981). Accidents are the fifth leading cause of death in the older population (aged 65 and older), and falls make up the largest percentage of accidents (over 65%) in this age group (The National Safety Council, 1995). Approximately 33% of the elderly population living at home will fall each year, and about 1 in 40 of them will be hospitalized (Campbell et al., 1981; Exton and Smith, 1977). Of those admitted to the hospital after a fall, only about 50% will be alive a year later (Gryfe, Amies, and Ashley, 1977; Overstall, 1978). Repeated falls are a primary reason for admission of previously independent elderly persons to long-term care institutions (Rodstein, 1964; Smallegan, 1983).

Table 2.13. Distribution by occupational category.

Occupational Category	% of Total Cases
Unskilled laborer	27
Skilled laborer	19
Clerical	8
Transport equipment operator	8
Machine operator	7
Production Worker	7
Manager/supervisor	6
Maintenance worker	5
Service worker	5
Trainee	1
Other occupation	2
Unknown occupation	<u>≤5</u>
	100

Table 2.14. Distribution by type of work surface.

Broad Accident Types	% of Total Cases
Floor	33
Ground (outdoors)	11
Stair	10
Ladder	6
Ramp/slope/incline	2
Scaffold/catwalk	2
Other surface	21
Not stated	<u>15</u>
	100

2.6.1.2 Causes of Falls in the Elderly

A review of the epidemiological literature on falls in the elderly reveals that there is no single type of fall, and little agreement on the etiology of falls. In general, falls are categorized by the associated medical, social, and environmental factors both in the community and institutional populations. The annual incidence of falls among elderly persons living in the community increases from 25% at 70 years of age to 35% after 75 years of age (Campbell et al., 1981). Falls are even more common in institutional (e.g., hospital and nursing home) settings (Rubenstein et al., 1988). Women fall more frequently than men until the age of 75 years, after which the frequency is similar in both sexes (Campbell et al., 1981).

Table 2.15 presents data from various published studies describing the epidemiology of falls in different settings (community-based, hospital-based, and long-term care institution surveys). Persons living in long-term care institutions have the highest rates of falls (.65 to 3.6 per bed annually with 1.65 mean), and hospitals have intermediate rates (.62 to 2.9 per bed annually with 1.5 mean). The lowest rate of falls (.22 to .625 per bed annually) was reported among community-living, generally healthy elderly.

Factors intrinsic to elderly people, the type of activity engaged, and the hazards and demands of the environment contribute to most falls in varying degrees. Causes of fall can be grouped in several ways; by presenting symptom complex (e.g., dizziness, drop attack, slips, etc.), by a precipitating mechanism (e.g., postural hypotension, environmental hazards, etc.), and by underlying risk factors (e.g., antihypertensive medications, decreased vision, etc.). Potential for ambiguity exists due to the different classifications of causes of falls. This might explain the lack of consistency in the falls literature that attempts to classify causes of falls.

Table 2.16 presents data from various published studies providing information on fall etiologies. In general, the “accidents and environment-related” category represents the most common cause in all of the published studies. The next most common cause fluctuates from study to study: “miscellaneous” causes in three studies, postural hypotension (Scott, 1976), weakness (Brocklehurst, 1978), drop attack (Sheldon, 1960), and dizziness/vertigo (Lucht, 1971). The last column in Table 2.16 presents the average

Table 2.15. Incidence of fall in different settings: Review of population-based studies.
(Adapted from Rubenstein et al., 1988).

Reference	Population/ Site (N)	Age	Annual Incidence per 1,000	% of fall w/ fracture
A. Community-based surveys				
Exton-Smith, 1977	Community survey (N=963)	65-69	400	NA
		70-74	510	
		75-79	610	
		80-84	730	
		85-90	750	
Perry, 1982	Apartment complex (N=64)	89% > 70	625	5.0%
Gabell, 1985	2 general practices	>65	224	NA
Simple mean of all surveys			325	
B. Hospital-based surveys				
Scott, 1976	Acute	>60	620	3.5%
Sehested, 1977	Geriatric	91% >60	2,900	4.2%
Morris, 1980	Geriatric	99% >65	1,500	1.7%
Berry, 1981	Chronic	68% >70	1,500	3.2%
Catchen, 1983	Acute	>65	1,900	5.0%
Morgan, 1985	Acute	>65	1,400	NA
Morse, 1985	Acute	NA	840	1.3%
Simple mean of all surveys			1,500	
C. Long-term care institution surveys				
Gryfe, 1977	Residential home	81% >75	650	6.1%
Miller, 1979	Skilled	82.3 (mean)	1,400	NA
Louis, 1983	Skilled	83.3 (mean)	760	NA
Colling, 1983	Skilled	NA	2,600	2.3%
Blake, 1986	Residential home	>60	3,600	NA
Simple mean of all surveys			1,650	

NA = not available

Table 2.16. Causes or types of falls: Review of literature. (Adapted from Rubenstein et al., 1988).

Reference Year	Sheldon 1960	Clark 1968	Lucht 1971	Scott 1976	Exton-Smith 1977	Brodcklehurst 1978	Morfitt 1983	Total
Population	H	H	H/NH	Hosp	H	H	H	
Number of falls	500	450	472	259	190	376	339	2,661
<hr/>								
Primary cause of fall								
Accident/envirn. related	44.8%	44.0%	38.9%	11.6%	27.9%	23.1%	52.9%	36.9%
Drop attack	25.0%	15.6%	-----	1.5%	13.1%	21.3%	-----	11.4%
Postural change/ hypotension	3.6%	2.7%	-----	23.5%	-----	-----	13.0%	5.1%
Syncope	-----	.4%	1.5%	-----	-----	-----	2.0%	1.0%
Dizziness/ vertigo	7.4%	4.0%	19.1%	2.7%	12.1%	-----	6.8%	7.7%
Weakness,balance/ gait	3.2%	-----	12.1%	22.8%	9.5%	29.5%	11.6%	12.3%
Other*	6.0%	25.8%	17.2%	16.6%	37.4%	18.6%	19.4%	18.1%
Unknown	4.6%	6.6%	16.1%	21.2%	-----	7.4%	-----	7.9%

Abbreviations: H=home living; NH-nursing home residents; Hosp=hospital patients.

* This category includes: acute illness, confusion, poor eyesight and drugs.

of all studies combined. However, due to the lack of consistency in terminology and methods between studies, these figures need to be interpreted with caution. Overall, about 55% of falls were related to medically diagnosed conditions, and 37% were related to environmental hazards.

Overstall et al. (1977), in a study of 240 subjects 60 years and over, revealed that the most common cause of fall was due to tripping (47%). This compares with Sheldon's (1960) total for trips and accidental falls of 45%.

2.6.1.3. Fall Injuries in the Elderly

A fall is reported as an underlying cause of about 9500 deaths each year among person's over 65 years of age. Five percent of falls by elderly persons, whether living in the community, or in an institution, result in a fracture (Tinetti, Speechley, and Ginter, 1988; Gryfe et al., 1977). This single diagnosis is the most common among all injuries (in all age groups) leading to hospital admission in the United States (Haupt and Graves 1982). Of approximately 200,000 hip fractures each year, 172,000 (84%) occur in the population 65 and older (Baker and Harvey, 1985).

Each hip fracture result in an average stay of 21 days in a short-term hospital. This is almost double the average stay for all other causes in this age group, and longer than the stay for any other diagnosis. Additionally, 5% to 10% of falls results in soft-tissue injuries such as hematomas, sprains, and joint dislocations that require medical care (Gryfe et al., 1977; Tinetti, 1987).

2.7 Summary

Reducing slip and fall accidents has been a topic of interest for ergonomics researchers since the 1920's. These researchers utilized four approaches to study slipping accidents. The four approaches include; the epidemiological, biomechanical, tribological and psychophysical approaches.

The epidemiological approach is concerned with the identification of the incidence, distribution, and potential controls for illness and injuries in a population. Epidemiological findings suggest that slip and fall accidents are among the most serious problems facing elderly population and constitute a major cause of mortality, morbidity.

immobility, and premature nursing home placement. A review of the epidemiological literature on falls in elderly reveals that there is no single type of fall, and little agreement on the etiology of falls. In general, women fall more frequently than men and persons living in long-term care institutions have the higher rates of fall than community-living, generally healthy elderly. Factors intrinsic to the elderly person, the type of activity engaged, and hazards and demands of the environment contribute to most falls in varying degrees. In general, about half of the falls were related to medically diagnosed conditions and over one-third of the falls were related to environment hazards. In addition, the most common cause of fall was due to tripping.

The biomechanical approach to slip and fall accidents describes the gait parameters (such as; the stride length, slip distance, heel velocity, and foot angle) and the ground reaction forces (such as; the horizontal and vertical forces, RCOF (H/V)) involved in human walking under normal and abnormal conditions. Perkins (1978), utilizing H/V ratio, indicated that forward slip at peak 3 and 4 was the most dangerous sequence of the step cycle due to the forward momentum of the body weight being progressively applied to the slipping foot. Strandberg and Lanshammar (1981) reproduced and measured slip distance previously identified by Perkins (1978), then classified slip distance into mini-slip, midi-slip, and maxi-slip. They concluded that if slip distance is greater than 10 cm., a fall might result. Leamon and Son (1989), and Leamon and Li (1990) reclassified slip distance into microslips (0-3 cm.), slips (3-10 cm.), and slides (>10 cm.). These classifications have been used to find the severity of slips (i.e., slipperiness of floor). Myung and Smith (submitted) first attempted to show the capability of slip distance as a biomechanical parameter in differentiating floor slipperiness and results indicated that SD was a good parameter for representing floor slipperiness by an inverse relationship with static COF. The relative sliding velocity (heel velocity) between the shoe sole and the flooring surface immediately after heel contact has been one of the essential gait parameters for slips and falls investigation. In general, if the heel sliding velocity after heel contact did not decrease to a certain limit (0.5 m/s), loss of balance or even a fall will result.

The tribological approach deals with surface dissipative process in terms of hydrodynamics of contaminants between the shoe and the floor and viscoelastic

characteristics of the shoe heel and sole materials. The tribological approach to fall accident prevention has concentrated on the static and dynamic coefficient of friction between shoe and floor surface. To protect people from slipping and falling, various groups have proposed to set minimum COF values for floor under standardized test conditions. However, due to the many variability in determining the COF, the method for determining the safe COF value for a particular shoe or floor materials has not been standardized to present day. There have been a great deal of apparatuses developed by many investigators to measure slipperiness of floor (COF); however, none of these device are universally accepted.

Psychophysics is the relationship between the perception of a sensation and the physical stimulus which produce the sensation. In using the psychophysical methodology for slips and falls, researchers have been asking research participants to subjectively assess the slipperiness of floor to obtain further insight into the parameters of vision and tactile sensation. In general, subjective judgments of slip-resistance correlation was negligible for static COF measurement and very high for dynamic COF. In addition, tactile cues were most sensitive to physical measurement of dynamic COF.

Any age-related deterioration in visual, proprioceptive, and vestibular signals concerning balance may produce a central signal detection problem, and to detect a peripheral stimulus correctly, a longer sampling period might be necessary and therefore, may increase the likelihood of fall accidents.

CHAPTER 3

METHOD

3.1 Subjects

Fourteen 18-29 year olds, fourteen 35-59-year-olds, and fourteen elderly individuals (65 years old and over) (total of forty two subjects: 7 male and 7 female for each age group) were recruited from Texas Tech University and the general population in Lubbock, Texas. Subject height and weight information are presented in Table 3.1. Subjects were recruited by word of mouth and a newspaper advertisement from the Department of Industrial Engineering (student subjects), local manufacturing companies, and the general population in Lubbock, Texas. Subjects were excluded from the study if they indicated any physical problems which might be complicated by their participation in the study. A questionnaire was used as an initial screening tool (Appendix A). Subjects also received a peripheral neuropathy examination from the Neurology Department at St. Mary's Hospital. Subjects were excluded from the study based on this test only if extreme disability (below 50% of the norm) was identified in the tests.

3.2 Apparatus

For this study, simulated floors, a contaminant (motor oil), a motion analysis system (Aerial Dynamic Inc.), a fall arresting rig, two Bertec force plates interfaced with LabView software, a remote controlled floor exchanger and a Horizontal Dynamometer were used. In addition, a NeuroTest (Neurocom, Inc.) was used to evaluate sensory organization and a force transducer was used to measure isometric muscle strength.

3.2.1 Simulated Floors

Two different floor materials were used for the experiment; vinyl tiles and the outdoor carpet. The dimensions of the simulated floors followed the shape of force plates (48"x 14"). The outdoor carpet served as a base line floor and covered the entire walking surface. To reduce the visual effect of floor materials, the color and contrast for all floor materials were similar.

Table 3.1. Subject information.

	Young (18-29 yrs.) Mean (S.D.)	Middle (35-59 yrs.) Mean (S.D.)	Old (65 yrs. and over) Mean (S.D.)
Age (yr)	22.6 (2.1)	46.9 (13.6)	75.6 (6.7)
Ht (cm)	169.7 (6.1)	173.5 (6.3)	170.2 (6.4)
Wt (kg)	68.7 (9.6)	75.5 (16.1)	76.8 (13.3)

3.2.2 Contaminants

Motor oil (10W40) was applied to the vinyl tile floor surface to reduce the coefficient of friction.

3.2.3 Motion Analysis System

An Ariel Performance Analysis System (APAS) was used to collect the three-dimensional coordinates of the subject's anatomical landmarks. The system features rapid data acquisition with data analyses and high resolution graphics, and provides a data collection rate of 60 frames per second (fps). The software modules in the APAS allowed the image data collected by the cameras to be tracked, digitized, and smoothed. Four Panasonic video recorders were used.

3.2.4 Bertec Force Plate and LabView Interface

The ground reaction forces of the subjects were collected by two Bertec force plates connected to an analog-to-digital converter (National Instruments, SCXI 1000) interfaced with LabView data collection software. In order to synchronize data collection of kinetic and kinematic profiles, an LED was used. The Bertec force plate was activated by a photo-electric switch and cameras were activated by remote controlled units.

3.2.5 Fall Arresting Rig

A fall arresting rig was used to protect the subjects from falling during the experiment. The rig consisted of a full-body harness and a rotational suspension system. The newly modified design of the fall arresting rig allowed subjects to control their own walking velocity via a potentiometer interfaced with LabView software. The overall function of the system allowed a subject, wearing a full-body harness, to walk under experiment conditions with minimal restrictions and provide self paced control of the fall arresting rig. Whenever an imbalance was detected, the system immediately arrested the fall and discontinued its motion (see Figure 3.9 p.140).

3.2.6 Slip Resistance Tester

A towed-sled (Big Toe) slip resistance tester with rubber test sensor material was used to measure the dynamic coefficient of friction of the simulated floor surfaces (vinyl–0.08, and carpet–1.80) above the force platform. The dimensions of the Big Toe was 3 x 2 inches and weighs 10 lb.

3.2.7 NeuroTest System (NeuroCom Inc.)

The NeuroTest System (NeuroCom Inc.) (St. Mary's Hospital, Neurology Research Center) is composed of two force plates and a computer system. The dual force plates are set into a platform base. Subjects stood on the dual force plates and faced a computer monitor. Force sensors under the dual force plates measured the vertical and horizontal forces exerted by the subject's feet. The computer received force measurements from the dual force plates, analyzed the information, and generated displacement data of the force platforms (COG) in a screen display and printed report.

3.2.8 Force Transducer (Chatillon DFGS-R-500)

Isometric strength measurements for the arms, legs, and torso were measured using an electronic strain gauge (Chatillon) which was incorporated into the tether. Force profiles were collected using an analogue-to-digital converter and a microcomputer.

3.2.9 Remote Controlled Floor Changer (RCFC)

A remote controlled floor changer (RCFC) was used to change test floor surfaces so as to provide unexpected slippery conditions. The RCFC unit was composed of a DC motor (LEESON Electric Corp.) and a gliding shaft (ACME Thread) attached to a platform. The DC motor was controlled by a remote control unit. Once triggered, the DC motor turned the ACME thread (max. 1750 rpm) thereby, moving the platform to a desired floor level (Figure 3.1). The test surfaces (vinyl tiles and outdoor carpet) were mounted on the platform, which was connected to the force platforms. The overall function of the system allowed a subject to walk under experiment conditions without being aware of the floor surface change.

Figure 3.1. Layout of the RCFC including ACME thread, platform, frame, DC motor, test floor surfaces and a force platform.

3.2.10 Container

A container (46 cm x 30 cm x 30 cm, 3 kg) was used for the carrying task. The container had 15.2 cm handles (with strap) at both sides to make it easy to carry. The container reduced the visibility of the subjects by restricting their visual field immediately in front of their feet.

3.3 Experimental Variables

3.3.1 Independent Variables

1. Age Groups (3) (Between Subjects). For this study, there were three age groups. A1 (18-29 year olds), A2 (35-59 year olds), and A3 (65 years old and over).

2. Floor surfaces levels (2) (Within Subjects). For this study, a Horizontal Pull Dynamometer (American Slip Meter Model ASM 725) with rubber test sensor material was used to measure DCOF. The tests were conducted at constant velocity with a vertical force of 10 lbs. The two floors were vinyl tiles with contaminant (DCOF-0.08) and outdoor carpet (DCOF-1.80). Outdoor carpet was chosen to minimize the interaction effect of oily residue on soles of the shoe. For the oily vinyl floor condition, a high viscosity motor oil (SAE 40) was used as the contaminant.

3. Load levels (2) (Within Subjects). Two load levels were used in this experiment (load [3 kg] and no-load).

3.3.2 Dependent Variables

3.3.2.1 Gait parameters

The converted coordinate data from APAS were used to calculate slip distances, sliding heel velocity, heel acceleration, heel contact velocity, position and velocity of center-of-gravity, and step length. A computer algorithm written in (C++) was used to calculate the gait parameters. Definitions of the gait parameters were based on the observed slip behavior. Figure 3.2 illustrates a typical slip behavior starting from the heel contact point. Heel contact was defined as the time when the vertical ground reaction force (GRF) exceeded 10N (to synchronize kinetic and kinematic variables, an LED was

Figure 3.2. Composite view of the gait parameters.

coupled to the vertical force output of the force plates, when the force exceeded 10N, an LED was triggered).

Initially, as indicated by the horizontal heel position (Figure 3.2 c), the heel does not slip forward (horizontal heel velocity decreases (Figure 3.2 b) as the heel quickly decelerates (Figure 3.2 a) during this time period). This (no slip) is believed to be the result of the position of the whole body COG (closer to the other stance foot) (MacKinnon and Winter, 1993) during the heel contact phase of the gait cycle.

Shortly after heel contact (approx. 60 ms) (as the fore foot comes down and COG shifts towards the sliding heel), the heel begins to slip forward (Figure 3.2 c). Afterwards, sliding heel reaches peak sliding heel velocity (PSHV) (Figure 3.2 b). During this slipping period, the heel accelerates reaching the maximum (Figure 3.2 a) near the mid point of the sliding heel velocity profile (Figure 3.2 b).

After reaching maximum heel velocity, the sliding heel velocity decreases to minimum, halting further slipping (not complete on the Figure 3.2).

Strandberg and Lanshammar (1981) identified slips by examining the coordinates of the heels. They defined the skid start as the first minimum in heel forward velocity, however, they did not mention how to determine the slip stop point. Perkins (1978) also did not specify how to determine the slip stop and slip start, instead presented multi-image photograph of heel slip using a stroboscope. Son (1990), utilizing 3-d coordinates of the reflectors on the subjects, identified slip start as the point at which a change in the horizontal displacement continued at a constant position in the vertical axis (the first minimum of the vertical heel velocity after the heel contact the floor surface), and the slip stop as the point at which change in vertical axis occurred, without a change in horizontal axis (the first minimum of the horizontal heel velocity after slip start point). While Son's definition is much clearer than the others, an alteration of the vertical force profile in most of the data beyond the point of maximum horizontal heel velocity was observed. Slip and fall experiments usually require a fall arresting rig to prevent injuries. However, a fall arresting harness may also affect the outcome of the slips beyond a certain point. Figure 3.2, illustrates this concept. Point (P1) of the vertical force profile illustrates that there is a big decrease in vertical force (Figure 3.2 d) as the subject slips (after reaching

peak heel sliding velocity). This decrease in vertical force may have resulted when the subject tried to compensate for a slip by utilizing the fall arresting harness, and in the process also, may have affected the horizontal force profile (point (P2) on Figure 3.2 e). Thus, beyond the peak heel velocity point, the fall arresting harness may affect the biomechanical parameters of slip severity (such as slip distance, slipping velocity etc). Utilizing the above concept, the slip start point was defined as the time where the first minimum of the vertical heel velocity after the heel contact occurred (a non-rearward positive acceleration-due to the slight rearward displacement occurring after heel contact), and the end of slip (for the purpose of calculation) as the time where the first maximum of the horizontal heel velocity after slip start point occurred (point before deceleration (PSHV), Figure 3.2).

To investigate the initiation phase of the unexpected slips and falls, initial gait characteristics (such as the stride length, heel velocity, and velocity of COG) and whole body strength (including the strength of lower extremities) of older individuals and their younger counterparts were compared. In addition, the relationship between the initial gait characteristic (such as heel velocity) and RCOF was further explored.

To investigate the detection and recovery phase of the unexpected slip and fall accidents, sensory organization scores, strength of lower extremity muscles and slip performance measures (such as, slip distances, sliding heel velocity, and heel acceleration) of older individuals and their younger counterparts were compared.

1. Slip distance. The horizontal distance traveled by the foot after the heel contacted the floor was measured. The overall slip distance was the distance between slip-start (X1,Y1) and PSHV (X2, Y2) points. The X and Y components represents the horizontal and lateral directions. The resultant slip distance was calculated with the biomechanical data from the APAS utilizing the formula (in addition, SD1 [slip-start to peak heel acceleration] and SD2 [peak heel acceleration to PSHV] was calculated and analyzed):

$$SD = \sqrt{(X_2 - X_1)^2 + (Y_2 - Y_1)^2}$$

2. Sliding heel velocity. The relative sliding heel velocity (SHV) of the heel after

heel contact was calculated by averaging the velocity of the heel during the slip start and PSHV points.

3. Heel acceleration. The relative heel acceleration (Hacc) of the heel after heel contact was calculated by averaging the acceleration of the heel from the slip start to the PSHV points.

4. Step length. The linear distance in the direction of progression between successive points of foot-to-floor contact of the same foot was measured. The step length was calculated from the difference between consecutive positions of the heel contacting the floor (resultant).

5. Heel velocity. The horizontal (x) velocity of the heel before the heel contact on the floor were measured. To find V_x , the difference of the foot displacements of last 1/60 second before and after the heel contact was divided by the elapsed time ($2\Delta t$) using the following formula.

$$V_x = [X(i+1) - X(i-1)]/2\Delta t$$

6. Position and velocity of the center-of-gravity of whole body. A sagittal 3-D link (14) segment model was used to calculate position and velocity of the COG. The frontal and sagittal models utilize the 14 component link-segment system defined by the reflective markers (Figure 3.3 and 3.4) and the anthropometric model (Winter, 1990; Zatsiorsky and Seluyanov, 1983, 1985) to compute the location of the center-of-gravity of the whole body (COG) in the transversal plane (Figure 3.5 and 3.6). Several assumptions were required to compute estimates of the COG. The assumptions included: (a) the human body can be represented by a set of 14 rigid bodies; (b) the center of mass of each segment is represented by a single point and its location remains fixed relative to the segment; (c) the anthropometric information used for the segment weights are representative of the body weights of interest; (d) the limbs move about fixed points when the body changes position; (e) the limbs are connected by massless hinge joints. The basic theory is briefly introduced below:

Definition of Center-of-gravity: The centroid of an assemblage of n similar quantities, $\Delta_1, \Delta_2, \dots, \Delta_n$, situated at points $P_1, P_2, \dots, P_n$, and having the position vectors $r_1, r_2, \dots, r_n$, has a position vector r :

$$\mathbf{r} = \frac{\sum_{i=1}^n r_i \Delta_i}{\sum_{i=1}^n \Delta_i}$$

the center of mass of an object is the location of the centroid of all mass elements, dm :

$$r_{COM} = \frac{\int r dm}{\int dm}$$

thus, the center-of-gravity of an object is the location of the centroid of all gravitational forces, G , of its mass elements, dG :

$$r_{COG} = \frac{\int r dG}{\int dG}$$

utilizing the above definition, a whole body center-of-gravity was calculated by summing the moment of the whole body about the same axis assuming uniform density:

$$M X = \sum_{i=1}^{14} m_i x_i$$

where $m_1, m_2, \dots, m_{14}$ are the weights of the 14 segments; M is the weight of the body; and $x_1, x_2, \dots, x_{14}$ are the respective distances of the center-of-gravity of the segments and whole body from the reference point (Table 3.2). Therefore,

$$X = \frac{1}{M} \sum_{i=1}^{14} m_i x_i$$

A similar computation of the moments about a second (Y) and third axis (Z) was performed to locate the 3-D whole body center-of-gravity.

Twenty-six reflective markers were used to define a whole body model. The locations of the external and extrapolated internal landmarks are shown in Figures 3.3 and 3.4. Internal landmarks were estimated at the mid-metatarsalphalangeal (MTP), subtalar, hip (in frontal plane), C7/T1 joints, mid-femoral condyles and mid-head (on

Figure 3.3. Marker placements and internal landmarks used to generate the frontal model.

Figure 3.4. Marker placements and internal landmarks used to generate sagittal model.

Table 3.2. Definition of the 14-segments and the location of COM of the segments employed in the sagittal model.

Segment Weight/			
Segment	Definition	Total Body Weight	COM Location
Foot (m1, m14)	Lateral malleolus/ head metatarsal II	0.0145	Midpoint between lateral malleolus and head of metatarsal II
Leg (m2, m13)	Femoral condyles/ Medial malleolus	0.0465	43.3 % below femoral condyle markers
Thigh (m3, m12)	Greater trochanter/ Femoral condyles	0.1000	43.3 % below greater trochanter markers
Trunk (m4)	Greater trochanter/ Glenohumeral joint	0.497	Midpoint between greater trochanter and glenohumeral joint
Upper arm (m5, m9)	Glenohumeral axis/ elbow axis	0.028	43.6 % below glenohumeral axis
Forearm (m6, m10)	Elbow axis/ ulnar styloid	0.016	43.0% below elbow axis
Hand (m7, m11)	Wrist axis /knuckle II middle finger	0.006	49.4 % above knuckle II middle finger
Head and Neck (m8)	C7/T1 and 1 st rib/ear canal	0.081	At the 1 st rib/ear canal

Figures 3.3 and 3.4, white balls represent internal landmarks). Internal landmarks at the knees, C7/T1 and head were calculated as the midpoint between markers as shown in Figures 3.3 and 3.4. The mediolateral location of the mid-metatarsalphalangeal joint center was determined as the point intersection of a line between the toe marker and subtalar joint center and the perpendicular line to a marker placed on the lateral border of the head of the fifth metatarsal. The subtalar joint center was estimated by extrapolating down 1.9cm (Isman and Inman, 1969) and perpendicular to the midpoint of the line between markers placed on the lateral and medial malleoli. The mediolateral location of the hip joint center was determined by extrapolating medially 19.7% (Brinckmann et al., 1981) of the distance between the right and left greater trochanter (hip) markers. The vertical and anterior/posterior location of the hip was determined using the coordinates of the greater trochanter (hip) marker. The internal and external landmarks allowed definition of a 14-segment whole body model which includes; foot, lower leg, thigh, abdomen and thorax, head and neck, upper arm, forearm, and hand segments (Tables 3.3 and 3.4). Utilizing frontal and sagittal models, averaged vertical and horizontal velocities of the five frames before and after the heel contact phase of the gait cycle was computed. The pilot test of this model is presented in the Appendix D.

3.3.2.2 Ground reaction forces

3.3.2.2.1. Horizontal and vertical ground reaction forces. The ground reaction forces were measured by two Bertec force plates during the heel contact phase of the gait cycle.

3.3.2.2.2. Required COF. The ratio between the horizontal and vertical ground reaction forces (during the initial heel contact phase of the gait [peak 3 as defined by Perkins,(1978)]) was calculated on a carpeted surface via a LabView software system.

3.3.2.2.3. Adjusted Required Coefficient of Friction (ARCOF). ARCOF is the measured ratio of the horizontal foot force to the vertical foot force at the slip-stop point and represents the ability to adjust dynamic frictional requirements during slipping. The significance of this ratio is that it indicates where in the gait profile compensation for a slip is most likely to occur. Figure 3.1 illustrates this concept. As the horizontal heel

Table 3.3. Definition of the 14-segments and the location of COM of the segments employed in the frontal model.

Segment Weight/			
Segment	Definition	Total Body Weight	COM Location
Foot (m1, m14)	Extrapolating down 1.9cm and perpendicular to the midpoint of the line between markers placed on the lateral and medial malleoli (SUBTALAR)/ Perpendicular line to a marker placed on the lateral border of the head of the fifth metatarsal (MTP) and intersection of the head of metatarsal II	0.0145	Midpoint between SUBTALAR and the intersection of the line perpendicular to the MTP and head of metatarsal II
Leg (m2, m13)	Mid point between medial and lateral femoral condyles/ Subtalar	0.0465	43.3 % below femoral condyle markers
Thigh (m3, m12)	Extrapolating medially 19.7% of the distance between the right and left Greater trochanter (HIP)/ Mid point between medial and lateral femoral condyles	0.1000	43.3 % below hip markers
Trunk (m4)	Mid point between the right and left hip markers/ Mid point between the right and left shoulder markers	0.497	Midpoint between the line intersecting hip and shoulder
Upper arm (m5, m9)	Glenohumeral axis/ elbow axis	0.028	43.6 % below glenohumeral axis
Forearm (m6, m10)	Elbow axis/ ulnar styloid	0.016	43.0% below elbow axis
Hand (m7, m11)	Wrist axis /knuckle II middle finger	0.006	49.4 % above knuckle II middle finger
Head and Neck (m8)	Mid point between the right and left acromion of scapula (C7/T1)/ Mid point between the right and left 1 st rib/ear markers	0.081	At the 1 st rib/ear canal

Figure 3.5. Marker placements in transversal plane (top).

Figure 3.6. Marker placements in transversal plane (under).

velocity reaches maximum, horizontal force is decreased (slight decrease in vertical force as well), thus, the ratio of horizontal to vertical force profile decreases. At this point, if ARCOF is higher than the available dynamic coefficient of friction (ADCOF), the heel will continue to increase in velocity; however, on this data, ARCOF is lower than the ADCOF, and the horizontal heel velocity decreases (beginning of halting a slip). ARCOF values were measured on vinyl tile floor surface during PSHV.

3.3.3 Sensory Organization Test and Motor Control Test Scores

The Sensory Organization Test (SOT) scores were based on the assumption that a normal individual can exhibit anterior to posterior sway over a total range of 12.5 degrees (6.25 anterior, 6.25 posterior) without losing balance. Equilibrium scores (proprioceptive, vestibular, and vision) were based on the Sensory Organization Test and reflected how much the subject swayed during each trial of the 4 sensory conditions (condition 1 = eyes open, stable platform; condition 2 = eyes closed, stable platform; condition 3 = eyes open, sway-referenced platform [e.g. platforms move with movement of the subjects COG]; condition 4 = eyes closed, sway-referenced platform). The equilibrium scores (proprioceptive, vestibular, and vision) were calculated by comparing the angular difference between the subject's calculated maximum anterior to posterior center-of-gravity displacements to this theoretical maximum displacement. The results were expressed as a percentage between 0 and 100, with 0 indicating sway exceeding the limits of stability and 100 indicating perfect stability. Conditions 1 and 2 were used to test a subject's ability to use input from the proprioceptive system to maintain balance. Conditions 1 and 4 were used to test a subject's ability to use input from the visual system to maintain balance. And, conditions 1 and 4 were used to test a subject's ability to use input from the vestibular system to maintain balance.

The muscle latency (Motor Control Test [MCT]) time was defined as the time in milliseconds between the onset of a translation and the onset of the subject's active response to the support surface movement. The muscle latency time was based on the Motor Control Test protocols utilizing six conditions (condition 1 = small forward translation of the force plates; condition 2 = medium forward; condition 3 = large forward; condition 4 = small backwards; condition 5 = medium backwards; condition 6

= large backwards). The composite muscle latency time was determined as the average of the latency scores following medium and large translations.

3.3.4 Maximal Isometric Strength

Whole-body isometric strength measurements for the arms, legs, and torso were collected as described by Chaffin et al (1978) and Chaffin and Andersson (1991). An electronic strain gauge (Chatillon) was incorporated into the chain, and force profiles were collected using an analog-to-digital converter and microcomputer (Figure 3.7).

3.4 Procedure

3.4.1 Familiarization Session

The subjects attended a familiarization program before the scheduling of the experiment (data collection). This program familiarized the subjects with the fall arresting rig system and the walking conditions (natural cadence). The subjects tested the fall arresting rig to assure themselves that the system (fall arresting rig) would arrest potential falls. Anthropometric data (body weight and height) and isometric strength of the subjects were measured at this time. Afterwards, SOT and MCT were performed using NeuroCom NeuroTest system at St. Mary's Hospital.

3.4.1.1 Maximal Isometric Strength Test

Isometric strength measurements for the arms, legs, and torso were collected as described by Chaffin et al. (1978) and Chaffin and Andersson (1991) (modified). For the test of arm lifting strength, subjects stood erect and grabbed a handle 46 cm long vertically positioned at their standing elbow height (90°). For the test of leg lift strength, the handle was 15 cm long. Subjects assumed a 'squat' posture with their knees bent (90°) and back straight. For the torso lift, subjects assumed a bent torso posture (90°) with the legs straight while holding a 48 cm handle.

For all strength trials, subjects were instructed to build slowly to their maximum level in a 2 s time interval, and then to maintain this level for an additional 2 s time period. The isometric strength tests were self limiting. Subjects were instructed to exert

Figure 3.7. Static strength test postures and results for 443 male and 108 female workers employed in four different industries (Chaffin, Herrin, and Keyserling, 1978).

their “safe voluntary maximum strength.” Testing was in an area isolated from other subjects to avoid any competition between subjects. Subjects were not provided with their strength scores (an another means of reducing over-exertion through competition). The maximum isometric strength for these trials was defined as the maximum force produced from the second to the fourth second of this 4 s exertion. To collect these measurements, subjects stood on a 1 m by 1 m aluminum platform and grasped a handle connected to the platform with a chain. An electronic strain gauge (Chatillon) was incorporated into the chain, and force profiles were collected using an analog-to-digital converter and microcomputer. A more detailed description of the procedures and apparatus used for these tests can be found in Chaffin et al. (1978).

3.4.1.2 Sensory Organization Test and Motor Control Test

The purpose of these tests was to assess balance by using the NeuroCom NeuroTest System. NeuroTest was designed to quantify aspects of the sensory and motor examination pertinent to neurological examinations. In this study, the NeuroTest System was utilized to analyze the subject’s balance at a normal standing position. This procedure indicated how good overall balance might be relative to norms and provided more specific information about the contributions of vision, muscle feedback (proprioceptive system), and inner ear (vestibular system) to balance for each individual. The subjects were asked to stand on the NeuroCom dual forceplates (balance platforms) with feet in the required position on the platform (Figure 3.8). For safety and confidence, subjects were asked to wear a safety harness. During the test, subjects were asked to close and open their eyes while the force plates moved forward and backward (translation), and also, up and down (rotation). Individual measurements lasted 20 seconds, and the total testing period lasted 20 minutes. For the Sensory Organization Test, there were total of three trials per each of four conditions (condition 1 = eyes open, stable platform; condition 2 = eyes closed, stable platform; condition 3 = eyes open, sway-referenced platform (e.g., platforms move with movement of the subjects COG); condition 4 = eyes closed, sway-referenced platform). In addition, for the Motor Control Test (muscle latency) there were two trials per each of six conditions (condition 1 = small forward translation of the force plates; condition 2 = medium forward; condition 3 =

Figure 3.8. Layout of the NeuroCom, including the force plates, computer monitor and safety harness.

large forward; condition 4 = small backwards; condition 5 = medium backwards; condition 6 = large backwards). This procedure was conducted at St. Mary's Hospital prior to the experimental session.

3.4.2 Protocol

Subjects were scheduled to participate in two testing sessions within one week's time. The first session served as an introductory (familiarization) and preliminary measurement session. During this time anthropometric measurements were taken (weight and height). In addition, isometric strength tests were conducted. Afterwards, the sensory organization test were performed at St. Mary's Hospital.

The biomechanical parameters of walking were collected during the second session of the experiment (utilizing motion analysis system). Prior to performing the walking experiments, subjects were fitted with standardized laboratory shoes in order to minimize possible variations due to footwear. In addition, retro-reflectors were attached to the anatomically significant body positions.

Before the walking trials began, subjects were fitted with the safety harness which was connected to the fall arresting rig. During the walking trials, subjects were asked to walk as naturally as possible as practiced during the familiarization session (natural cadence). During the experiment, the subjects walked across each floor condition for 10 min with, and 10 min without the load (total of 20 minutes). While walking, subjects were instructed to focus their eyes on a light emitting diode located approximately 2 meters above and 3 meters away from the testing area. A secondary task that required them to call out when the light was on and when it was off was used to ensure that they attended to the LED. During each of the 10 min sessions, 2 slippery conditions were randomly introduced by the system, and measurements of subject's posture and ground reaction forces were recorded. Location of the slippery surfaces were also randomly distributed by the two floor changers (e.g., two force plate locations). Subjects were also supplied with a walkman (listening to old comedy routines) during the walking experiment to conceal any sound of the floor changer's motors. Field layout of the experiment is illustrated in Figure 3.9.

Figure 3.9. Field layout of the experiment including; fall arresting rig, potentiometer interfaced with the LabView system, safety harness, force platforms, optoelectric switch, CCD cameras (4), AG 6300 VCR (4) and Remote Control Floor Changer (RCFC) Units with base line carpet floor material.

3.5 Data Analyses

3.5.1 ANOVAs

A 3 x 2 x 2 (age x floor x load) three-way repeated measures analysis of variance (ANOVA) was performed on each dependent variable with $\alpha \leq 0.5$. The p-values in the ANOVA were adjusted for violations of the assumptions regarding the variance-covariance matrix using the Huynh-Feldt method to estimate ε and adjusting the degrees-of-freedom accordingly. In addition, constant variance and normality assumptions were verified by residual analysis and normality plots. Post-hoc means separation test (Tukey-Kramer) were performed on all significant age effects. A computer algorithm was written in the C++ to objectively determine biomechanical parameters. Figure 3.10 illustrates summary of the data analyses.

The statistical model for this design was;

$$Y_{ijkl} - \mu = \beta_k + \pi_{i(k)} + \alpha_j + \alpha\beta_{jk} + \pi\alpha_{ji(k)} + \Gamma_l + \beta\Gamma_{kl} + \Gamma\pi_{li(k)} + \alpha\Gamma_{jl} + \alpha\beta\Gamma_{jkl} + \alpha\Gamma\pi_{jli(k)} + \mathcal{E}_{ijkl}$$

(i [subject] = 1 to 14; j [floor] = 1 to 2; k [age] = 1 to 3; and l [load] = 1 to 2)

where,

β_k = fixed effect of the age groups (factor B);

α_j = fixed effect of the floor levels (factor A);

π_i = effect of the person (random) in each group;

$\alpha\beta_{jk}$ = interaction effects of the age groups and floor levels;

$\pi\alpha_{ji(k)}$ = effect of a particular level of repeated measures factor A on the particular individual nested within the group.

Γ_l = fixed effect of the load levels (factor C);

$\beta\Gamma_{kl}$ = effect of the interaction between repeated measures factor C and the

group factor B (age group);

$\Gamma\pi_{li(k)}$ = effect of the particular level of repeated measures factor C on the particular individual;

$\alpha\Gamma_{jl}$ = effect of the interaction between the factor A and factor C (floor and load);

$\alpha\beta\Gamma_{jkl}$ = effect of interaction between the three factors;

$\alpha\Gamma\pi_{jli(k)}$ = effect of a particular combination of levels of the repeated measures factors (A and C) on the particular individual;

$\mathcal{E}_{ijk}$ = random effect of the ith person receiving the jth age group followed by the kth floor level.

The EMS for the two factor repeated measures design is listed below.

$$\begin{aligned}
 E(MS_A) &= n_j \sum \alpha^2 / (J-1) & + K\sigma_{\pi\alpha}^2 + \sigma_{\epsilon}^2 \\
 E(MS_{A \times S}) &= & K\sigma_{\pi\alpha}^2 + \sigma_{\epsilon}^2 \\
 E(MS_B) &= n_k \sum \beta^2 / (K-1) & + J\sigma_{\pi\beta}^2 + \sigma_{\epsilon}^2 \\
 E(MS_{B \times S}) &= & J\sigma_{\pi\beta}^2 + \sigma_{\epsilon}^2 \\
 E(MS_{A \times B}) &= n_{jk} \sum \sum \alpha\beta^2 / (J-1)(K-1) & + \sigma_{\pi\alpha\beta}^2 + \sigma_{\epsilon}^2 \\
 E(MS_{A \times B \times S}) &= & \sigma_{\pi\alpha\beta}^2 + \sigma_{\epsilon}^2 \\
 & & \text{(same for the load effect).}
 \end{aligned}$$

Therefore, F ratio of Age Groups is $E(MS_A) / E(MS_{A \times S})$, F ratio of Floor Surfaces Levels is $E(MS_B) / E(MS_{B \times S})$, F ratio of Load Levels is $E(MS_c) / E(MS_{A \times B})$ and $E(MS_{(sw) B \times S})$, and F ratio of the interaction is $E(MS_{A \times B}) / E(MS_{A \times B \times S})$.

3.5.2 Correlation Analysis

Bivariate correlation analyses were performed to describe the relationships between the independent (HV, COGVB, and COGVA) and dependent (RCOF) variables. To investigate the relationship between the initial gait characteristics and RCOF, bivariate correlation analyses were performed between the heel velocity (x) and RCOF (y), COGVB (x) and RCOF (y), and COGVA (x) and RCOF (y). To investigate the initial jarring effect during the heel contact phase of the gait, bivariate correlation analysis was performed between the vertical COGVA and lower extremity (leg) strength.

3.5.3 Regression Analysis

Regression analyses were performed to describe and predict the relationship between the independent (predictor variable (X)) and dependent (response variable (Y)) variables. The response variables (Y) were slip distance (slip severity), SD1, SHV, Hacc, and HV. The predictor variables (X) were age, gender, weight, height (stature), sensory organization test scores (vision, proprioceptive, and vestibular system response), maximal isometric strength and muscle latency (ML) response-time in milliseconds between the onset of a translation and the onset of the subject's active response to the support surface movement. These analyses were used to explain which variables (dependent) were most related to slip severity (e.g., slip distance). For prediction purposes, a statistical model developed by analyzing the relationship between response variable and predictor variables was utilized to predict slip performance given the predictor variables. These models predicted which subjects have greater difficulty adjusting to walking over unexpected slippery floor surfaces. The data were analyzed by utilizing techniques (scatter plot, residual vs. predicted, normal probability plot, hat matrix, Cook's D, and Variance Inflation Factor (VIF) -for the multicollinearity) available for evaluating the assumptions of regression analysis (the assumption of a probabilistic process, functional specification of mean response, constant variance, normality assumptions). The predictor variables were selected by utilizing the cp and the backward elimination procedure for the dependent variable – SD, SD1, HV, SHV, and Hacc.

The Process of Initiation, Detection, and Recovery of Inadvertent Slips and Falls

Figure 3.10. Summary of the data analyses.

CHAPTER 4

RESULTS AND DISCUSSION

4.1 Treatment of Data

The dependent measures, step length (SL), step length index (SLI), heel velocity (HV), velocity of center-of-gravity before heel contact (COGVB), and velocity of center-of-gravity after heel contact (COGVA [x and z]) were analyzed by 3 x 2 x 2 (age x floor x load) three-way repeated measures analyses of variance (ANOVA). The center-of-gravity velocity difference ($COGV_{diff}$) between before and after heel contact was analyzed by one-way (age) repeated measures analysis of variance on a carpeted floor surface. Required Coefficient of Friction (RCOF) was analyzed by 3 x 2 (age x load) two-way repeated measures analysis of variance (ANOVA) on the carpeted floor surface. Adjusted RCOF (ARCOF), slip distances (overall SD, SD1 and SD2), sliding heel velocity (SHV), heel acceleration (Hacc), and velocity of center-of-gravity ($COGV_{slip}$) during slipping were analyzed by 3 x 2 (age x load) two-way repeated measures analysis of variance (ANOVA) on the vinyl floor surface. Descriptive and inferential statistical analyses were performed on a Power Macintosh using the SuperANOVATM and SAS (regression) statistical packages.

4.2 ANOVA Results

The findings from these analyses are summarized under the following headings: age comparisons, floor levels comparison (where applicable), load levels comparison, and interactions.

4.2.1 Step Length (SL)

The summary of the three-way ANOVA is presented in Table 4.1.

4.2.1.1 Age Comparisons

The main effect (age group) was compared utilizing calculated SL for young, middle, and old age groups across floor and load levels. It was hypothesized that older

Table 4.1 Summary of a three-way ANOVA of 3 age groups, 2 floor levels, and 2 load levels on SL (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	2057.858	1028.929	4.735	.0144		
Subject(Group)	39	8474.100	217.285				
floor	1	79.574	79.574	8.537	.0058	.0058	.0058
floor * age	2	59.030	29.515	3.166	.0532	.0532	.0532
floor * Subject(Group)	39	363.532	9.321				
load	1	47.800	47.800	1.554	.2200	.2200	.2200
load * age	2	52.964	26.482	.861	.4307	.4307	.4307
load * Subject(Group)	39	1199.687	30.761				
floor * load	1	3.445	3.445	.321	.5742	.5742	.5742
floor * load * age	2	3.787	1.894	.176	.8389	.8389	.8389
floor * load * Subject(G...	39	418.476	10.730				

Dependent: sl

individual's SL would be shorter than their younger counterparts. The results of the three-way ANOVA indicated statistically significant ($p \leq 0.05$) SL differences between young (64.35 cm), middle (67.63 cm), and old (59.13 cm) subjects (Table 4.2 and Figure 4.1). Furthermore, Tukey-Kramer post-hoc test indicated that middle age group's SL was significantly different from younger and older subjects.

4.2.1.2 Floor Level Comparisons

The main effect (floor level) was compared using calculated SL for each floor level across both age groups and load levels. It was hypothesized that floor slipperiness (DCOF) would affect SL. The results indicated a statistically significant ($p \leq 0.05$) SL differences between carpeted floor (64.39 cm) and vinyl floor (63.01 cm) surfaces (Table 4.3 and Figure 4.2).

4.2.1.3 Load Level Comparisons

The main effect (load level) was compared using calculated SL for each load levels across both age groups and floor levels. It was hypothesized that load levels would affect SL of the subjects. The results indicated no statistically significant ($p > 0.05$) differences between the load (63.17 cm) and no-load (64.23 cm) conditions (Table 4.4).

4.2.1.4 Interactions

The results indicated statistically significant ($p \leq 0.05$) SL differences between (Age * Floor) interaction. Overall, younger subjects had higher SL than older subjects across floor levels (Table 4.5 and Figure 4.3).

In summary, the step length was significantly different ($p \leq 0.05$) across age groups and floor levels. In general, younger subjects had longer step length than older individuals and the middle-aged group had the longest step length. Previous studies (Imms and Edholm (1979), Bassey et al. (1976), and Winter (1991)) also found reductions in step length for the older individuals. The overall step length was only slightly (less than 1 cm) longer for the carpeted floor surface than the vinyl (slippery) floor surface (compared to previous experiment [> 10 cm, (Lockhart, 1997)]), indicating that subjects were not aware of the floor change to slippery floor surface.

Table 4.2 Descriptive summary of SL on main effect Age Group.

	Count	Mean	Std. Dev.	Std. Error
young	56	64.345	7.344	.981
middle	56	67.625	9.048	1.209
old	56	59.126	7.668	1.025

Figure 4.1 Age effect on step length with 95% confidence error bars.

Table 4.3 Descriptive summary of SL on main effect Floor Levels.

	Count	Mean	Std. Dev.	Std. Error
carpet	84	64.387	8.394	.916
vinyl	84	63.010	9.073	.990

Figure 4.2 Floor effect on step length with 95% confidence error bars.

Table 4.4 Descriptive summary of SL on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	84	63.165	8.426	.919
no-load	84	64.232	9.065	.989

Table 4.5 Descriptive summary of SL on interaction effect Age x Floor.

	Count	Mean	Std. Dev.	Std. Error
carpet, young	28	65.769	6.534	1.235
carpet, middle	28	67.599	9.144	1.728
carpet, old	28	59.792	7.465	1.411
vinyl, young	28	62.920	7.935	1.500
vinyl, middle	28	67.652	9.118	1.723
vinyl, old	28	58.459	7.945	1.501

Figure 4.3 Interaction effect (Age x Floor) on step length with 95% confidence error bars.

4.2.2 Step Length Index (SLI)

The summary of the three-way ANOVA for SLI is presented in Table 4.6.

4.2.2.1 Age Comparisons

The main effect (age group) was compared utilizing calculated step length index (SLI) for young, middle and old across floor and load levels. It was hypothesized that SLI would be longer for the younger individuals than the older individuals (same as the SL). Consistent with previous findings, the results of the three-way ANOVA indicated statistically significant ($p \leq 0.05$) SL differences between young (.381), middle (.393), and old (.347) subjects (Table 4.7 and Figure 4.4). Tukey-Kramer post-hoc test indicated that middle age group's SLI was significantly different from younger and older subjects.

4.2.2.2 Floor Levels Comparisons

The main effect (floor level) was compared using calculated SLI for each floor levels across both age groups and cadence levels. It was hypothesized that floor slipperiness (DCOF) would affect SLI. The results indicated statistically significant ($p \leq 0.05$) SLI differences between carpeted floor (.378) and vinyl floor (.370) surfaces (Table 4.8 and Figure 4.5).

4.2.2.3 Load Levels Comparisons

The main effect (load level) was compared using calculated SLI for each load levels across both age groups and floor levels. It was hypothesized that load levels would affect SLI of the subjects. The results indicated no statistically significant ($p > 0.05$) SLI differences between load (.371) and no-load (.377) conditions.

4.2.2.4 Interactions

The results indicated no statistically significant ($p > 0.05$) SLI differences between interaction terms.

In summary, similar to step length, the step length index was significantly different ($p \leq 0.05$) across age groups and floor levels. However, Floor x Age interaction was not significantly different ($p > 0.05$) as it was with step length.

Table 4.6 Summary of a three-way ANOVA of 3 age groups, 2 floor levels, and 2 load levels on SLI (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	.066	.033	6.676	.0032		
Subject(Group)	39	.191	.005				
floor	1	.003	.003	9.058	.0046	.0046	.0046
floor * age	2	.002	.001	2.975	.0627	.0627	.0627
floor * Subject(Group)	39	.013	3.305E-4				
load	1	.002	.002	1.717	.1977	.1977	.1977
load * age	2	.002	.001	.932	.4024	.4024	.4024
load * Subject(Group)	39	.042	.001				
floor * load	1	1.343E-4	1.343E-4	.367	.5483	.5483	.5483
floor * load * age	2	1.143E-4	5.717E-5	.156	.8560	.8560	.8560
floor * load * Subject(G...	39	.014	3.662E-4				

Dependent: sl (index)

Table 4.7 Descriptive summary of SLI on main effect Age Group.

	Count	Mean	Std. Dev.	Std. Error
young	56	.381	.040	.005
middle	56	.393	.044	.006
old	56	.347	.036	.005

Figure 4.4 Age effect on step length index with 95% confidence error bars.

Table 4.8 Descriptive summary of SLI on main effect Floor Levels.

	Count	Mean	Std. Dev.	Std. Error
carpet	84	.378	.044	.005
vinyl	84	.370	.046	.005

Figure 4.5 Floor levels effect on step length index with 95% confidence error bars.

4.2.3 Heel Velocity (Horizontal)

The summary of the three-way ANOVA for horizontal heel velocity is presented in Table 4.9.

4.2.3.1 Age Comparisons

The main effect (age group) was compared utilizing calculated horizontal HV for young, middle, and old across floor and load levels. It was hypothesized that horizontal HV would be higher for the older individuals. The results of the three-way ANOVA indicated no statistically significant ($p > 0.05$) horizontal HV differences between young (31.03 cm/sec), middle (32.12 cm/sec), and old (42.37 cm/sec) subjects (Table 4.10).

4.2.3.2 Floor Levels Comparisons

The main effect (floor level) was compared using calculated horizontal HV for each floor level across both age groups and load levels. It was hypothesized that floor levels would affect horizontal HV of the subjects. The results indicated statistically significant ($p \leq 0.05$) horizontal HV differences between the carpeted (39.61 cm/sec) and vinyl (30.731 cm/sec) floor surfaces (Table 4.11 and Figure 4.6).

4.2.3.3 Load Levels Comparisons

The main effect (load level) was compared using calculated horizontal HV for each load level across both age groups and floor levels. It was hypothesized that load levels would affect horizontal HV of the subjects. The results indicated no statistically significant ($p > 0.05$) differences in horizontal HV between load (37.67 cm/sec) and no-load (32.67 cm/sec) conditions (Table 4.12).

4.2.3.4 Interactions

The results indicated no statistically significant ($p > 0.05$) horizontal HV differences between interaction terms.

In summary, the heel velocity on floor levels differed significantly ($p \leq 0.05$). On the average, older subject's horizontal HV was faster than younger individuals, and horizontal HV was faster for the load condition than the no-load condition.

Table 4.9 Summary of a three-way ANOVA of 3 age groups, 2 floor levels, and 2 load levels on horizontal HV(including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	4383.526	2191.763	2.885	.0678		
Subject(Group)	39	29626.728	759.660				
floor	1	3312.489	3312.489	11.699	.0015	.0015	.0015
floor * age	2	478.844	239.422	.846	.4370	.4370	.4370
floor * Subject(Group)	39	11042.182	283.133				
load	1	1047.911	1047.911	3.711	.0614	.0614	.0614
load * age	2	1130.681	565.340	2.002	.1487	.1487	.1487
load * Subject(Group)	39	11013.538	282.398				
floor * load	1	849.996	849.996	2.193	.1467	.1467	.1467
floor * load * age	2	1326.883	663.442	1.712	.1939	.1939	.1939
floor * load * Subject(G..	39	15116.894	387.613				

Dependent: heel vel (1)

Table 4.10 Descriptive summary of HV on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	56	31.034	21.564	2.882
middle	56	32.112	13.528	1.808
old	56	42.369	26.732	3.572

Table 4.11 Descriptive summary of HV on main effect floor levels.

	Count	Mean	Std. Dev.	Std. Error
carpet	84	39.612	20.032	2.186
vinyl	84	30.731	22.684	2.475

Figure 4.6 Floor Levels effect on HV with 95% confidence error bars.

Table 4.12 Descriptive summary of HV on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	84	37.669	21.634	2.361
no-load	84	32.674	21.797	2.378

4.2.4 Horizontal Center-of-Gravity Velocity Before Heel Contact

The summary of the three-way ANOVA is presented in Table 4.13.

4.2.4.1 Age Comparisons

The main effect (age group) was compared utilizing estimated COGVB for young, middle, and old age group across floor and load levels. It was hypothesized that COGVB would be slower for the older individuals (due to slower walking speed) than their younger counterparts. The results of the three-way ANOVA indicated statistically significant ($p \leq 0.05$) COGVB differences between young (109.99 cm/sec), middle (115.53 cm/sec), and old (99.87 cm/sec) subjects (Table 4.14 and Figure 4.7). Furthermore, Tukey-Kramer post-hoc test indicated that middle age group's COGVB was significantly different than their younger and older counterparts.

4.2.4.2 Floor Levels Comparisons

The main effect (floor level) was compared using estimated COGVB for each floor level across both age groups and load levels. It was hypothesized that floor levels would affect COGVB of the subjects. The results indicated statistically significant ($p \leq 0.05$) COGVB differences between the carpeted (110.02 cm/sec) and vinyl (105.91 cm/sec) floor surfaces (Table 4.15 and Figure 4.8).

4.2.4.3 Load Levels Comparisons

The main effect (load level) was compared using estimated COGVB for each load level across both age groups and floor levels. It was hypothesized that load levels would affect COGVB of the subjects. The results indicated no statistically significant ($p > 0.05$) COGVB differences between the load (110.16 cm/sec) and no-load (106.77 cm/sec) conditions (Table 4.16).

4.2.4.4 Interactions

The results indicated no statistically significant ($p > 0.05$) COGVB differences between interactions terms.

In summary, the COGVB was significantly different across age groups. In general, younger subjects COGVB was faster than the older individuals and middle-aged group's COGVB was the fastest. On the average, COGVB was faster for the carpeted

Table 4.13 Summary of a three-way ANOVA of 3 age groups, 2 floor levels, and 2 load levels on COGVB(including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	7065.635	3532.817	4.329	.0201		
Subject(Group)	39	31827.782	816.097				
floor	1	404.462	404.462	6.152	.0176	.0176	.0176
floor * age	2	197.337	98.668	1.501	.2356	.2356	.2356
floor * Subject(Group)	39	2564.194	65.749				
load	1	481.044	481.044	3.251	.0791	.0791	.0791
load * age	2	140.995	70.497	.476	.6245	.6245	.6245
load * Subject(Group)	39	5770.392	147.959				
floor * load	1	.171	.171	.002	.9632	.9632	.9632
floor * load * age	2	177.797	88.898	1.123	.3356	.3356	.3356
floor * load * Subject(G..)	39	3087.431	79.165				

Dependent: cogv(B)

Table 4.14 Descriptive summary of COGVB on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	56	109.995	14.426	1.928
middle	56	115.533	18.195	2.431
old	56	99.870	16.513	2.207

Figure 4.7 Age Groups effect on COGVB with 95% confidence error bars.

Table 4.15 Descriptive summary of COGVB on main effect Floor Levels.

	Count	Mean	Std. Dev.	Std. Error
carpet	84	110.017	16.597	1.811
vinyl	84	106.914	18.514	2.020

Figure 4.8 Floor Levels effect on COGVB with 95% confidence error bars.

Table 4.16 Descriptive summary of COGVB on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	84	110.158	15.464	1.687
no-load	84	106.773	19.446	2.122

surface than the vinyl floor surface, and COGVB was faster for the load condition than the no-load conditions.

4.2.5 Horizontal Center-of-Gravity Velocity After Heel Contact

The summary of the three-way ANOVA is presented in Table 4.17.

4.2.5.1 Age Comparisons

The main effect (age group) was compared utilizing estimated COGVA for young, middle, and old age groups across floor and load levels. It was hypothesized that COGVA would be slower for the older individuals (due to the slower walking speed) than their younger counterparts. The results of the three-way ANOVA indicated statistically significant ($p \leq 0.05$) COGVA differences between young (115.99 cm/sec), middle (123.23 cm/sec), and old (107.37 cm/sec) subjects (Table 4.18 and Figure 4.9). Tukey-Kramer post-hoc test indicated that middle age group's COGVA was significantly different than their younger and older counterparts.

4.2.5.2 Floor Levels Comparisons

The main effect (floor level) was compared using estimated COGVA for each floor level across both age groups and load levels. It was hypothesized that floor levels would affect COGVA of the subjects. The results indicated statistically significant ($p \leq 0.05$) COGVA differences between the carpeted (118.38 cm/sec) and vinyl (112.67 cm/sec) floor surfaces (Table 4.19 and Figure 4.10).

4.2.5.3 Load Levels Comparisons

The main effect (load level) was compared using estimated COGVA for each load level across both age groups and floor levels. It was hypothesized that load levels would affect COGVA of the subjects. The results indicated no statistically significant ($p > 0.05$) COGVA differences between the load (117.33 cm/sec) and no-load (113.72 cm/sec) conditions (Table 4.20).

4.2.5.4 Interactions

The results indicated no statistically significant ($p > 0.05$) COGVA differences between interactions terms.

Table 4.17 Summary of a three-way ANOVA of 3 age groups, 2 floor levels, and 2 load levels on COGVA(including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	7062.816	3531.408	3.632	.0358		
Subject(Group)	39	37923.188	972.389				
floor	1	1371.265	1371.265	10.713	.0022	.0022	.0022
floor * age	2	86.534	43.267	.338	.7152	.7152	.7152
floor * Subject(Group)	39	4991.898	127.997				
load	1	548.267	548.267	2.947	.0940	.0940	.0940
load * age	2	187.214	93.607	.503	.6085	.6085	.6085
load * Subject(Group)	39	7254.845	186.022				
floor * load	1	111.309	111.309	1.630	.2093	.2093	.2093
floor * load * age	2	38.071	19.035	.279	.7583	.7583	.7583
floor * load * Subject(G..	39	2663.937	68.306				

Dependent: cogv(A)

Table 4.18 Descriptive summary of COGVA on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	56	115.987	17.493	2.338
middle	56	123.230	20.458	2.734
old	56	107.367	16.694	2.231

Figure 4.9 Age Groups effect on COGVA with 95% confidence error bars.

Table 4.19 Descriptive summary of COGVA on main effect Floor Levels.

	Count	Mean	Std. Dev.	Std. Error
carpet	84	118.385	16.411	1.791
vinyl	84	112.671	21.541	2.350

Figure 4.10 Floor Levels effect on COGVA with 95% confidence error bars.

Table 4.20 Descriptive summary of COGVA on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	84	117.334	15.830	1.727
no-load	84	113.721	22.196	2.422

In summary, the COGVA was significantly different across age groups. In general, younger subjects COGVA was faster than the older individuals and middle-aged group's COGVA was the fastest. On the average, COGVA was faster for the carpeted surface than the vinyl floor surface, and COGVA was faster for the load condition than the no-load condition.

4.2.6 Vertical Center-of-Gravity Velocity After Heel Contact

The summary of the three-way ANOVA is presented in Table 4.21.

4.2.6.1 Age Comparisons

The main effect (age group) was compared utilizing estimated vertical COGVA for young, middle, and old age groups across floor and load levels. It was hypothesized that vertical COGVA would be faster for the older individuals than their younger counterparts. The results of the three-way ANOVA indicated no statistically significant ($p > 0.05$) vertical COGVA differences between young (-4.27 cm/sec), middle (-4.62 cm/sec), and old (-5.87 cm/sec) subjects (Table 4.22).

4.2.6.2 Floor Levels Comparisons

The main effect (floor level) was compared using estimated vertical COGVA for each floor levels across both age groups and load levels. It was hypothesized that floor level would affect vertical COGVA of the subjects. The results indicated no statistically significant ($p > 0.05$) vertical COGVA differences between the carpeted (-5.06 cm/sec) and vinyl (-4.89 cm/sec) floor surfaces (Table 4.23).

4.2.6.3 Load Levels Comparisons

The main effect (load level) was compared using estimated COGVA for each load level across both age groups and floor levels. It was hypothesized that load levels would affect COGVA of the subjects. The results indicated statistically significant ($p \leq 0.05$) vertical COGVA differences between the load (-5.55 cm/sec) and no-load (-4.41 cm/sec) conditions (Table 4.24 and Figure 4.11).

Table 4.21. Summary of three-way ANOVA of 3 age groups, 2 floor levels and 2 load levels on vertical COGVA(including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
AGE	2	80.732	40.366	2.607	.0876		
Subject(Group)	36	557.385	15.483				
floor	1	.964	.964	.173	.6800	.6800	.6800
floor * AGE	2	13.352	6.676	1.197	.3138	.3138	.3138
floor * Subject(Group)	36	200.730	5.576				
load	1	47.582	47.582	10.103	.0030	.0030	.0030
load * AGE	2	1.465	.733	.156	.8565	.8565	.8565
load * Subject(Group)	36	169.545	4.710				
floor * load	1	.003	.003	.001	.9772	.9772	.9772
floor * load * AGE	2	2.324	1.162	.293	.7475	.7475	.7475
floor * load * Subject(G...	36	142.598	3.961				

Dependent: cogv (z)

Table 4.22. Descriptive summary of vertical COGVA on the main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
YOUNG	56	-4.274	2.598	.347
MIDDLE	40	-4.621	2.583	.408
OLD	60	-5.871	2.934	.379

Table 4.23. Descriptive summary of vertical COGVA on the main effect Floor Levels.

	Count	Mean	Std. Dev.	Std. Error
carpet	78	-5.063	2.739	.310
vinyl	78	-4.892	2.887	.327

Table 4.24. Descriptive summary of vertical COGVA on the main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	78	-5.549	2.387	.270
no-load	78	-4.405	3.081	.349

Figure 4.11. Load Levels effect on vertical COGVA with 95% confidence error bars.

4.2.6.4 Interactions

The results indicated no statistically significant vertical ($p > 0.05$) COGVA differences between interactions terms.

In summary, the vertical COGVA was significantly different across load levels. On the average, vertical COGVA was faster for the load condition than the no-load condition.

4.2.7 Velocity of Center-of-Gravity Difference (COGV_{diff})

The summary of the three-way ANOVA is presented in Table 4.25.

4.2.7.1 Age Comparisons

The main effect (age group) was compared using the calculated COGV_{diff} ($\text{COGV}_{\text{diff}} = \text{COGVA} - \text{COGVB}$) for young, middle, and old age groups across the carpeted floor surface only on the no-load condition. It was hypothesized that COGV_{diff} would be slower for the older individuals than their younger counterparts. (This measurement was used to explain RCOF differences among age groups in the discussion chapter). The results of the one-way ANOVA indicated statistically significant ($p \leq 0.05$) COGV_{diff} values between young (10.13 cm/sec), middle (8.43 cm/sec), and old (6.67 cm/sec) subjects (Table 4.26 and Figure 4.12). Tukey-Kramer post-hoc test indicated that young age group's COGV_{diff} was significantly different than their older counterparts.

In summary, as indicated by above analyses on the center-of-gravity velocities (before and after heel contact), COGV after heel contact was always faster than the COGV before heel contact. By taking the difference between these two velocities, one may find how fast the subjects transferred their center-of-gravity position (i.e., transfer of vertical force). This speed of transfer (or COGV_{diff}) may have some effect on RCOF. In addition, this analysis was only performed on the carpeted surface under a no-load condition to compare with normal walking condition (RCOF).

The results indicated that the younger individual's transfer of center-of-gravity was faster than the middle-aged and, elderly individuals.

Table 4.25 Summary of a one-way ANOVA of three age groups on $COGV_{diff}$.

Source	df	Sum of Squares	Mean Square	F-Value	P-Value
age	2	83.831	41.915	4.418	.0186
Residual	39	369.992	9.487		

Dependent: COGdiff

Table 4.26 Descriptive summary of $\text{COGV}_{\text{diff}}$ on main effect Age Group.

	Count	Mean	Std. Dev.	Std. Error
young	14	10.126	3.934	1.051
middle	14	8.432	3.168	.847
old	14	6.666	1.717	.459

Figure 4.12. Age Group effect on $\text{COGV}_{\text{diff}}$ with 95% confidence error bars.

4.2.8 Required Coefficient of Friction (RCOF)

The summary of the two-way ANOVA is presented in Table 4.27.

4.2.8.1 Age Comparisons

The main effect (age group) was compared utilizing calculated RCOF for young, middle, and old age groups across load levels on the carpeted floor surface. It was hypothesized that RCOF would be higher for the older individuals than their younger counterparts. The results of the two-way ANOVA indicated no statistically significant ($p > 0.05$) RCOF differences between young (.176), middle (.188), and old (.192) subjects (Table 4.28).

4.2.8.2 Load Comparisons

The main effect (load level) was compared using calculated RCOF for each of the age groups. It was hypothesized that load levels would affect RCOF. The results indicated no statistically significant ($p > 0.05$) RCOF difference between load (.186) and no-load (.184) conditions (Table 4.29).

4.2.8.3 Interactions

The results indicated no statistically significant ($p > 0.05$) RCOF differences between the interaction load x age (Table 4.30).

In summary, the main effect age groups and load levels were not significantly different. However, on the average, the RCOF was higher for the older individuals than the younger counterparts. In terms of the load levels, the interaction plot (Figure 4.13) indicated that for the elderly individuals, RCOF was dramatically increased for the load condition.

Table 4.27 Summary of a two-way ANOVA of 3 age groups and 2 load levels on RCOF(including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	.004	.002	2.392	.1047		
Subject(Group)	39	.033	.001				
load	1	8.005E-5	8.005E-5	.315	.5778	.5778	.5778
load * age	2	.001	2.539E-4	.999	.3773	.3773	.3773
load * Subject(Group)	39	.010	2.540E-4				

Dependent: rcof

Table 4.28 Descriptive summary of RCOF on main effect Age Group.

	Count	Mean	Std. Dev.	Std. Error
young	28	.176	.019	.004
middle	28	.188	.029	.005
old	28	.192	.021	.004

Table 4.29 Descriptive summary of RCOF on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	42	.186	.022	.003
no-load	42	.184	.026	.004

Table 4.30 Descriptive summary of RCOF on interaction effect (Age x Load).

	Count	Mean	Std. Dev.	Std. Error
load, young	14	.174	.018	.005
load, middle	14	.188	.025	.007
load, old	14	.196	.018	.005
no-load, young	14	.177	.020	.005
no-load, middle	14	.188	.033	.009
no-load, old	14	.187	.023	.006

Figure 4.13. Interaction (Age x Load) effect on RCOF with 95% confidence error bars.

4.2.9 Adjusted Required Coefficient of Friction (ARCOF)

The summary of the two-way ANOVA is presented in Table 4.31.

4.2.9.1 Age Comparisons

The main effect (age group) was compared utilizing calculated ARCOF for young, middle, and old age groups across load levels on the vinyl (slippery) floor surface. It was hypothesized that ARCOF would be higher for the older individuals than their younger counterparts (less optimally adjusted to maintain a fixed ratio of ARCOF to DCOF). The results of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) ARCOF differences between young (.073), middle (.10), and old (.12) subjects (Table 4.32 and Figure 4.14). Tukey-Kramer post-hoc test indicated that the younger group's ARCOF was significantly different from both the middle and older age groups.

4.2.9.2 Load Comparisons

The main effect (load level) was compared using the calculated ARCOF for each load level across age groups. It was hypothesized that load levels would affect ARCOF. The results indicated no statistically significant ($p > 0.05$) ARCOF difference between load (.093) and no-load (.102) conditions.

4.2.9.3 Interactions

The results indicated no statistically significant ($p > 0.05$) ARCOF difference interaction effect (Age x Load).

In summary, ARCOF was significantly different across age groups. Overall, the younger age group adjusted their ARCOF below their DCOF value of the vinyl floor surface, however, middle and elderly could not.

Table 4.31 Summary of two-way ANOVA of 3 age groups and 2 load levels on ARCOF (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	.028	.014	13.197	.0001		
Subject(Group)	39	.042	.001				
load	1	.002	.002	2.695	.1087	.1087	.1087
load * age	2	.003	.001	2.312	.1125	.1125	.1125
load * Subject(Group)	39	.025	.001				

Dependent: arcof

Table 4.32 Descriptive summary of ARCOF on main effect Age Group.

	Count	Mean	Std. Dev.	Std. Error
young	28	.073	.026	.005
middle	28	.102	.030	.006
old	28	.118	.033	.006

Figure 4.14. Age Group effect on ARCOF with 95% confidence error bars.

Table 4.33 Descriptive summary of ARCOF on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	42	.093	.034	.005
no-load	42	.102	.035	.005

4.2.10 Slip Distance (SD)

The summary of the two-way ANOVA is presented in Table 4.34.

4.2.10.1 Age Comparisons

The main effect (age group) was compared using calculated overall slip distance (from slip-start to slip-stop) for young, middle, and old age groups across load levels. It was hypothesized that elderly subject's overall SD would be longer than younger subjects. The result of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) overall SD differences between young (5.25 cm), middle (7.97 cm), and old (11.57 cm) subjects (Table 4.35 and Figure 4.15). Tukey-Kramer post-hoc test indicated that older age group's SD was significantly different from both the young and middle age groups.

4.2.10.2 Load Comparisons

The main effect (load level) was compared using calculated slip distance for each load level across age groups. It was hypothesized that load level would affect overall SD. The results indicated no statistically significant ($p > 0.05$) overall SD differences between load (8.68 cm) and no-load (7.85 cm) conditions (Table 4.36).

4.2.10.3 Interactions

The results indicated no statistically significant ($p > 0.05$) overall SD differences between the interaction effect (Age x Load).

In summary, overall SD was significantly longer for the older individuals than their younger counterparts and load did not significantly affect overall SD. Although overall SD was not significantly different across load levels, on the average, the interaction effect (Age x Load) indicated that older individuals overall SD was longer for the load condition than the no-load condition (Table 4.37 and Figure 4.16).

Table 4.34 Summary of two-way ANOVA of 3 age groups and 2 load levels on overall SD (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	563.420	281.710	9.956	.0003		
Subject(Group)	39	1103.545	28.296				
load	1	14.483	14.483	.552	.4619	.4619	.4619
load * age	2	98.260	49.130	1.873	.1672	.1672	.1672
load * Subject(Group)	39	1023.083	26.233				

Dependent: sd

Table 4.35 Descriptive summary of overall SD on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	28	5.246	4.128	.780
middle	28	7.969	4.887	.924
old	28	11.570	6.482	1.225

Figure 4.15. Age Group effect on overall SD with 95% confidence error bars.

Table 4.36 Descriptive summary of overall SD on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	42	8.677	6.721	1.037
no-load	42	7.846	4.779	.737

Table 4.37 Descriptive summary of overall SD on interaction effect (Age x Load).

	Count	Mean	Std. Dev.	Std. Error
load, young	14	5.015	3.905	1.044
load, middle	14	7.507	5.162	1.380
load, old	14	13.509	7.713	2.062
no-load, young	14	5.477	4.476	1.196
no-load, middle	14	8.431	4.743	1.268
no-load, old	14	9.631	4.435	1.185

Figure 4.16. Interaction effect on overall SD with 95% confidence error bars.

4.2.11 Slip Distance One (SD1)

The summary of the two-way ANOVA is presented in Table 4.38.

4.2.11.1 Age Groups Comparison

The main effect (age group) was compared using calculated slip distance one (SD1) (from slip-start to peak heel acceleration) for young, middle, and old age groups across load levels. It was hypothesized that elderly subject's SD1 would be longer than younger subjects. The results of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) SD1 differences between young (1.09 cm), middle (1.86 cm), and old (2.28 cm) subjects (Table 4.39 and Figure 4.17). Tukey-Kramer post-hoc test indicated that older age group's SD1 was significantly different from the middle age groups.

4.2.11.2 Load Levels Comparison

The main effect (load level) was compared using calculated slip distance for each load level across age groups. It was hypothesized that the load level would affect SD1. The results indicated no statistically significant ($p > 0.05$) SD1 differences between load (1.637 cm) and no-load (1.855 cm) conditions (Table 4.40).

4.2.11.3 Interaction

The results indicated no statistically significant ($p > 0.05$) SD1 differences between the interaction effect (Age x Load).

In summary, SD1 was significantly longer for the older individuals than their younger counterparts and load did not significantly affect SD1. Again, although SD1 was not significantly different across load levels, on the average, interaction effect (Age x Load) indicated that older individuals SD1 was longer for the load condition than the no-load condition (Table 4.41 and Figure 4.18).

Table 4.38 Summary of two-way ANOVA of 3 age groups and 2 load levels on SD1 (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	20.113	10.056	3.286	.0480		
Subject(Group)	39	119.364	3.061				
load	1	.999	.999	.989	.3260	.3260	.3260
load * age	2	4.768	2.384	2.360	.1078	.1078	.1078
load * Subject(Group)	39	39.401	1.010				

Dependent: sd1

Table 4.39 Descriptive summary of SD1 on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	28	1.098	1.405	.266
middle	28	1.859	1.431	.270
old	28	2.280	1.439	.272

Figure 4.17. Age Groups effect on SD1 with 95% confidence error bars.

Table 4.40 Descriptive summary of SD1 on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	42	1.637	1.475	.228
no-load	42	1.855	1.518	.234

Table 4.41 Descriptive summary of SD1 on interaction (Age x Load) effect.

	Count	Mean	Std. Dev.	Std. Error
load, young	14	1.111	1.370	.366
load, middle	14	1.417	1.280	.342
load, old	14	2.382	1.548	.414
no-load, young	14	1.085	1.492	.399
no-load, middle	14	2.301	1.481	.396
no-load, old	14	2.178	1.373	.367

Figure 4.18. Interaction effect on SD1 with 95% confidence error bars.

4.2.12 Slip Distance Two (SD2)

The summary of the two-way ANOVA is presented in Table 4.42.

4.2.12.1 Age Group Comparison

The main effect (age group) was compared using calculated slip distance two (SD2) (from peak heel acceleration to slip-stop) for young, middle, and old age groups across load levels. It was hypothesized that elderly subject's SD2 would be longer than younger subjects. The result of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) SD2 differences between young (3.97 cm), middle (6.21 cm), and old (9.49 cm) subjects (Table 4.43 and Figure 4.19). Tukey-Kramer post-hoc test indicated that older age group's SD2 was significantly different from both the young and middle age groups.

4.2.12.2 Load Levels Comparison

The main effect (load level) was compared using calculated SD2 for each load level across age groups. It was hypothesized that load level would affect SD2. The results indicated no statistically significant ($p > 0.05$) overall SD differences between load (7.07 cm) and no-load (6.06 cm) conditions (Table 4.44).

4.2.12.3 Interactions

The results indicated no statistically significant ($p > 0.05$) SD2 differences between the interaction effect (Age x Load).

In summary, SD2 was significantly longer for the older individuals than their younger counterparts and load did not significantly affect overall SD. Although SD2 was not significantly different across load levels, on the average, interaction effect (Age x Load) indicated that older individuals SD2 was higher for the load condition than the no-load condition (Table 4.45 and Figure 4.20).

Table 4.42 Summary of two-way ANOVA of SD2 on 3 age groups and 2 load levels (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	431.518	215.759	12.850	.0001		
Subject(Group)	39	654.844	16.791				
load	1	21.286	21.286	1.046	.3127	.3127	.3127
load * age	2	74.515	37.257	1.831	.1738	.1738	.1738
load * Subject(Group)	39	793.654	20.350				

Dependent: sd2

Table 4.43 Descriptive summary of SD2 on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	28	3.973	2.941	.556
middle	28	6.219	3.595	.679
old	28	9.493	5.968	1.128

Figure 4.19. Age Groups effect on SD2 with 95% confidence error bars.

Table 4.44 Descriptive summary of SD2 on main effect Load Levels.

	Count	Mean	Std. Dev.	Std. Error
load	42	7.065	5.922	.914
no-load	42	6.059	3.549	.548

Table 4.45 Descriptive summary of SD2 on interaction effect (Age x Load).

	Count	Mean	Std. Dev.	Std. Error
load, young	14	3.692	2.699	.721
load, middle	14	6.182	4.016	1.073
load, old	14	11.321	7.390	1.975
no-load, young	14	4.254	3.242	.867
no-load, middle	14	6.256	3.273	.875
no-load, old	14	7.665	3.489	.933

Figure 4.20. Interaction effect on SD2 with 95% confidence error bars.

4.2.13 Sliding Heel Velocity (SHV)

The summary of the two-way ANOVA is presented in Table 4.46.

4.2.13.1 Age Comparisons

The main effect (age group) was compared utilizing calculated SHV for young, middle, and old age groups across load levels. It was hypothesized that SHV would be faster for the older individuals than their younger counterparts. The result of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) SHV differences between young (44.06 cm/sec), middle (63.96 cm/sec), and old (74.14 cm/sec) subjects (Table 4.47 and Figure 4.21). Tukey-Kramer post-hoc test indicated that older age group's SHV was significantly different from their younger counterparts (only the young age group).

4.2.13.2 Load Comparisons

The main effect (load level) was compared using calculated SHV for each load condition across age groups. It was hypothesized that SHV would be faster for the load condition than the no-load condition. The result of the two-way ANOVA indicated no statistically significant ($p > 0.05$) SHV differences between the load (59.51 cm/sec) and no-load (61.93 cm/sec) conditions.

4.2.13.3 Interaction

The result indicated no statistically significant ($p > 0.05$) SHV differences between the interaction (Age x Load) effect.

In summary, the sliding heel velocity of the age groups differed significantly. In general, older subjects had faster sliding heel velocities than their younger counterparts. Composite of the sliding heel velocity pattern for different age groups is illustrated in the Figure 4.22. The pattern illustrates 15 frames of the gait cycle (7 frames before heel contact and 7 frames after heel contact).

Table 4.46 Summary of two-way ANOVA of 3 age groups and 2 load levels on SHV (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	13112.618	6556.309	5.536	.0077		
Subject(Group)	39	46188.550	1184.322				
load	1	123.694	123.694	.086	.7708	.7708	.7708
load * age	2	545.953	272.976	.190	.8278	.8278	.8278
load * Subject(Group)	39	56049.910	1437.177				

Dependent: hv (slip)

Table 4.47 Descriptive summary of SHV on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	28	44.056	35.101	6.633
middle	28	63.960	31.715	5.993
old	28	74.141	39.668	7.497

Figure 4.21. Age Groups effect on SHV with 95% confidence error bars.

Figure 4.22 Composite pattern of SHV on different age groups (including the heel contact frame [HC]).

4.2.14 Heel Acceleration (Hacc)

The summary of the two-way ANOVA is presented in Table 4.48.

4.2.14.1 Age Comparisons

The main effect (age group) was compared utilizing calculated Hacc for young, middle, and old age groups across load levels. It was hypothesized that Hacc would be faster for the older individuals than their younger counterparts. The results of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) Hacc differences between young (609.56 cm/sec^2), middle (906.82 cm/sec^2), and old (912.05 cm/sec^2) subjects (Table 4.49 and Figure 4.23). Tukey-Kramer post-hoc test indicated that younger age group's Hacc was significantly different from middle and old age groups.

4.2.14.2 Load Comparisons

The main effect (load level) was compared using calculated Hacc for each load condition across age groups. It was hypothesized that Hacc would be faster for the load condition than the no-load condition. The results of the two-way ANOVA indicated no statistically significant ($p > 0.05$) Hacc differences between the load (804.54 cm/sec^2) and no-load (814.42 cm/sec^2) conditions.

4.2.14.3 Interaction

The result indicated no statistically significant ($p > 0.05$) SHV differences between the interaction (Age x Load) effect.

In summary, the heel acceleration of age groups differed significantly. In general, older subjects had faster heel acceleration during slipping than their younger counterparts. Composite of the sliding heel acceleration pattern for different age groups is illustrated in the Figure 4.24. The pattern illustrates 15 frames of the gait cycle (7 frames before heel contact and 7 frames after heel contact).

Table 4.48 Summary of two-way ANOVA of 3 age groups and 2 load levels on Hacc (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	1678973.152	839486.576	5.448	.0082		
Subject(Group)	39	6009678.959	154094.332				
load	1	2051.340	2051.340	.013	.9094	.9094	.9094
load * age	2	62526.739	31263.369	.200	.8196	.8196	.8196
load * Subject(Group)	39	6097206.843	156338.637				

Dependent: hacc

Table 4.49 Descriptive summary of Hacc on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	28	609.565	418.166	79.026
middle	28	906.826	389.338	73.578
old	28	912.053	352.629	66.641

Figure 4.23. Age Groups effect on Hacc with 95% confidence error bars.

Figure 4.24 Composite sliding heel acceleration on different age groups (including the heel contact frame [HC]).

4.2.15 Center-of-Gravity Velocity During Slipping (COGVS)

The summary of the two-way ANOVA is presented in Table 4.50.

4.2.15.1 Age Comparisons

The main effect (age group) was compared utilizing calculated COGVS for young, middle, and old age groups across load levels. It was hypothesized that COGVS would be faster for the younger individuals than their older counterparts. The results of the two-way ANOVA indicated statistically significant ($p \leq 0.05$) COGVS differences between young (120.18 cm/sec), middle (130.24 cm/sec), and old (109.39 cm/sec) subjects (Table 4.51 and Figure 4.25). Tukey-Kramer post-hoc test indicated that middle age group's COGVS was significantly different from the old age groups.

4.2.15.2 Load Comparisons

The main effect (load level) was compared using calculated COGVS for each load condition across age groups. It was hypothesized that COGVS would be faster for the load condition than the no-load condition. The results of the two-way ANOVA indicated no statistically significant ($p > 0.05$) COGVS differences between the load (121.32 cm/sec) and no-load (118.56 cm/sec) conditions.

4.2.15.3 Interaction

The results indicated no statistically significant ($p > 0.05$) COGVS difference between the interaction (Age x Load) effect.

In summary, the velocity of center-of-gravity during slipping of age groups differed significantly. In general, older subjects had slower COGV during slipping than younger counterparts, and middle age group's COGVS was the fastest.

Summary of ANOVA results (initiation parameters and slip performance parameters) is presented in Table 4.52 and 4.53.

Table 4.50 Summary of two-way ANOVA of 3 age groups and 2 load levels on COGVS (including the p-values associated with Greenhouse-Geisser and the Huynh-Feldt adjustments).

Source	df	Sum of Squares	Mean Square	F-Value	P-Value	G-G	H-F
age	2	6093.940	3046.970	5.096	.0108		
Subject(Group)	39	23317.599	597.887				
load	1	160.392	160.392	1.665	.2045	.2045	.2045
load * age	2	122.177	61.089	.634	.5357	.5357	.5357
load * Subject(Group)	39	3756.688	96.325				

Dependent: cogv(slip)

Table 4.51 Descriptive summary of COGVS on main effect Age Groups.

	Count	Mean	Std. Dev.	Std. Error
young	28	120.183	16.050	3.033
middle	28	130.247	19.655	3.714
old	28	109.388	19.217	3.632

Figure 4.25. Age Groups effect on COGVS with 95% confidence error bars.

Table 4.52 Summary of ANOVA results on initiation of slip (parameters).

Source	Dependent Measure				
	Step Length	SLI	Heel Velocity	RCOF	vCOG Va
Age	*	*			
Floor	*	*	*		
Load					*
Age * Floor	*				
Age * Load					
Age*Floor*load					

* Significant at $\alpha = 0.05$

Table 4.53 Summary of ANOVA results on slip performance measures.

Source	Dependent Measure				
	ARCOF	SD	SD1	SHV	Hacc
Age	*	*	*	*	*
Load					
Age * Load					

* Significant at $\alpha = 0.05$

4.3 Correlation Analysis

Bivariate correlation analyses were performed to describe the relationships between the independent (HV, COGVB, and COGVA) and dependent (RCOF) variables. There were three separate bivariate correlation analyses. To investigate the relationship between the initial gait characteristics and RCOF, bivariate correlation analyses were performed between the heel velocity (x) and RCOF (y), COGVB (x) and RCOF (y), and COGVA (x) and RCOF (y). To investigate the initial jarring effect during the heel contact phase of the gait, bivariate correlation analysis was performed between the vertical COGVA and lower extremity (leg) strength.

4.3.1 HV and RCOF

Bivariate correlation analysis between HV and RCOF indicated no statistically significant relationship ($p > 0.05$). ($R^2 = .1177$, $p = 0.286$).

4.3.2 COGVB and RCOF

Bivariate correlation analysis between COGVB and RCOF indicated statistically significant relationship ($p \leq 0.05$). ($R^2 = .2909$, $p = 0.007$).

4.3.3 COGVA and RCOF

Bivariate correlation analysis between COGVA and RCOF indicated statistically significant relationship ($p \leq 0.05$). ($R^2 = .4616$, $p = 0.0001$).

4.3.4 Vertical COFVA and Leg Strength

Bivariate correlation analysis between vertical COGVA and RCOF indicated statistically significant relationship ($p \leq 0.05$). ($R^2 = -.516$, $p = 0.0001$).

4.4 Regression Analyses

Regression analyses were performed to describe and predict the relationships between the independent (predictor variable (X)) and dependent (response variable (Y)) variables. The response variables (Y) were slip distance (SD), SDI, HV, SHV, and Hacc. The predictor variables (X) were age, gender, weight, height (stature), sensory organization test scores (vision, proprioceptive, and vestibular system response), maximal

isometric strength and muscle latency (ML) response. These analyses were used to explain which variables (dependent) were related to slip severity (e.g., slip distance). For prediction purposes, a statistical model developed by analyzing the relationships between the response variable and predictor variables was utilized to predict response variables given the predictor variables. These models predicted which subjects would have greater difficulty adjusting to walking over unexpected slippery floor surfaces. The data were analyzed by utilizing techniques (scatter plot, residual vs. predicted, normal probability plot, hat matrix, Cook's D, and Variance Inflation Factor [VIF] -for the multicollinearity) available for evaluating the assumptions of regression analysis (the assumption of a probabilistic process, functional specification of mean response, constant variance, normality assumptions). The predictor variables were selected by utilizing the cp and the backward elimination procedure for the dependent variables.

4.4.1 SD

The final model of overall SD is listed in Table 4. 54. Fitted values of SD and actual SD are presented in Figure 4.26.

The results of the regression analysis indicated that the relationship between SD and physical parameters of the subject population was significant with $R^2 = .413$.

Furthermore, vision, muscle control time (MCT) and lower leg strength index (lower leg strength/weight) were significant. This suggests that there is some relationship between SD and physical parameters (vision, MCT, and LLI).

4.4.2 SDI

The final model of SDI is listed in Table 4. 54. The results of the regression analysis indicated that the relationship between SDI and physical parameters of the subject population was meaningful with $R^2 = .323$. Although cp statistics indicated some relationships, the variables AGE, GENDER, VISION, and VEST were not significant ($p > 0.05$). However, MCT and LLI were significant ($p \leq 0.05$). This suggests that there is some relationship between SDI and physical parameters (MCT and LLI). In addition, the gender term in the model suggested that SDI would be longer for the female subjects than the male subjects given the same treatments (i.e., utilized 0 for male and 1 for female).

4.4.3 HV

The final model of the HV is listed in Table 4. 54. The result of the regression analysis indicated that the relationship between the HV and physical parameters of the subject population was meaningful with $R^2 = .281$. Although cp statistics indicated some relationships, the variables AGE and VEST were not significant ($p>0.05$). However, VIS was significant. This analysis suggest that there is some relationship between HV and VIS.

4.4.4 SHV

The final model of the SHV is listed in Table 4. 54. The result of the regression analysis indicated that the relationship between the SHV and physical parameters of the subject population was less meaningful (than SD, SDI, HV and SHV) with $R^2 = .174$. Although cp statistics indicated some relationships, the variables AGE and MCT were not significant ($p>0.05$). However, GEN was significant. The gender term in the model suggested that SHV will be faster for the female subjects than the male subjects given the same treatments.

4.4.5 Hacc

The final model of the Hacc is listed in Table 4.54. The result of the regression analysis indicated that the relationship between the Hacc and physical parameters of the subject population was somewhat meaningful with $R^2 = .177$. Again, as was with SHV, AGE and MCT were not significant ($p>0.05$). However, GEN was significant. The gender term in the model suggested that Hacc will be faster for the female subjects than the male subjects given the same treatments.

Table 4.54 Summary of multiple regression between SD and physical parameters.

Multiple Regression Equation	R ²
SD = -15.785 -.037 (vision) + .204 (MCT) - .308 (LLI)	.413
SDI = 13.59 + .027 (age) + 1.03 (gen) -.02 (vision) -.01 (vest) -.08 (MCT) - 2.61 (LLI)	.323
HV = -30.44 +1.37 (age) + 8.98 (vision) + 4.24 (vest)	.281
SHV = 666.79 + 5.33 (age) + 73.37 (gen) - 4.35 (MCT)	.174
Hacc = 1050.77 + 8.56 (age) + 121.27 (gen) - 6.96 (MCT)	.177

Figure 4.26. Fitted values of SD and actual SD.

4.5 Sensory Organization Test (SOT) and Muscle Control Test (MCT)

4.5.1 Sensory Organization Test (SOT)

The purpose of this test was to indicate how good a subject's overall balance might be relative to population norms and to assess more specific information about the contributions of vision, muscle feedback and inner ear to balance for each of the individuals. The overall average of SOT scores for the subjects indicated that the younger subject's SOT scores (83.85) were significantly ($p \leq 0.05$) higher than the middle (78.6), and old (68.1) subjects (Table 4.55).

4.5.2 Muscle Control Test (MCT)

The purpose of this test was to indicate how well individuals respond to translation of the force plates and further assess specific information about the contributions of sensory input and response selection and execution of the subjects. The overall average of the MCT scores for the subjects indicated that the younger subject's muscle latency time (123.28 ms) was significantly ($p \leq 0.05$) lower than the middle (131.40 ms), and old (139.73 ms) subjects (Table 4.55).

4.6 Maximal Isometric Strength

4.6.1 Maximal Isometric Strength of the Arms

The result of the one-way ANOVA of the maximal isometric arm strength across age groups indicated no statistically significant ($p > 0.05$) arm strength differences between young (327.93 N), middle (346.00 N), and old (285.80 N) subjects (Table 4.56).

4.6.2 Maximal Isometric Strength of the Legs

The result of the one-way ANOVA of the maximal isometric leg strength across age groups indicated statistically significant ($p \leq 0.05$) leg strength differences between young (923.00 N), middle (855.10 N), and old (605.67 N) subjects (Table 4.57).

4.6.3 Maximal Isometric Strength of the Torso

The result of the one-way ANOVA of the maximal isometric torso strength across age groups indicated no statistically significant ($p > 0.05$) torso strength difference between young (730.46 N), middle (762.00 N), and old (557.47 N) subjects (Table 4.58).

Table 4.55 Descriptive summary of SOT and MCT scores on Age groups.

Age Groups	SOT (%)	MCT (ms)
Young	83.85	123.78
Middle	78.60	131.40
Old	68.13	139.73

Table 4.56 Summary of one-way ANOVA of 3 age groups on maximal isometric arm strength.

Source	df	SS	MS	F	p-value
Age	2	24667.646	12333.823	.987	.3825
Residual	39	449851.329	12495.870		

Table 4.57 Summary of one-way ANOVA of 3 age groups on maximal isometric leg strength.

Source	df	SS	MS	F	p-value
Age	2	798079.459	399039.72	4.224	.0225
Residual	39	3400522.233	94458.95		

Table 4.58 Summary of one-way ANOVA of 3 age groups on maximal isometric torso strength.

Source	df	SS	MS	F	p-value
Age	2	325621.278	162810.64	2.249	.1202
Residual	39	2606597.965	72405.49		

4.7 Slip and Fall Classification

Slip and fall classification was obtained by comparing horizontal COGVA of the whole body with sliding heel velocity of the individuals on the slippery surface (during slipping). A fall was identified as whenever the average SHV was greater than the average horizontal COGVA. A slip (recovery) was identified whenever SHV did not exceed the average horizontal COGVA during slipping. The result of slip and fall classification indicated that younger individuals (24 slips and 4 slips and falls), as well as the middle-aged (20 slips and 8 slips and falls), and older individuals (16 slips and 12 slips and falls) slipped; however, older individuals fall frequency was higher (Figure 4.31).

In addition, utilizing the slip and fall classification and comparing with newly defined slip parameters, exceeding certain limits (see Table 4.59) of SHV, Hacc, and SD1 resulted in falls (recovery index). The results of this analysis indicated that the younger individuals recovery index was higher on the average and suggested that the recovery index is not all same for the different age groups (Table 4.59). Thus in a given situation, the older individuals are at a higher risk for fall accidents.

Figure 4.27. Slip and fall classification by the age groups.

Table 4.59. Slip recovery index across three age groups.

	SHV(cm/s)	SD1 (cm)	Hacc (cm/s²)
Young	144.45	3.91	1580
Middle	145.26	3.80	1310
Old	107.63	3.12	1220

CHAPTER 5

CONCLUSIONS AND RECOMMENDATIONS

5.1 Conclusions

This chapter summarizes the principal experimental findings and discusses them with respect to the experimental objectives (hypotheses) presented in Chapter 1.

5.1.1 Principal Experimental Findings

5.1.1.1 Initiation of Slips

Older age group's RCOF will be higher than their younger counterparts due to the muscle weakness and initial gait characteristics.

As indicated by many researchers, initial gait characteristics such as step length and heel velocity may affect RCOF due to the increase in horizontal foot force. Consistent with previous findings (Winter, 1990, Lockhart, 1997) older individuals step length was shorter than their younger counterparts and the older individuals heel velocity was on the average faster than the younger individuals. However, the results from this investigation indicated that older age group's RCOF was not significantly higher than younger counterparts (although overall mean of the RCOF was higher for the older individuals). These results are somewhat confounding due to the fact that shorter step length of the older individuals should have resulted in lower overall mean value of RCOF. This generalization leads one to believe that the higher heel velocity may have affected RCOF, however, when examining carefully how RCOF was calculated (at peak 3), the instantaneous heel velocity at heel contact may have minimum effect on the RCOF (due to the heel already being on the ground and going backwards at this instance). Furthermore, bivariate correlation analysis between RCOF and HV have indicated no statistically significant relationship ($R^2 = .1177$, $p = .286$). These findings suggest that there might be other variable(s) affecting RCOF. Bivariate correlation analyses between RCOF and COGVB and COGVA indicated statistically significant relationships ($R^2_{\text{COGVB}} = .29$, $p_{\text{COGVB}} = .007$; $R^2_{\text{COGVA}} = .46$, $p_{\text{COGVA}} = .0001$). These results suggest that the RCOF is affected by walking velocity (or COG velocity) rather than heel velocity of the subjects. Furthermore, $\text{COGV}_{\text{diff}}$ may have greater influence on RCOF

values than the all other variables discussed so far. As indicated in the results, younger individuals transfer of COG was faster than older individuals on the carpeted surface, this faster transfer of COG may have decreased the ratio of horizontal to vertical force (i.e. RCOF) for the younger individuals.

In conclusion, older age group's RCOF was not significantly higher than their younger counterparts, and initial gait characteristics such as heel velocity did not significantly influence RCOF. In addition, based on the analysis of slip distances (particularly the SD1), younger individuals as well as older individuals were susceptible to slips. These results indicate that initiation of slips are far more complicated than thought before, and younger individuals as well as older individual are susceptible to slips.

5.1.1.2 Detection and Recovery

Older age group's slip performance measures (e.g., slip distance, sliding heel velocity, heel acceleration and adjusted required coefficient of friction) will be poorer (less optimally adjusted to maintain balance) than younger counterparts.

Older age group's slip distances will be longer than younger counterparts due to the muscle weakness and sensory degradation.

Irrespective of the activity being performed or the environmental factors associated with the time of a potential fall, there are certain processing stages that the central nervous system must undertake (detection phase) if a fall is to be avoided or compensated for (recovery phase). First, during the detection phase, if a potential slip and fall is imminent, sensory input must trigger or alert those centers responsible for response selection. This alerting process may be initiated by one or more of the following sensory inputs; proprioception, vision, or vestibular function. The results of the Sensory Organization Test indicated that equilibrium scores were lower for older individuals due to the sensory degradation (especially the vestibular). In addition, muscle latency time (reaction time) was longer for older individuals than for their younger counterparts. The effect of the sensory degradation is further supported by higher ARCOF. On the average, the younger individuals ARCOF (.074) was adjusted within the dynamic friction requirements (.08). However, on the average, middle (ARCOF - .10) and older

individuals (ARCOF - .12) could not. Consequently, the result was longer slip distances and higher frequency of falls. The prediction model further supports that the vision, reaction time and muscle strength (lower extremity) were important for determining slip and fall severity.

In conclusion, all subjects (young and old) slipped under slippery conditions. However, the older individuals could not control their slips, leading to more falls. Inability to control slipping responses may be a result of the sensory degradation and muscle weakness. Most of the current research on slips and falls concentrates predominantly on initiation of slips (i.e., RCOF), however, this study indicates that how slips result in a fall is important as well. Therefore, future research should focus not only on the dynamics of slips, but the dynamics of falls.

5.1.1.3 Work Demand

Increasing the work demand (induced by the load) will affect the gait of older groups more than their younger counterparts in ways that make slip and fall accidents more likely.

Carrying the load most likely resulted in deteriorated vision of the subjects at heel contact phase of the gait cycle (rather than “induce work demand”), which could have affected their slip and recovery characteristics. However, although only a light load was used in this study, the load effect was much more pronounced for the older individuals than their younger counterparts.

In terms of initiation of slip, overall average of RCOF (age x load) indicated that older individuals RCOF was higher for the load condition than the no-load condition. In addition, vertical COGVA was significantly faster for the load condition than the no-load condition. Thus, it seems that the older individuals landed their feet quickly in order to compensate for an absent visual cue and thereby increasing the slip tendency (e.g. higher horizontal force). Therefore the older individuals risk for initiation of slip may increase. In terms of detection and recovery of slips and falls, older individuals slip distance was affected by load more than the younger counterparts. On the average, older individuals slip distance was longer for the load condition than the no-load condition. Thus the load

carriage may increase likelihood of slip and fall accidents of older individuals more than their younger counterparts.

5.2 Final Remarks

5.2.1 Limitations of the Study

The following limitations apply to the study:

1. Errors associated with video instrumentation and the measurement/data reduction process are acknowledged (such as: digitizing error, camera vibration, instrument calibration, errors in identifying anatomical landmarks, and synchronization of the video and analog systems).
2. Errors associated with (a) representing analog signals in digital format and (b) the sequential sampling of the analog channels by the analog to digital converter are acknowledged and assumed minimal.
3. Limitations associated with the utilization of existing anthropometric models to obtain information about body segment parameters is recognized.

5.2.2 Assumptions

The following assumptions were made in the study:

1. Subjects will be properly categorized into their experimental groups.
2. Subjects will respond naturally and their performances will be unaffected by the experimental setting and included instrumentation.
3. Instrumentation will perform reliably and the sampling rates will be sufficient for obtaining information about the characteristics of gait.
4. The whole body COG model will provide adequate estimates of the real COG during walking.
5. Experimental design and methodology will answer stated hypothesis.

This research project was undertaken to quantify gait parameter differences between older and younger individuals under inadvertent slip and fall situations. Although every attempt was made to study inadvertent slips and falls, some assumptions made in this study could lead to potential sources of error. For example, it was assumed

that the subject's gait was consistent for all trials, but there may have been some subtle changes in gait between conditions. Although speculated, an inspection of the data indicated that the subjects were consistent throughout the experiment.

5.2.3 Middle-Age Considerations

The results of the gait parameters indicated greater dispersion of parameter data for the middle age group than the young and old groups. This dispersion may have influenced factor analyses thereby reducing significance. The source of this dispersion of parameter data may have resulted from the wide range of middle age (35 to 59 years old) classification. Therefore, in the future, age category should be contained within the normal characteristics of age groups (e.g., divide middle age into two categories). In addition, in order to increase the power of analyses, increase the number of subjects, or categorize age groups into physiological age groups utilizing their sensory and muscle strength.

5.3 Recommendations for Future Research

1. The gait parameter differences between the age groups were indicated, however, the processes involving the control of the gait parameters were not explored. Therefore, it may be desirable to further investigate control of the gait parameters by studying different types of gait patterns.
2. The regression models indicated that the lower extremity muscle strength was important for decreasing slip severity. Therefore, future study should explore the training effect (such as muscle strengthening) on severity of slips and falls.
3. The load condition affected the gait parameters of the subjects, however, the effects of load was most likely due to the obstruction of the visual field during the heel contact phase of the gait cycle. In order to alleviate this problem, future load carriage study should be explored with see-through (plexiglass) containers.

REFERENCES

- Amontons, M., 1699, De la resistance causee dans les machnies. *Histoire del' Academie Royale des Sciences Avec les Memoires Mathematique et de Physique*, Paris , 206.
- Andersson, R., & LagerLof, E., 1983, Accident data in the new Swedish information system on occupational injuries. *Ergonomics*, 26(1), 33-42.
- Andres, R.O., & Chaffin, D.B. ,1985, Ergonomic analysis of slip-resistance measurement devices. *Ergonomics*, 28(7), 1065-1080.
- Andres, R.O., & O'Connor, D.O., 1992, A practical synthesis of biomechanical results to prevent slip and falls in the workplace. *Advances in Industrial Ergonomics and Safety IV*, 1001-1006.
- Andriacchi, T.P., Ogle, J.A., Galante, J.O., 1977, Walking speed as a basis for normal and abnormal gait measurements. *J. Biomech.* 10: 261-268.
- ASTM (American Society for Testing and Materials), 1975, designation D 2047-75, Standard method of test for static COF of polish-coated floor surfaces as measured by the James Machine. *American Society for Testing and Materias*, Philadelphia.
- Astrand, P. O. and Rodahl, K., 1986, *Textbook of Work Physiology*. New York: McGraw-Hill.
- Baker, S.P., & Harvey, A.H., 1985, Fall injuries in elderly. *Clin. Geriatr. Med.*, 1, 501-512.
- Baker, S.P., O'Neil, B., & Karpf, R., 1984, *The Injury Fact Book*. Lexington, MA: Lexington Books.
- Barter, J. T., 1957, Estimation of the mass of body segments. WADC Technical report 57-260, Wright-Patterson Air Force Base, Ohio, 1957.
- Basler, A., 1931, Die Lage des Schwerpunktes in lebenden Menschen. *Fortschritte der Medizin.* 11: 310-28.
- Basmajian, J.V., 1976, The human bicycle, *Proceedings of the Fifth International Congress of Biomechanics*, Jyvaskyla, Finland.
- Bassey, E.J., Gentem, P.H., MacDonald, I.C., & Scriven, P.M., 1976, Self-paced walking as a method for exercise testing in elderly and young men. *Clin. Sci.*, 51, 609-612.

- Belen'kii, V.Ye., Gurfinkel, V.S., & Pal'tsev, Ye.I., 1967, Elements of control of voluntary movements. *Biofizika*, 12, 154-168.
- Bernsten, N., 1967, *The coordination and regulation of movements*. London: Pergamon Press, 9-14.
- Bidanda, B., & Redfern, M.S., 1991, Development of a micro computer based slip resistance tester. *Computers in Industrial Engineering Journal*.
- Bober, T., 1966, Porowanie metod wyznaczenia sroda ciezkosci cial a u czlosieka. *Wychowanie Fizyczne i Sport* 10: 109-15.
- Bonder, B. R. and Wagner, M. B., 1994, *Functional Performance in Older Adults*. Philadelphia: F. A. Davis Company.
- Bouisset, S., & Zattara, M., 1981, A sequence of postural movements precedes voluntary movement. *Neurosci. Lett.*, 22, 263-270.
- Borelli, G. A., 1680, *De motu animalium*. Lugduni Batavorum.
- Braune, W., and Fischer, O., 1889, Vber den Schwerpunkt des menschlichen korpers, mit Riicksicht auf die Ausrustung des deutschen In fanteristen. Abhandlungen der mathematisch-physichen classe der Koigl, *Sachsischen Gesellschaft der Wissenschaften*. 26: 561-672.
- Brinckmann, P., Hoefer, H. and Jongen, H. Th., 1981, Sex differences in the skeletal geometry of the human pelvis and hip joint. *J. Biomechanics*, 14, 427-430.
- Bring, C., 1964, *Friction and slipping*. Stockholm, Sweden: The National Swedish Council for Building Research.
- Bring, C., 1982, Testing of slipperiness. Document D5:1982. Stochholm: *The National Swedish Council for Building Research*.
- Brocklehurst, J.C., Robertson, D., & James-Groom, P., 1982, Clinical correlates of sway in old age - sensory modalities. *Age Ageing*, 11, 1-10.
- Broer, M.R., & Zernicke, R.F., 1979, *Efficiency of human movement*, Philadelphia, PA: Saunders College Publishing, 45-58, 172-184.
- Brooks, C. B., and Jacobs, A. M., 1975, The gamma mass scanning technique for inertial anthropometric measurement. *Med. Sci. Sports* 7, 290-294.
- Brough, R., Malkin, F., & Harrison, R., 1979, Measurement of the COF of floors. *Journal of Physics*, 12, 517-528.

- Braun, R., & Brungraber, R.J., 1978, A comparisons of two slip resistance testers. In C. Anderson & J. Seene (Eds.), *Walkway surface: Measurement of slip resistance*, ASTM STP 649 (pp. 49-59). Philadelphia: American Society for Testing and Materials.
- Brungraber, R.J., 1977, A new portable tester for the evaluation of the slip-resistance of walkway surfaces. *U.S. National Bureau of Standards*, Technical Note 953.
- Brunterngchit, Y., 1990, *Measurement of dynamic friction available between shoes and floors, appropriate to friction demand in walking*. Unpublished Ph.D. dissertation, The University of New South Wales, Australia.
- Buck, P.C., & Coleman, V.P., 1985, Slipping, tripping and falling accidents at work: A national picture. *Ergonomics*, 28(7), 949-958.
- Campbell, A.J., Reinken, J., Allan, B.C., & Martinez, G.S., 1981, Falls in old age; a study of frequency and related factors. *Age Aging*, 10, 264-270.
- Cappozzo, A., Figura, F., & Marchetti, M., 1976, The interplay of muscular and external forces in human anulation. *J. Biomech.*, 9, 35-43.
- Cappozzo, A., 1981, Analysis of the linear displacement of the heel and trunk during walking at different speeds. *J. Biomech.* 14: 411-425.
- Carlsoo, J., 1962, A method for studying walking on different surfaces, *Ergonomics*, 5, 271-274.
- Cavagna, G.A., Dusman, B., and Margaria, R., 1968, Positive work done by a previously stretched muscle. *J. Appl. Physiol.* 24: 21.
- Chaffin, D.B., & Andersson, G.B.J., 1984, *Occupational Biomechanics*, New York: John Wiley & Sons, Inc.
- Chaffin, D. B., Herrin, G. D., and Keyserling, W. M., 1978, Preemployment strength testing, *J. Occup. Med.* 20(6), 403-408.
- Chaffin, D.B., Woldstad, J.C., & Trujillo, A., 1992, Floor/shoe slip resistance measurement. *Am. Ind. Hyg. Assoc. J.*, 53, 283-289.
- Clauser, C. E., McConville, J. T., Young, J.W., 1969, Weight, volume and center of mass of segments of the human body. AMRL Technical Report 69-70, Wright-Patterson Air Force Base, Ohio.
- Clarkson, P.M., 1978, The effect of age and activity level on simple and choice fractionated response time. *Eur. J. Appl. Physiol.*, 40, 17-25.

- Cleaveland, H.G., 1955, The determination of the center-of-gravity of segments of the human body. Ed. D. dissertation, University of California, Los Angeles.
- Cohen, H.H., & Compton, D.M.J., 1982, Fall accident patterns: Characterization of most frequent work surface-related injuries. *Professional Safety*, 16-22.
- Cohen, H.H., & Cohen, D.M., 1994a, Psychophysical assessment of the perceived slipperiness of floor tile surfaces in a laboratory setting. *Journal of Safety Research*, 25(1), 19-26.
- Cohen, H.H., & Cohen, D.M., 1994b. Perceptions of walking slipperiness under realistic conditions utilizing a slipperiness rating scale. *Journal of Safety Research*, 25(1), 27-31.
- Cohn, T.E., & Lasley, D.J., 1985, Visual depth illusion and falls in the elderly. *Clin. Geriatr. Med.*, 1, 601-610.
- Coleman, R., 1993, A demographic overview of the aging of the First World populations. *Applied Ergonomics*, 24, 5-8.
- Cooper, J. M., & Glassow, R.B., 1963, *Kinesiology*. New York: Mosby Company, 140-175.
- Cooper, J.M., & Glassow, R.B., 1968, *Kinesiology*. New York: Mosby Company, 150-164.
- Cotton, F. S., 1931, Studies in center-of-gravity changes. 1. A new method for finding the height of the center-of-gravity in man, with some applications. *Australian Journal of Experimental Biology and Medical Science* 8(1); 53-67.
- Cotton, F. S., 1932, Studies in center-of-gravity changes. 2. A new method of determining the anteroposterior position of the center-of-gravity balance table. *Australian Journal of Experimental Biology and Medical Science* 10(1): 17-32.
- Coulomb, C.A., 1785, *Memoires de Mathematique et de Physique del' Academie royale des Science*, Paris, 10, 161.
- Cram, A.P. and Masters, L.W., 1974, Preliminary study of the slipperiness of flooring. *National Bureau of Standards*, NBSIR, 74, 613.
- Croskey, M. I., Dawson, P.M., Iuessen, A.C., Marohn, I.E., and Wright, H.E., 1922, The height of the center-of-gravity in man. *American Journal of Physiology* 61: 171-85.
- Crowinshield, R.D., Brand, R.A. & Johnston, R.C., 1978, The effect of velocity on the kinematics and kinetics of gait. *Clinical Orthopedics and Related Research*, 132, 140-144.

- Cummings, S.R., Rubin, S.M., and Black, D., 1990, The future of hip fractures in the United States. *Clinical Orthopaedics and Related Research*, 252: 163-166.
- Czaja, S. J., 1990, *Human Factors Research Needs for an Aging Population*. Washington, DC: National Academy Press.
- Davis, P.R., 1983, Human factors contributing to slips, trips and falls, *Ergonomics*, 26(1), 51-59.
- Demeny, G., 1887, Etude des déplacements du centre de gravité dans le corps de l'homme pendant les actes de la locomotion. *comptes Rendus Hebdomadaires des séances de l'Académie des Sciences*. 105: 679-82.
- Dempster, W. T., 1955, Space requirements of the seated operator, WADC Technical Report 55-159, Wright-Patterson Air Force Base, Ohio.
- Do, M.C., Breniere, Y., & Brenguier, P., 1982, A biomechanical study of balance recovery during the fall forward. *J. Biomech.*, 15, 933-939.
- Drillis, R., 1958, Objective recording and biomechanics of pathological gait, *Ann. N.Y. Acad. Sci.*, 74, 86-109.
- Drillis, R., and Contini, R., 1966, Office of Vocational Rehabilitation, Department of Health, Education, and Welfare, Technical Report 1166.03. New York University School of Engineering and Science, 1966.
- Ekkubus, C.F., & Killey, W., 1973, Validity of .5 static COF (James Machine) as a measure of safe walkway surfaces. *Soap/Cosmetics/Chemical*, 49(2), 40-45.
- Exton-Smith, A.N., 1977, Functional consequences of aging: Clinical manifestation, in Exton-Smith A.N., Grimeley-Evans J (eds): *Care of the Elderly: Meeting the challenge of dependency*. London: Academic Press, 41.
- Fernie, G.R., & Holliday, P.J., 1978, Postural sway in amputees and normal subjects. *J. Bone Joint Surg.*, 60A, 895-898.
- Finley, F. R., Karpovich, P.V., 1969, Locomotor patterns in elderly women. *Arch. Phys. Med. and Rehab.* 50:140-146.
- Fischer, O., 1906, Theoretische Grundlagen für eine Mechanik der lebenden Körper mit Speziellen Anwendungen auf den Menschen, sowie auf einige Bewegungsvorgänge an Maschinen. Berlin: B.G. Teubner.
- Fozard, J.L., Wolf, E., Bell, B., 1977, Visual perception and communication. In Birren, J.E., and Schaie, K.W. (eds.): *Handbook of the Psychology of Aging*. New York: Van Nostrand Reinhold.

- Gescheider, G.A. ,1985, *Psychophysics: method, theory, and application*. Hillsdale, NJ: Lawrence Erlbaum Associates.
- Gillis, B., Gilroy, K., Lawley, H., Mott, L. and Wall, J.C., 1986, Slow walking speeds in healthy young and elderly females. *Physiotherapy Canada* 38:350-352.
- Goldman, R., 1986, Decline in organ function with aging. In I. Rossman (Ed.), *Clinical Geriatrics*, Philadelphia: Lippincott, 23-59.
- Gooch, H.D., 1981, A comparison of four methods of measuring slip resistance of floor polishes. *Chem. Times and Trends*, 7, 47-51.
- Gottsdanker, R., 1980, Aging and the maintenance of preparation. *Exp. Aging Res.*, 6, 13-27.
- Gottsdanker, R., 1982, Aging and simple reaction time. *J. Gerontol.*, 37, 342-348.
- Grieve, D.W. and Gear, R.J., 1966, The relationship between length of stride, step frequency, time of swing and speed of walking for children and adults. *Ergonomics* 9: 379-399.
- Grieve, D.W., 1968, Gait patterns and the speed of walking. *Biomedical Engineering*, 3, 119- 122.
- Gronqvist, R., Roine, J., Jaroinen, E., & Korhonen, E., 1989, An apparatus and a method for determining the slip resistance of shoes and floors by simulation of human foot motions. *Ergonomics*, 32(8), 979-995.
- Gronqvist, R., Roine, J., Korhonen, E., & Rahikainen, A., 1990, Slip resistance versus surface roughness of deck and other underfoot surfaces in ships. *J. Occup. Accid.*, 13, 291-302.
- Gronqvist, R., Hirvonen, M., & Tuusa, A. ,1993, Slipperiness of the shoe-floor interface: Comparison of objective and subjective assessments. *Applied Ergonomics*, 24(4) 258-262.
- Gryfe, C.I., Amies, A., & Ashley, M.J., 1977, A longitudinal study of falls in an elderly population: Incidence and morbidity. *Age Aging*, 6, 201.
- Haddon, W. and Baker, S.P., 1981, Injury control, in Clark D.W., MacMahion B. (eds): *Preventive and Community Medicine* (2nd.ed.). Boston, MA: Little Brown and CO. 109-140.
- Hanavan, E. P., 1964, A mathematical model of the human body. AMRL Technical Report 64-102, Wright-Patterson Air Force Base, Ohio, 1964.

- Harless, E., 1860, Die statischen Momente der menschlichen Gliedmassen. Abhandlungen der Mathemat.-Physikalischen classe der Koeniglichen Bayerischen Akademie der Wissenschaften. 8, 69-96, 257-94.
- Harris, G.W., & Shaw, S.R. ,1988, Slip resistance of floors: users' opinions, Tortus instrument readings and roughness measurement. *Journal of Occupational Accident*, 9, 287-298.
- Hasselkus, B.R., 1974, Aging and the human nervous system. *American Journal of Occupational Therapy*, 28, 16-21.
- Hasselkus, B.R., 1975, Aging and postural sway in women. *Journal of Gerontology*, 30 (6), 661-667.
- Haupt, B.J., & Graves, E., 1982, Detailed diagnoses and surgical procedures for patients discharged form short-stay hospitals: United States, 1979. DHHS Pub. No. (PHS) 82- 1274-1. U.S. *Department of Health and Human Services*, Washington, D.C.
- Hay, J.G., 1973, The Center-of-gravity of the Human Body. *Kinesiology III*, 20-44.
- Haycraft, J. B., 1900, Animal mechanics. In E. A. Schafer (Ed.). *Textbook of Physiology*. Edinburgh: Young J. Pentland, 228-73.
- Haywood, K.M., 1986, *Life Span Motor Development*, Champaign, IL: Human Kinetics Publishers, nc. 109-115.
- Herman, R., Wirta, R., Bampton, S. & Finley, F.R., 1976, Human solutions for locomotion. I. Single limb analysis. In: Herman, R., Grillner, S., Stein, P.S.G. and Stuart, D.G. (eds.), Neural control of locomotion. *Advances in behavioral Biology*, 18, New York: Plenum Press.
- Hertzberg, H.T. E., Daniels, G. S., and Churchill, E., 1954, Anthropometry of flying personnel. WADC Technical Report 52-321, Wright-Patterson Air Force Base, Ohio.
- Huang, H. K., and Suarez, F. R., 1983, Evaluation of cross-sectional geometry and mass density distributions of humans and laboratory animals using computerized tomography. *J. Biomechanics* 16, 821-832.
- Huang, H. K., Weiss, P., Kraft, H. H., and Heidtman, B., 1979, CTIP-An on line CT image processing software package. *Proceedings of the Computer Software and Applications Conference (IEEE)*, 355-361, IEEE Computer Society, Chicago.
- Iida, H., Yamamura, T., 1987, Kinetic analysis of the center-of-gravity of the human body in normal and pathological gait. *J. Biomech.* 20:987-995.

- Imms, F.J., & Edholm, O.G., 1979, The assessment of gait and mobility in the elderly. *Age Aging*, 8, 261-267.
- Imms, F.J., & Edholm, O.G., 1981, Studies of gait and mobility in the elderly. *Age Ageing*, 10, 147-156.
- Inman, V. T., 1966, Human locomotion. *Cdn. Med. Assoc. J.* 94:1047-1054.
- Inman V.T., Ralston H.J. and Todd F., 1981, Human Walking. Baltimore: Williams and Wilkins.
- Irvine, C.H., 1986, Evaluation of the effect of contact-time when measuring floor slip resistance. *J. Test. Eval.*, 1, 19-22.
- Isaacs, B., 1985, clinical and laboratory studies of falls in old people. *Clin. Geriatr. Med.*, 1, 513.
- Isman, R.E. and Inman, V.T., 1969, Anthropometric studies of the human foot and ankle. *Bull. Pros. Res.* 10-11, 97-129.
- James, D.I., 1983, Rubber and plastics in shoe and flooring: The importance of kinetic friction. *Ergonomics*, 26(1), 83-99.
- Jensen, C.R., & Schultz, G.W., 1970, *Applied Kinesiology*. New York: McGraw-Hill Book Company, 275-279.
- Johnston, W., & Packer, A., 1987, *Work force 2000: Work and workers for the twenty-fifth century*. Indianapolis, IN.: Hudson Institute.
- Kenshalo, D.R., 1977, Age changes in touch, vibration, temperature, kinesthesia and pain sensitivity. In Birren, J. E., and Schaie, K.W. (eds.): *Handbook of the Psychology of Aging*. New York: Van Nostrand Reinhold.
- King, B. G., Patch, C. T., and Shinkman, P. G., 1961, Weightlessness-training requirements and solutions. NAVTRADEVCE Technical Report 560-1, Port Washington, New York.
- Kokmen, E., Bossemeyer, R.W., Barney, J., & Williams, W.J., 1977, Neurological manifestations of aging. *J. Gerontol.*, 32, 411-419.
- Kornweigh A.L., 1977, Visual loss in the elderly. *Hosp. Pract.*, 12, 51-59.
- Koller, C.W., Glatt, L.S., & Fox, J.J., 1985, Senile gate: A distinct neurologic entity. *Clinics in Geriatric Med.*, 1, 661-669.
- Kroll, W., & Clarkson, P.M., 1978, Age, isometric knee extension strength, and fractionated resisted response time. *Exp. Aging Res.*, 4, 389-409.

- Kulwicke, P. V., Schlei, E. J., and Vergamini, P. L., 1962, Weightless man: Self-rotation techniques. AMRL Technical documentary Report 62-129.
- Lacour, M., Vidal, P.P., & Xerri, C., 1983, Dynamic characteristics of vestibular and visual control of rapid postural adjustments. In Desmedt, J. (ed.): *Motor Control Mechanisms in Health and Disease*. New York: Raven Press.
- Laidlaw, R.W., & Hamilton, M.A., 1937, A study of thresholds in a perception of passive movement among normal control subjects. *Bull. Neurol. Inst.*, 6, 268-273.
- Larish, D., & Stelmach, G., 1982, Preprogramming, programming, and reprogramming of aimed hand movements as a function of age. *J. Mot. Behav.*, 14, 322-340.
- Larsson, L., 1982, Aging in mammalian skeletal muscle. In Mortimer, J. A., Pirazzolo, P. J., and Meletta, G. J. (eds.): *The Aging Motor System*. New York: Praeger Publishers.
- Larsson, L., Grimby, G., and Karlsson, J., 1979, Muscle strength and speed of movement in relation to age and muscle morphology. *J. Appl. Physiol.*, 46:451-456.
- Lay, W. E., and Fisher, L. C., 1940, Riding comfort and cushions. *SAE Journal* 47 (5): 482-96.
- Leamon, T.B., & Son, D.H., 1989, The natural history of a microslip. *Advanced in Industrial Ergonomics and Safety I*. Taylor & Francis, 633-638.
- Leamon, T.B., & Li, K.W., 1990, Micro length and the perception of slipping. *Proceedings of 23rd International Advanced in Industrial Congress on Occupational Health*, 17.
- Li, K.W., 1991, *A biomechanical study of slipping accidents with load carriage*, Ph. D. Dissertation, Texas Tech University, Lubbock, Texas.
- Lin, L.J., Chiou, F.T. and Cohen, H.H., 1995, Slip and fall accident prevention: A review of research, practice, and regulations. *Journal of Safety Research*, 6, 203-212.
- Lishman, J.R., S& Lee, D.N., 1973, The autonomy of visual kinesthesia. *Perception*, 2, 287-294.
- Lockhart, T.E., 1997, The ability of elderly people to traverse slippery walking surfaces. *Proceedings of the Human Factors and Ergonomics Society 41st Annual Meeting*. 1: 125-129.

- Lishman, J.R., 1981, Vision and the Optic flow field. *Nature*, 293, 263-264.
- Loveless, N.E., 1980, Aging effects in simple RT and voluntary movement paradigms. *Prog. Brain Res.*, 54, 547-551.
- Low, J. and Reed, A., 1996, *Basic Biomechanics Explained*. London, England: Butterworth-Heinemann.
- Luijten, J.A.J., & Feld, H.A., 1993, Slip resistance of soiling materials and top pieces. *Shoe and Allied Trades Research Association*, Information publication, 141.
- Lucht, U., 1971, A prospective study of accidental falls and resulting injuries in the home among elderly people. *Acta Socio-Med. Scand.* 3: 105-120.
- MacKinnon, C.D., 1990, Control of whole body balance and posture in the frontal plane during human walking. M.Sc. Thesis, Univ. Waterloo.
- Majcherczyk, R., 1978, A different approach to measuring pedestrian friction: The CEBTP skidmeter. In C. Anderson & J. Senne (Eds.), *Walkway surfaces: Measurement of slip resistance*, ASTM STP 649 (pp. 88-99). Philadelphia: American Society for Testing and Materials.
- Mankovskii, N., Mints, Y.A., & Lysenyuk, U.P., 1980, Regulation of the preparatory period for complex voluntary movement in old and extreme old age. *Hum. Physiol.*, 6, 46-50.
- Manning, D.P., Ayers, I., Jones, C., Bruce, M., and Cohen, K., 1988, The incidence of underfoot accidents during 1985 in a working population of 10,000 Merseyside people. *Journal of Occupational Accidents*, 10, 121-130.
- Manton, K. G., Stallard, E. and Singor, B. H., 1991, *Future Demographic Trend in Europe and North America. What Can We Assume Today?* London: Academic Press.
- Marey, E.J., 1895, Translated by E.Pritchard. New YorkA: Appleton, Century, Crofts.
- Matsui, H., 1958, A new method to determine the center-of-gravity of a human body by somatometry. *J. Biomech.* 4: 332-336.
- Melvill, J.G., & Watt, D.G.D., 1971(a), Observations on the control of stepping and hopping movements in man. *J. Physiol. (Lond.)*, 219, 709-727.
- Melvill, J.G., & Watt, D.G.D., 1971(b), Muscular control of landing from unexpected falls in man. *J. Physiol. (Lond.)*, 219, 729-737.
- Meserlain, E., 1995, The effects of walking cadence on static COF required by the elderly. *Professional Safety*, 100-110.

- Meyer, H., 1853, Die Mechanik des Kniegelenks. Archiv Fur Anatomie, Physiologie und Wissenschaftliche Medizin 497-547.
- Miller, J.M., 1983, Slippery work surfaces: Towards a performance definition and quantitative COF criteria. *J. of Safety Research*, 14, 145-158.
- Mochon, S., & McMahon, T.A., 1980, Ballistic walking. *J. Biomech.*, 13, 49-57.
- Molen, N.H., Boon, W., 1972, Measurement of momentary velocity in a study of human gait. *J. Biomech.* 5:273-267.
- Morin, A.J., 1835, Nouvelles experiences sur le frottement, *Fait a metz en 1835*, Paris.
- Morton, B.J., & Fuller, B.D., 1952, *Human Locomotion and Body Form*. Baltimore: The Williams and Wilkins Co., 135-166.
- Mosso, A., 1884, Application de la balance a l'etude de la circulation du sang chez l'homme. *Archives italiennes de Biologie* 5:130-43.
- Murray, M.P., Kory, R.C., Clarkson, B.H., & Sepic, S.B., 1966, Comparison of slow and fast speed walking patterns of normal men. *American Journal of Physical Medicine*, 45, 8-24.
- Murray, M.P., Draught, A.B., & Kory, R.C., 1967, Walking patterns of normal men. *J. Bone Joint Surg.*, 46(a), 335-360.
- Murray, M.P., Kory, R.C., Clarkson, B.H., 1969, Walking patterns in healthy old men. *J. Geront.* 24:169-178.
- Murray, M.P., Mollinger, L. a., Gardner, G.M., Sepic, S.B., 1984, Kinematic and EMG patterns during slow, free and fast walking. *J. Orthop. Res.* 2:272-280.
- Myung, R., Smith, J.L., Leamon, T.B., (Submitted). The effects of load carrying and contaminants on slip and fall parameter. *Submitted to Ergonomics*, January, 1996.
- National Institute on Aging, 1991, *Behavioral and Social Research Program: Global Aging. Comparative Indicators and Future Trends*. Washington, DC: US Department of Commerce, Bureau of Census.
- National Research Council, 1961, Causes and measurement of walkway slipperiness (Federal Construction Council, Technical Report No. 43). Washington, DC: National Academy of Sciences - NRC, Publication 899.
- National Safety Council, 1993, *Accidents Facts, 1993 Edition* Itasca, IL: Author.
- National Safety Council, 1995, *Accidents Facts 1995 edition*. Itasca, IL: Author.

- Nashner, L.M., 1973, Vestibular and reflex control of normal standing. In Stein, R.B., Pearson, K.G., Smith, R.S., and Redford, J.B. (eds.): *Control of Posture and Locomotion*, New York: Plenum Press.
- Nashner, L., 1980, Balance adjustments of humans perturbed while walking. *J. Neurophysio.* 44: 650-664.
- Nashner, L.M., 1982, Analysis of movement control in man using the movable platform. In Desmedt, J. (eds.): *Motor Control Mechanisms in Health and Disease*. New York: Raven Press.
- Nashner, L., 1982, Adaptations of human movement to altered environments. *Trends in Neurosci.* 3: 358-361.
- Newman, G., Dovenmuehle, R., & Bass, E., 1960, Alterations in neurologic status with age. *J. Am. Geriatr. Soc.*, 8, 915-917.
- Nickens, H., 1985, Intrinsic factors in falling among the elderly. *Arch. Intern. med.*, 145, 1089-93.
- Ohmichi, H., & Miyashita, M., 1983, Relationship between step length and selected parameters in human gait. *Biomechanics, VIII*, Champaign, IL: Human Kinetics Publishers, 480-484.
- Overstall, P.W., 1978, Falls in elderly: Epidemiology, etiology and management, in Isaacs, B., (ed): *Recent advances in geriatric medicine*. New York: Churchill Livingstone, 61.
- Overstall, P.W., Exton-Smith, A.N., Imms, F.J., & Johnson, A.L., 1977, Falls in the elderly related to postural imbalance. *Br. Med. J.*, 1, 261-264.
- Perkins, P.J., 1978, Measurement of slip between the shoe and ground during walking. American Society of Testing and Materials, *Special Technical Publication* 649, 71-87.
- Perkins, P.J., & Wilson, M.P., 1983, Slip resistance testing of shoes-New developments. *Ergonomics*, 26(1), 73-82.
- Pfauth, M.J. and Miller, J.M., 1976, Work surface friction coefficients: A survey of relevant factors and measurement methodology, *Journal of Safety Research*, 8 (2).
- Pierson, W.R., & Montoye, H.J., 1958, Movement time, reaction time, and age. *J. Gerontol.*, 13, 418-421.

- Plagenhoef, S., 1971, *Patterns of human motion*, Englewood cliffs, N.J.: Prentice-Hall Inc., 18-27.
- Pooley, R.W., 1978, Measurements of frictional properties of footwear sole and heeled materials. *American Society for Testing and Materials*, Special Technical Publication, 649, 11-20.
- Proctor, T.D., & Coleman, V., 1988, Slipping, tripping and falling accidents in Great Britain-present and future. *Journal of Occupational Accidents*, 9, 269-285.
- Prudham, D., Evans, J.G., 1981, Factors associated with falls in the elderly: A community study. *Age Aging* , 10, 141-146.
- Pykett, I. L., 1982, NMR imaging in medicine. *Sci. Am.* 246, 78-88.
- Rabbitt, P., & Rogers, M., 1965, Age and choice between responses in a self-paced repetitive task. *Ergonomics*, 8, 435-444.
- Rabinowicz, E., 1956, Stick and slip. *Scientific American*, 194, 109-118.
- Rhoades, T.P., & Miller, J.M., 1988, Measurement and comparison of “required” Vs. “available” slip resistance. *21st Annual Meeting, Human Factors Association of Canada*, Edmonton, Alberta.
- Richer, P., 1921, Nouvelle anatomie artistique. *Physiologie III: Attituedes et mouvements*. Paris.
- Rice, D. P., Mackenzie, E. J. and Associates, 1989, *Cost of Injury in the United States: A Report to Congress*. San Francisco, Institute for Health and Aging, University of California.
- Rodriguez, D., and Gagnon, M., 1983, The mass and inertia characteristics of the main segments of the human body. In Biomechanics VIII-B. Matsue, H., and Kobayashi, K. (Eds.), 1152-1159, Champaign, IL: Human Kinetics Publishers.
- Rodstein, M., 1964, Accidents among the aged: Incidence, causes and prevention. *J. Chronic Dis.*, 17, 515-518.
- Rubenstein, L.Z., Robbins, A.S., Schulman, B.L., Rosado, J., Osterweil, D., & Josephson, K.R., 1988, Falls and instability in the elderly. *J. Am. Geriatrics Society*, 36, 266-278.
- Ruder, G.K., 1989, *Whole body balance during normal and perturbed walking in the sagittal plane*. M.Sc. Thesis, Univ. Waterloo.

- Salminen, S., Saari, J., Saarela, and Rasanen, 1991, Falls as serious occupational accidents. *Fourth International Conference on Slipping, Tripping and Falling Accidents*, London.
- Sampson, J.B., Morgan, F., Reed, D.W., & Muskat, M., 1943, Studies in lubrication. XII: Friction behavior during the slip portion of the stick-slip process. *Journal of Applied Physics*, 14, 689-700.
- Santschi, W. R., Du Bois, J., and Omoto, C., 1963, Moments of inertia and center of gravity of the living human body. AMRL Technical Documentary Report 63-36.
- Sattin, R.W., 1992, falls among older persons: A public health perspective. *Ann. Rev. Pub. Health*, 13: 489-508.
- Saunders, J.B.D.M., Inman, V.T., Eberhart, H.D., 1953, The major determinants in normal and pathological gait. *J. Bone It. Surg.* 35-A: 543-558.
- Scott, C.J., 1976, Accidents in hospital with special reference to old people. *Health Bull (Edinb)*, 34, 330.
- Serow, W., Sly, D., & Wrigley, J.M., 1990, *Population aging in the United States* New York: Greenwood Press.
- Sheldon, J.H., 1960, On the natural history of falls in old age. *British Medical Journal*, 4, 1685-1690.
- Sheldon, J.H., 1963, The effect of age on the control of sway. *Gerontologia Clinica*, 5, 129.
- Sherman, R.M., 1986, Slip and fall accident prevention simplified. *Professional Safety*, 2, 40-43.
- Shimba, T., 1984, An estimation of the center-of-gravity from force platform data. *J. Biomech.* 17:53-60.
- Skinner, H.B., Barrack, R.L., & Cook, S.D., 1984, Age-related decline in proprioception. *Clin. Orthop.*, 184, 208-211.
- Smallegan, M., 1983, How families decide on nursing-home admission. *Geriatr. Consult.*, 2, 21-25.
- Soames, R.W., Richardson, R.P.S., 1985, Stride length and cadence: Their influence on ground reaction forces during gait. In: D.A. Winter et al. (eds.), *Biomechanics IX*, Human Kinetics Publisher, Champaign, IL., 406-410.
- Soderberg, G. L., Minor, S. D. and Nelson, R. M., 1991, a comparison of motor unit behavior in young and aged subjects, *Age and Aging*, 20, 8-15.

- Son, D., 1990, The effect of postural changes on slip and fall accidents.
- Strandberg, L., and Lanshammar, H., 1981, The dynamics of slipping accidents. *Journal of Occupational Accidents*, 3, 153-162.
- Strandberg, L., 1983, On accident analysis and slip-resistance measurement. *Ergonomics*, 26, 11-32.
- Strandberg, L., and Lanshammar, H., 1985, Walking slipperiness compared to data from friction meters' in Winter, D.A., Norman, R.W., Wells, R.P., Hayes, K.C., and Patla, A.E., (eds) *Biomechanics IX-B*, Champaign, IL: Human Kinetics Publishers, 76-81.
- Steindler, A., 1977, *Kinesiology*. Springfield, IL: Charles C. Thomas Publisher.
- Stelmach, G.E., & Worringham, G.J., 1985, Sensorimotor deficits related to postural stability: Implication for falling in elderly. *Clin. Geriatr. Med.*, 1, 1679.
- Stokes, V.P., Anderson, C., Forssberg, H., 1989, Rotational and translational movement features of the pelvis and thorax during adult human locomotion, *J. Biomech.* 22:43-50.
- Swensen, E., Purswell, J., Schlegel, R., and Stanevich, R., 1992, Coefficient of friction and subjective assessment of slippery work surfaces, *Human Factors*, 34, 67-77.
- Swearingen, J. J., 1962, Determination of centers of gravity of man. Report 62-14, civil Aeromedical Research institute, Federal Aviation Agency, Oklahoma City
- Thorstensson, A., Nilsson, J., Carlson, H., Zomlefer, M.R., 1984, Trunk movements in human locomotion. *Acta Physiol. Scand.* 121: 9-22.
- Thurston, A.J., Whittle, M. W., Stokes, I.A.F., 1981, Spinal and pelvic movement during walking-a new method of study. *Engng. in Med.* 10:219-222.
Oklahoma.
- Tideiksaar, R., 1990, The Biomedical and Environmental Characteristics of Slips, Stumbles, and Falls, *Slips, Stumbles, and Falls: Pedestrian Footwear and Surfaces*, ASTM STP 1103, B. E. Gray, Ed., American Society for Testing and Materials, Philadelphia, 17-27.
- Tinetti, M.E., & Williams, T.F., 1986, Fall risk index for elderly patients based on number of chronic disabilities. *Am. J. Med.*, 80, 429-434.
- Tinetti, M.E., 1987, Factors associated with serious injury during falls by ambulatory nursing home residents. *J. Am. Geriatr. Soc.*, 35, 644-648.

- Tinetti, M.E., Speechley M., & Ginter, S.F., 1988, Risk factors for falls among elderly persons living in the community. *N. Engl. J. Med.*, 319, 1701-1707.
- Tinetti, M.E., & Speechley, M., 1989, Prevention of falls among the elderly. *Medical Intelligence*. 320(16), 1055-1059.
- Tisserand, M., 1969, Criteres d'adherences des semelles de securite. *Disseratation, Institute de Recherche et de Securite*, Nancy.
- Tisserand, M., 1972(a), Adherence statique et dynamique des chaussures de securite. Rapport d'etude No. 11/Re, *Institute de Recherche et de Securite*, Nancy.
- Tisserand, M., 1985, Progress in the prevention of falls caused by slipping, *Ergonomics*, 28-7, 1027-1042.
- Tobis, J.S., Reinsch, S., Swanson, J.M., Byrd, M., & Scharf, T., 1985, Visual perception dominance of fallers among community-dwelling adults. *J. Am. Geriatr. Soc.*, 33, 330-333.
- Weber, W., and Weber, E., 1836, *Mechanik der menschlichen Gehwerkzeuge*. Gottingen.
- Weber, F.R., & Karpovich, P.V., 1964, Electrogoniometric analysis of normal and pathological traits, *Res. Quart.*, 35, 379-384.
- Whitsett, C. E., 1963, Some dynamic response characteristics of weightless man. AMRL Technical Documentary Report 63-18, Wright-Patterson Air Force Base, Ohio.
- Wild, D., Nayak, U.S. L., & Isaacs, B., 1980, Characteristics of old people who fell at home. *J. Clin. Exp. Gerontol.*, 2, 271-287.
- Williams, M., & Lissner, H., 1962, *Biomechanics of Human Motion*, Philadelphia: Saunders Company, 122.
- Winer, B. J., Brown, D. R., and Michels, K. M., 1991, *Statistical Principles in Experimental Design* (3rd. ed.). New York, NY: McGraw-Hill.
- Winter, B.J., 1971, *Statistical principles in experimental design*. 2nd ed., New York: McGraw-Hill.
- Winter, D. A., Patla, A. E., Frank, J. S., and Walt, S. E., 1990, Biomechanical walking pattern changes in the fit and healthy elderly. *Phys. Ther.* 70: 340-347.
- Winter, D.A., 1980, Overall principal of lower limb support during stance phase of gait. *J. Biomech.* 13: 923-927.

- Winter, D.A., 1983a, Energy generation and absorption at the ankle and knee during fast natural and slow cadences. *Clin. Orthop. Rel. Res.*, 175: 147-154.
- Winter, D.A., 1983b, Biomechanical motor patterns in normal walking. *J. Mot. Behav.* 15: 302-330.
- Winter, D.A., 1984, Kinematic kinetic patterns in human gait: Variability and compensating effects. *Hum. Movement Sci.* 3: 51-76.
- Winter, D.A., 1992, Foot trajectory in human gait - a precise and multifactorial control task. *Physiotherapy*, 72: 45-56.
- Winter, D. A., Quanbury, A.O., Reimer, G.D., 1976, Analysis of instantaneous energy of normal gait. *J. Biomech*, 9:253-257.
- Winter, D.A., 1991, *Biomechanics and Motor Control of Human Movement*. (2nd Ed.) John Wiley & Sons, Inc. Toronto, Ontario.
- Winter, D.A., 1992, *Biomechanics of human movement*. 2nd ed., New York: John Wiley & Sons.
- Wolfson, L., Whipple, R., Amerman, P., Kaplan, J. and Kleinberg, A., 1985, Gait and Balance in the Elderly, *Clinics in Geriatric Medicine*, 1-3, 649-659.
- Woolacott, M.H., Sumway-Cook, A., & Nashner, L., 1982, Postural reflexes and aging. In J.A., Mortiner, F.J., Pirozzolo, & G.J., Maletta (Eds.), *The Aging Motor system*. New York: Praeger.
- Woolacott, M.H., 1986, Aging and postural control: Changes in sensory organization and muscular coordination. *Int. J. Aging Hum. Dev.*, 23, 97-101.
- Zatsiorsky, V.M. and Selayanov, V.N., 1983, The mass and inertial characteristics of the main segments of the human body. In *Biomechanics VIII-B* (Edited by Matsui, H. and Kobayshi, K.), pp. 1152-1159. Human Kinetics Publishers, Champaign.
- Zatsiorsky, V.M. and Selayanov, V.N., 1985, Estimation of the mass and inertial characteristics of the human body by means of the best predictive regression equations. In *Biomechanics IX-B* (Edited by Winter, D.A., Norman, R. W., Wells, R.P., Hayes, K.C. and Patla, A.E.), pp. 233-239. Champaign IL: Human Kinetics Publishers.
- Zohar, D., 1978, Why do we bump into things while walking?. *Human Factors*, 20(6), 671-679.

APPENDIX A
PERSONAL DATA AND CONSENT FORM

Personal Data and Consent Form
Texas Tech University

Effects of Musculoskeletal and Sensory Degradation due to Aging on the Biomechanics
of Slips and Falls Date _____

Name _____ Age _____

Sex _____ Height (ft in) _____ Weight (lb) _____

In case of emergency contact: Name _____ Phone _____

Check if susceptible to:

Shortness of breath _____ Dizziness _____ Headaches _____ Fatigue _____

Pain in arm, shoulder or chest _____

If you checked any of the items above, please explain: _____

Have you ever had a heart attack ? _____ If so, give history:

Are you currently taking any type of medication ? _____ If so, please explain:

Have you had or do you now have any problems with your blood pressure ? _____ If
so, please explain: _____

In the last 6 month, have you had any back pain ? _____ If so, please explain:

Have you had or do you now have a hernia ? _____ corrective date:

Have you had or do you have any knee problems ? _____ If so, please explain:

Have you ever experienced slips and falls ? _____ If so, how long ago : _____
please explain: _____

APPENDIX B
CONSENT FORM

Please carefully read and sign the attached consent form.

I have truthfully answered the personal data questions attached to this form to the best of my knowledge. I hereby give my consent form for my participation in the project entitled: "Effects of Musculoskeletal and Sensory Degradation due to Aging on the Biomechanics of Slips and Falls". I understand that the person responsible for this project is: Dr. J. C. Woldstad, telephone number 742-3543. He or his authorized representative, Thurmon Lockhart, 742-3429 has explained that these studies are part of a project that has the following objectives: To investigate the changes in biomechanical parameters and ground reaction forces due to increase in age. Dr. J.C. Woldstad or his authorized representative has agreed to answer any inquires I may have concerning the procedure and has informed me that I may contact the Texas Tech University Institutional Review Board for the Protection of Human Subject by writing them in care of the Office of Research Services, Texas Tech University, Lubbock, Texas 79409, or by calling (806) 742-3884. Information concerning payment for my participation in this study has been explained to me as follows: (a) for participation in the study I will be paid \$10.00 per hour; and (b) I may withdraw from the study at any time. He or his authorized representative has (1) explained the procedure to be followed and identified those which are experimental and (2) described the attendant discomforts and risks. The explained procedure is as follows. Prior to experiments, I will be given an opportunity to walk around the laboratory to familiarize myself with the task at the pace of my normal walking speed. I will be then asked to walk across dry and oily floor while wearing a harness. The risks have been explained to me as follows: muscle sprain or strain, pulled tendons, back pain or strain, hernia, bruises or broken bones if I lose my balance while walking on the floors. It has further been explained to me that the total duration of my participation will be three hours; that only members of the research group will have access to the records and/or data collected for this study; and that all data associated with this study remain strictly confidential. If this research project causes any physical injury to participants in this project, treatment is not necessarily available at Texas Tech University or the Student Health Center, nor is there necessarily any insurance carried by the University or its personnel applicable to cover any such injury. Financial compensation for any such injury must be provided through the participant's own insurance program. Further information about these matters may be obtained from Dr. Robert M. Sweazy, Vice Provost for Research, (806) 742-3884, Room 203 Holden Hall, Texas Tech University, Lubbock, Texas 79409-1035.

I understand that I will not derive therapeutic treatment from participation in this study. I understand that I may discontinue this study at any time I choose without penalty.

Signature of Subject _____ Date: _____

Signature of Project Director or his Authorized Representative: _____ Date: _____

Signature of Witness to Oral Presentation: _____ Date: _____

APPENDIX C
SPECIAL INSTRUCTION FOR SUBJECT

Special Instruction for Subject

(Please read carefully before starting the experiment)

This is an experiment to investigate the changes in biomechanical parameters and ground reaction forces due to increase in age. The objective of this experiment is to measure the cadence effect on different surface conditions with or without contaminant (oil).

Prior to this experiment, you will be given an opportunity to walk around the laboratory wearing a harness to familiarize yourself with the equipment (fall arresting rig), floor surfaces (2) and cadence levels (2). You will then be asked to walk across (with or without the load) on the oily or dry floor surface with different speeds (cadence levels). While you are walking along the path, please keep your eyes on your front and try to maintain the speed that you practiced.

After the familiarization session, you will be asked to walk on specially prepared floor surfaces wearing the harness. The floor surface which you will walk across may or may not be slippery. As you experienced in the familiarization session, you will be arrested of any dangerous slip.

You will also be asked to stand on the NeuroCom balance platform and place your feet in the required position on the platform. No movement of feet on the platform is required. For your safety and confidence you will be asked to wear a safety harness. These testing procedures are not designed to make you lose your balance. One of the procedures requires you to close your eyes, and one will have the force plate you stand on move forward and backward, and also move up and down. You can move your feet between measurements and use the grab bars to maintain your balance between tasks.

APPENDIX D
PILOT TEST

A pilot test was performed to predict the three-dimensional coordinates of the whole body center-of-gravity utilizing the frontal and sagittal plane models during natural walking. According to the method described in the Chapter 3, one person (male, 27 years of age) was fitted with black warm-up suit, and reflective markers were placed on the anatomical landmarks as shown in Figure 3.2 and 3.3. Two Panasonic video recorders were used to collect the three-dimensional coordinates of the subject's anatomical landmarks. During the walking trials, the subject was asked to walk as naturally as possible on the plain plywood platform. The frontal and sagittal models were recorded separately (due to the availability of the video recorders at this time). Two video recorders were synchronized by a light emitting diode connected to the photo-electric switch. Utilizing the APAS software, collected images from the cameras were tracked, digitized and smoothed (cutoff frequency-6 Hz). Afterwards, a computer algorithm written in C++ was use to predict the three-dimensional coordinates of the whole body center-of-gravity in frontal and sagittal planes. Force platforms were not used in this pilot test.

I. The Frontal Model (Trajectory of the Whole Body Center-of-Gravity)

The predicted positions (horizontal [X], lateral [Y], and vertical [Z] trajectories) of the whole body center-of-gravity in the frontal plane are presented in Figures A1.1, A1.2 and A1.3 respectfully. Time elapsed stick figure display of the subject during the walking trial is illustrated in Figure A1.4.

The frontal model predicted approximately 250 cm displacement in X-axis (correspond to the distance traveled in plane of progression). Lateral sway or the position of the whole body center-of-gravity in Y-axis is presented in Figure A1.2. The frontal model predicted approximately 10 cm displacement in Y-axis (correspond to the side-to-side movement of the center-of-gravity). In addition, the frontal model predicted approximately 5 cm displacement in Z-axis (correspond to the up-and-down motion of the center-of-gravity).

Combined positions of the whole body center-of-gravity in frontal plane are presented in Figure A1.5. From HC1 (heel contact, right foot) to HC2 (heel contact, left

foot), the whole body center-of-gravity positions of the Y and Z axis (side-to-side, and up-and-down) resembles typical patterns of center-of-gravity during walking (see Figures 2.9 and 2.12).

The whole body center-of-gravity in Y-axis (lateral oscillations) moves from right to left as each alternate leg becomes weight bearing. It follows a smooth sinusoidal curve, but with only one oscillation per stride as opposed to the two vertical oscillations (Z-axis). At the time of heel contact, the whole body center-of-gravity in Y-axis moves to the side (swing leg). Afterwards, the position of the whole body center-of-gravity attains its greatest distance from the midline shortly after the support of the (now) standing leg (before-swing leg) is shifted to the whole sole (double support). At this point there is an inversion of motion (the velocity is zero, the acceleration is maximal). Figure A1.6 presents the whole body center-of-gravity position in Y-axis as well as the velocity and acceleration profiles. After the period of double support, the velocity increases as the center of gravity approaches the midline.

In Z-axis (up-down), the whole body center-of-gravity is moving up and down. The summits occur at the middle of the stance phases (ms) and lowest point occurs during double support (ds) when both feet are on the ground. At the peak of vertical movement, the velocity reaches a minimum and acceleration reaches a maximum (Figure A1.7). At the time of the heel contact, the whole body center-of-gravity is moving down until complete double stance has been achieved. This downward velocity maybe of interest in assessing slip severity.

Figure A1.1. The position of the whole body center-of-gravity in the frontal plane (X-axis).

Figure A1.2. The position of the whole body center-of-gravity in the frontal plane (Y-axis).

Figure A1.3. The position of the whole body center-of-gravity in frontal plane (Z-axis).

Figure A1.4. Time elapsed stick figure display of the subject during the walking trial (plane of progression [X-axis]).

Figure A1.5. Combined position of the whole body center-of-gravity.

Figure A1.6. The whole body center-of-gravity position in Y-axis as well as the velocity and acceleration profiles. **A**-inversion of motion (velocity minimum, acceleration maximum), **B**-after period of double support (velocity maximum, acceleration minimum), **C**-period of mid stance (only one leg), inversion of motion (velocity minimum, acceleration not quite maximum).

Figure A1.7. The whole body center-of-gravity position in Z-axis as well as the velocity and acceleration profiles. **A**-middle of the stance phase (ms), and inversion of motion (velocity minimum, acceleration maximum), **B**-period of mid stance, before double support (only one leg), velocity maximum and acceleration minimum, **C**- period of double support (velocity minimum, acceleration not quite maximum).

II. The Sagittal Model

The predicted positions of the whole body center-of-gravity in the sagittal plane are presented in Figures A1.8 and A1.9, and the time elapsed stick figure display of the subject during walking trial is illustrated in Figure A1.10. Forward displacement in the plane of progression (X-axis) is illustrated in Figure A1.8. The sagittal model predicted approximately 90 cm displacement in X-axis (correspond to the distance traveled in plane of progression). The position of the whole body center-of-gravity in Z-axis is illustrated in Figure A1.9. The sagittal model predicted approximately 4 cm displacement in Z-axis (correspond to the up-and-down motion of the center-of-gravity). In Z-axis (up-down), the whole body center-of-gravity is moving down (at the heel contact) until complete double stance has been achieved (similar to the frontal model).

Figure A1.8. The position of the whole body center-of-gravity in sagittal plane (X-axis).

Figure A1.9. The position of the whole body center-of-gravity in sagittal plane (Z-axis).

Figure A1.10. Time elapsed stick figure display (in sagittal plane) of the subject during the walking trial (plane of progression [X-axis]).